

Search > Results for Energy, exergy, ... >

MENU

Energy, exergy, economic, environmental analysis for solar still using partia...

[Full text at publisher](#)[Export ▾](#)[Add To Marked List](#)< 1 of 1 >

Energy, exergy, economic, environmental analysis for solar still using partially coated condensing cover with thermoelectric cover cooling

By: Shatar, NM (Shatar, Nursyahirah Mohd) ^[1]; Sabri, MFM (Sabri, Mohd Faizul Mohd) ^[1], ^[2]; Salleh, MFM (Salleh, Mohd Faiz Mohd) ^[3]; Ani, MH (Ani, Mohd Hanafi) ^[4]

[View Web of Science ResearcherID and ORCID](#) (provided by Clarivate)

JOURNAL OF CLEANER PRODUCTION

Volume: 387

Article Number: 135833

DOI: 10.1016/j.jclepro.2022.135833

Published: FEB 10 2023

Early Access: JAN 2023

Indexed: 2023-02-09

Document Type: Article

Abstract:

The declining freshwater resources can be overcome using thermal desalination methods such as solar still. However, the productivity of a solar still is highly dependent on the environment and design. In this study, an improvement of the passive solar still with a partially coated condensation cover and a thermoelectric cooling system was made. The effect of varying thermoelectric cooling power (12 W and 36 W) was investigated and compared with a reference solar still under the tropical weather conditions of Malaysia. The performance of the solar still was analysed in detail based on freshwater yield, energy, exergy, environmental and economic aspects. The results showed that freshwater production could be increased by up to 126% with a 36 W thermoelectric cooling capacity. The energy efficiency improved by 44%, but the exergy efficiency decreased by 25% compared to the reference solar still. The results of the energy matrices show that the minimum energy payback time

and maximum energy production factor for the coated glass solar still are 6.55 years and 0.15, respectively. The amount of carbon dioxide mitigated by the modified solar still was 2.97 tonnes of CO₂ in a lifetime. The lowest cost per litre was found to be \$0.036 with a thermoelectric cooling power of 36 W. The highest exergo-economic and enviro-economic values analysed for the coated glass solar still with thermoelectric cooling were 4.64 kWh/\$ and \$83.21, respectively.

Keywords

Author Keywords: 4E analysis; Combined wettability; Partially coated condensing cover; Solar still; Thermoelectric cooling

Keywords Plus: CONDENSATION SURFACE; WATER; MATRICES

Author Information

Corresponding Address: Sabri, Mohd Faizul Mohd (corresponding author)

▼ Univ Malaya, Fac Engr, Dept Mech Engr, Kuala Lumpur 50603, Malaysia

Addresses:

▼ ¹ Univ Malaya, Fac Engr, Dept Mech Engr, Kuala Lumpur 50603, Malaysia

▼ ² Univ Malaya, Ctr Energy Sci, Kuala Lumpur 50603, Malaysia

▼ ³ Univ Malaya, Fac Engr, Dept Elect Engr, Kuala Lumpur 50603, Malaysia

▼ ⁴ Int Islamic Univ Malaysia, Dept Mfg & Mat, Kulliyah Engr, Kuala Lumpur 50728, Malaysia

E-mail Addresses: faizul@um.edu.my

Categories/ Classification

Research Areas: Science & Technology - Other Topics; Engineering; Environmental Sciences & Ecology

Citation Topics: 7 Engineering & Materials Science > 7.70 Thermodynamics > 7.70.2153 Solar Still

Web of Science Categories: Green & Sustainable Science & Technology; Engineering, Environmental ; Environmental Sciences

Funding

Funding agency	Grant number	Show All Details
Ministry of Education, Malaysia	FRGS/1/2020/TK0/UM/02/10	Show details

[View funding text](#)

+ See more data fields

Journal information

11.072

JOURNAL OF CLEANER PRODUCTION

ISSN: 0959-6526

eISSN: 1879-1786

Current Publisher: ELSEVIER SCI LTD, THE BOULEVARD, LANGFORD LANE,
KIDLINGTON, OXFORD OX5 1GB, OXON, ENGLAND

Journal Impact Factor: Journal Citation Reports™

Research Areas: Science & Technology - Other Topics; Engineering; Environmental
Sciences & Ecology

Web of Science Categories: Green & Sustainable Science & Technology; Engineering,
Environmental; Environmental Sciences

**Journal
Impact Factor
™ (2021)**

1.51

**Journal
Citation
Indicator™
(2021)**

Citation Network

In Web of Science Core Collection

4

Citations



Create citation alert

4

Times Cited in All
Databases

+ See more times
cited

39

Cited References

[View Related Records](#)

Citing items by classification

Breakdown of how this article has been mentioned,
based on available citation context data and
snippets from 1 citing item(s).

Background	0
Basis	0
Support	0
Differ	0
Discuss	1

Most Recently Cited by

Abulkhair, H; Sharshir, SW; Elsheikh, AH; et al.

Use in Web of Science

Web of Science Usage Count

10

Last 180 Days

10

Since 2013

[Learn more](#)

This record is from:

Web of Science Core Collection

- Science Citation Index Expanded (SCI-EXPANDED)

Suggest a correction

If you would like to improve the quality of the data in this record, please Suggest a correction

Thermal performance enhancement of a modified pyramid distiller using different modifications with low-cost materials

SUSTAINABLE ENERGY TECHNOLOGIES AND ASSESSMENTS

Su'ait, MS; Sahudin, MA; Scardi, P; et al.

Potential of transition metal sulfides, $\text{Cu}_2\text{ZnSnS}_4$ as inorganic absorbing layers in dye-sensitized solar cells

JOURNAL OF CLEANER PRODUCTION

See all

39 Cited References

Showing 30 of 39

[View as set of results](#)

(from Web of Science Core Collection)

Portal
Product
Support

Statement
Newsletter

Policy of
Terms of
Use