



Results for ADVANCEMENT I... > Advancement in Electrolyte Materials for Solid Oxide Fuel Cells


[Full text at publisher](#)

Export ▾

Add To Marked List


 < 1 of 1 >


Advancement in Electrolyte Materials for Solid Oxide Fuel Cells

By

[Rabuni, MF](#) (Rabuni, Mohamad Fairus) ^[1]; [Adnan, FH](#) (Adnan, Faidzul Hakim) ^[1]; [Mohd-Noor, F](#) (Mohd-Noor, Faizani) ^[2]; [Bahrudin, FI](#) (Bahrudin, Fadzli Irwan) ^[3]; [Kamarudin, D](#) (Kamarudin, Diyana) ^[4], ^[5]

[View Web of Science ResearcherID and ORCID](#) (provided by Clarivate)

Source

[KOREAN JOURNAL OF CHEMICAL ENGINEERING](#)

[← View Journal Impact](#)

Citation Network

In Web of Science Core Collection

0 Citations

[🔔 Create citation alert](#)

286

Cited References

Volume: 43 Issue: 3 Page: 593-631

DOI: 10.1007/s11814-025-00601-2

Published FEB 2026**Early Access** DEC 2025**Indexed** 2025-12-15**Document Type** Review

Abstract Solid oxide fuel cell (SOFC) electrolytes has advanced from conventional oxide-ion conductors such as YSZ to sophisticated proton-conducting and co-ionic systems. This review synthesises progress across oxide-, proton- and dual-ion-conducting families within a harmonised 500-800 degrees C window, using mainly a single cell-level reporting schema. By centring the comparison at the cell level, we assemble state-of-the-art demonstrations and map them onto a durability framework that makes performance limits and degradation risks explicit. Tables 7 and 8 convert materials insights into stack-relevant guidance, enabling like-for-like benchmarking that is reproducible and decision-oriented. Three messages emerge where oxide-ion systems are the most mature and stack-ready, yet ≤ 650 degrees C operation is constrained by residual ohmic losses and cathode surface-exchange kinetics, even with sub-micrometre membranes. Protonic cells deliver high conductivity and competitive power at 500-650 degrees C but require chemical robustness against CO₂/H₂O to stabilise Ba-containing perovskites. Dual-ion electrolytes spanning engineered semiconductor-ionic heterostructures and composite co-ionic designs achieve attractive outputs near 500-550 degrees C, although long-term stability is constrained by secondary-

[→ View Related Records](#)

How does this document's citation performance compare to peers?

[Open comparison metrics panel](#)

Data is from InCites Benchmarking & Analytics

Use in Web of Science

24 24

Last 180 Days Since 2013

[Learn more →](#)

phase volatility, coarsening and interfacial drift. Architecture and processing are decisive levers: dense ultrathin electrolytes with targeted interlayers, bilayer/multilayer stacks, space-charge/strain-engineered heterostructures and thin-film routes complement scalable tape-casting, screen printing, extrusion and micro-tubular formats. We prioritise chemically robust protonics; stabilised co-ionic systems with engineered interfaces; cathode-electrolyte pairings qualified under realistic fuels and humidities; and standardised reporting that ties electrochemical diagnostics and post-mortem analysis to fade metrics. This framework provides decision-oriented evidence to guide device design, operating policy and scale-up from record single cells to stacks.

Keywords

Author Keywords: SOFC; Electrolyte materials; Oxide-conducting, proton-conducting and dual ion-conducting

Keywords Plus: YTTRIA-STABILIZED-ZIRCONIA; ATOMIC LAYER DEPOSITION; CERIA-CARBONATE COMPOSITE; HIGH-PERFORMANCE; ELECTRICAL-PROPERTIES; DOPED CERIA; CHEMICAL-STABILITY; ELECTROCHEMICAL PROPERTIES; NANOCOMPOSITE ELECTROLYTE; TRANSPORT-PROPERTIES

Author Information

Corresponding Address: Rabuni, Mohamad Adnan, Faidzul Fairus; Hakim (corresponding author)

▼ Univ Malaya, Fac Engr, Sustainable Proc Engr Ctr SPEC, Dept Chem Engr, Kuala Lumpur 50603, Malaysia

E-mail Addresses :

fairus.rabuni@um.edu.my; faidzulhakim.adnan@um.edu.my

Addresses :

▼ ¹ Univ Malaya, Fac Engr, Sustainable Proc Engr Ctr SPEC, Dept Chem Engr, Kuala Lumpur 50603, Malaysia

This record is from:

Web of Science Core Collection

- Science Citation Index Expanded (SCI-EXPANDED)

Suggest a correction

If you would like to improve the quality of the data in this record, please [Suggest a correction](#)

- ▼ ² Univ Teknol Malaysia, Fac Sci, Dept Phys, Skudai 81310, Johor Bahru, Malaysia
 - ▼ ³ Int Islamic Univ, Kulliyah Architecture & Environm Design, Kuala Lumpur 53100, Malaysia
 - ▼ ⁴ Univ Kebangsaan Malaysia, Fac Sci & Technol, Dept Chem Sci, Bangi 43600, Selangor, Malaysia
 - ▼ ⁵ Univ Kebangsaan Malaysia, Fac Sci & Technol, Polymer Res Ctr, Bangi 43600, Selangor, Malaysia
- E-mail Addresses :
- fairus.rabuni@um.edu.my; faidzulkhakim.adnan@um.edu.my;
faizani@utm.my; fadzliirwan@iiium.edu.my; diyana.k@ukm.edu.my

**Categories/
Classification**

Research Areas: Chemistry; Engineering
 Citation Topics [5](#) [Physics](#) > [5.77 Applied](#) > [5.77.285 Solid Oxide Fuel](#)
 : [Physics](#) [Physics](#) [Cell](#)
 Sustainable Development Goals: [07 Affordable and Clean Energy](#)

**Web of Science
Categories**

[Chemistry, Multidisciplinary](#); [Engineering, Chemical](#)

Funding
