

measurement. In Electrical Cell-substrate Impedance Sensing (ECIS) technique, the most notable signal is the peak magnitude of the normalized impedance change. The peak magnitude is related to the effective cell blockage which depends on the cell coverage, cell-substrate contacts and spaces. For biosensing using ECIS, the first step is to characterize the sensor assemblies in appropriate electrolyte solutions at their various stages of construction as well as before and after use in the sensor application, probing the changes which may have occurred. The second is to use the recorded impedance spectra, or a part of them (possibly at only one or two frequencies) to quantitatively measure analytical concentrations of desired electroactive species. In this paper, the strategies and methodologies by which ECIS can be used for characterization and for quantitative measurements in electrochemical sensors and biosensors will be presented and discussed, together with examples to illustrate the advantages and limitations. Then we use the method that involves the use of microelectrode-embedded microwells seeded with DF-1 or animal cell-lines, allowing for continuous measurements of impedance by an Impedance analyzer. Impedance measurements over a wide range of frequency will be performed on these microwells to study the DF-1 cell behavior. We will report the experimental observation of electrode impedance changes caused by cell deposition and growth which affects cell attachments.

P-33 Simulation of a Surface-Transverse Wave (STW) Biosensor for DF-1 Cells

*Anis Nurashikin Nordin, Nadira Jamil, Maizirwan Mel, Ioana Voiculescu, Muhammad Ibrahimy
Electrical and Computer Engineering, Kulliyah of Engineering
International Islamic University Malaysia*

A 250 MHz Surface-Transverse Wave (STW) resonator is employed as a sensor element for the detection of DF-1 cells. STW belongs to the shear-horizontal acoustic plate modes (SH-APM) waves™ family where it has attracted plenty considerable interest. STWs are horizontally polarized shear waves which are generated and detected by the interdigital transducers (IDTs) similar to surface-acoustic wave (SAW) resonators [1]. Detection of chemical and biological agents in aqueous solutions is a difficult problem, especially when the detection technique has to be sensitive, power-efficient and very handy. Acoustic plate mode is a mode of vibration where particle motion is parallel to the surface. This makes it possible to produce a sensitive sensor capable of operating in fluids [2]. This paper presents the biosensor prototype utilizing STW resonator.

P-35 iLukBa ver 1.1: Indoor User Location system with Speech Recognition for Mobile Users

*Teddy Mantoro, Amir Borovac
Department of Computer Science, Kulliyah of Information & Communication Technology
International Islamic University Malaysia*

iLukBa is a prototype to provide a solution for determining indoor symbolic (hierarchical) user location for mobile user. It works with small mobile devices such as PDAs and it is combined with the speech recognition systems on how the environment response delivered to the location of the user. It has been developed using an advanced and robust algorithm in determining user location for indoor environment which offers location precision accuracy in small room scale.

iLukBa capable to handle the unpredictability of IEEE 802.11 (Wifi) signals across perturbation in space, and in time (diurnally) by using Wifi's signal strength. iLukBa also provides direct service delivery when a user on the move from on location to another, the environment response in delivering service is based on the speed of user. Dynamic buffer is created, the buffer size depends on the speed of the user. The faster a user moves, the smaller the buffer in delivering the speech. iLukBa is a proof of concept of a low cost smart environment capability, i.e. indoor user location can be determined and the environment response can be delivered using speech recognition based on indoor user location.

In the long -term, i-LukBa intends to change computing paradigm: provision service directly to where the user is located. The current paradigm is delivering service without knowing the user location and the new paradigm is delivering the service directly to current user location. The service can be in the form of sound/speech, image/graphics (such as jpg or video) or text based

(e-mail,news,micro-blog,etc)

P-37 Bioremediation of oil spills in soil

*Ma'an Alkhatib, Md Zahangir Alam, Iman A.F. Husain
Biotechnology Engineering, Kulliyah of Engineering
International Islamic University Malaysia*

Oil spillage can cause a critical environmental impact on soil. Thus, many technologies have been developed for treating land contaminated by petroleum products. In this project, crude oil contaminated soil will be treated by bioremediation using oil-utilizing bacterial consortium. The bacterial consortium will be isolated from the crude-oil contaminated soil samples, and the best hydrocarbons degrading organisms will be selected for developing the bioremediation process. Water sludge with known composition will be used as nutrient source for the degradation process. The highest growth and hydrocarbon-degradation rate bacteria with the optimum process parameters will be used for the design of the bioremediation process.

P-39 In-situ method to monitor surface reaction / oxidation at high temperature

*Mohd Hanafi Bin Ani, Raihan Othman, Mitsutoshi Ueda, Kenichi Kawamura, Toshio Maruyama
Manufacturing and Materials, Kulliyah of Engineering
International Islamic University Malaysia*

The formation of external Cr_2O_3 scale is important to obtain the oxidation resistance of Fe-Cr alloys at high temperatures. It is well known that the critical concentration of Cr to form protective external scale of Cr_2O_3 in humid condition is higher than that in dry condition, and the criterion of this concentration is expressed as Wagner's equation. To determine this concentration experimentally, a lot of mass gain data and metallographic surveys are required. An in-situ method of continuous monitoring of surface oxygen potential by oxygen concentration cell using stabilized zirconia has been developed and applied to the oxidation of Fe-Cr alloy in order to check the protectiveness of the scale. In our previous work, the oxygen chemical potential on growing oxide scales during high temperature oxidation of Fe, Ni, and Co were successfully measured. In this study, the surface oxygen potentials of Fe-0~17 wt% Cr alloys in Ar-21% O_2 gas as dry condition and Fe-10~22 wt% Cr alloys in Ar-20% O_2 -20% H_2O gas as humid condition were measured at 1073 K up to 20 ks.

In dry condition, the surface oxygen potentials of Fe with more than 10 wt% Cr alloys were close to the oxygen potential of atmosphere immediately after the heating period. It indicates that protective Cr_2O_3 scale formed on these alloys at early stage of oxidation. However, the surface oxygen potentials of these same composition alloys were lower in humid condition than that in dry. By this method, the protectiveness of scales formed on Fe-Cr alloys can be evaluated in-situ in a few hours.

P-42 Molecular Characterization of Malaysian Ginger (Zingiber officinale Rosc.)

*Julia Retno Andayani Budi Muljono, Ishak, Mahdi H. J., Retno A. Budi Muljono
Pharmaceutical Chemistry, Kulliyah of Pharmacy
International Islamic University Malaysia*

The genetic polymorphisms among *Zingiber officinale* Rosc. (= *halia*) from Bukit Tinggi (BT), Tanjung Sepat (TS and Sabah (SB) cultivars of were studied using a single microsatellite oligo-primers: (CATA)5, (GATA)5 and (GAC)6 as DNA molecular markers in the polymerase chain reaction (PCR). Seven polymorphic bands were obtained from the PCR products, with in average about 2.334 polymorphic bands per primer, leading to a polymorphic rate of 17.9 %. Jaccard's coefficient of similarity varied from 0.562 to 0.875, indicative of close genetic relatedness among the genotype studied. UPGMA clustering indicated that the BT ginger cv. more related genetically to the TS cv. compared to the SB ginger. A putative new gene was observed from the DNA sequencing of the polymorphic bands of TS