

ADVANCED MACHINING TOWARDS IMPROVED MACHINABILITY OF DIFFICULT-TO-CUT MATERIALS

Edited by:

A.K.M. Nurul Amin (Chief Editor)

Dr. Erry Yulian Triblas Adesta

Dr. Mohammad Yeakub Ali



IIUM PRESS

INTERNATIONAL ISLAMIC UNIVERSITY MALAYSIA


ADVANCED MACHINING
TOWARDS IMPROVED MACHINABILITY OF
DIFFICULT-TO-CUT MATERIALS

Edited by:

A.K.M. Nurul Amin (Chief Editor)

Dr. Erry Yulian Triblas Adesta

Dr. Mohammad Yeakub Ali



IIUM Press

Published by:
IIUM Press
International Islamic University Malaysia

First Edition, 2011
©IIUM Press, IIUM

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without any prior written permission of the publisher.

Perpustakaan Negara Malaysia

Cataloguing-in-Publication Data

Advanced Machining Towards Improved Machinability of Difficult-To-Cut Materials: A.K.M.
Nurul Amin, Erry Yulian Triblas Adesta & Mohammad Yeakub Ali

ISBN: 978-967-418-175-8

Member of Majlis Penerbitan Ilmiah Malaysia – MAPIM
(Malaysian Scholarly Publishing Council)

Printed by :
IIUM PRINTING SDN.BHD.
No. 1, Jalan Industri Batu Caves 1/3
Taman Perindustrian Batu Caves
Batu Caves Centre Point
68100 Batu Caves
Selangor Darul Ehsan
Tel: +603-6188 1542 / 44 / 45 Fax: +603-6188 1543
EMAIL: iiumprinting@yahoo.com

SECTION A: HEAT ASSISTED MACHINING	1
1. CHAPTER 1: INFLUENCE OF WORKPIECE PREHEATING ON CHATTER AND MACHINABILITY OF TITANIUM LOY - TI6AL4V	1
2. CHAPTER 2: MACHINABILITY IMPROVEMENT IN END OF MILLING TITANIUM ALLOY TI-6AL-4V THROUGH PREHEATING	9
3. CHAPTER 3: SOME ASPECTS OF IMPROVED MACHINABILITY IN PREHEATED MACHINING OF TITANIUM ALLOY TI-6AL-4V	19
4. CHAPTER 4: MACHINABILITY ASPECTS IN HEAT ASSISTED MACHINING OF HARDENED STEEL AISI H13 USING COATED CARBIDE TOOL	27
5. CHAPTER 5: TOOL WEAR AND SURFACE ROUGHNESS ASPECTS IN HEAT ASSISTED END MILLING OF AISI D2 HARDENED STEEL	35
6. CHAPTER 6: MODELING IN PREHEATED MACHINING OF AISI D2 HARDENED STEEL	43
7. CHAPTER 7: RELATIVE PERFORMANCES OF PREHEATING, CRYOGENIC COOLING AND HYBRID TURNING OF STAINLESS STEEL AISI 304	49
SECTION B: CHATTER AND SELECTED METHODS OF CHATTER SUPPRESSION	57
8. CHAPTER 8: ROLE OF THE FREQUENCY OF SECONDARY SERRATED TEETH IN CHATTER FORMATION DURING TURNING OF CARBON STEEL AISI 1040 AND STAINLESS STEEL	57
9. CHAPTER 9: INFLUENCE OF THE ELASTIC SYSTEM AND CUTTING PARAMETERS ON CHATTER DURING MACHINING OF MILD STEEL	65
10. CHAPTER 10: INFLUENCE OF CHATTER ON TOOL LIFE DURING END MILLING OF ALUMINIUM AND ALUMINIUM ALLOY ON VMC	75

11	CHAPTER 11: A NEW METHOD FOR CHATTER SUPPRESSION AND IMPROVEMENT OF SURFACE ROUGHNESS IN END MILLING OF MILD STEEL	83
12	CHAPTER 12: APPLICATION OF PERMANENT ELECTROMAGNET FOR CHATTER CONTROL IN END MILLING OF MEDIUM CARBON STEEL	91
13	CHAPTER 13: APPLICATION OF PERMANENT ELECTROMAGNET FOR CHATTER CONTROL IN END MILLING OF TITANIUM ALLOY - Ti6Al4V	99
14	CHAPTER 14: CHATTER SUPPRESSION IN END MILLING OF TITANIUM ALLOY Ti6Al4V APPLYING PERMANENT MAGNET CLAMPED ADJACENT TO THE WORKPIECE	107
	SECTION C: MODELING AND OPTIMIZATION IN MACHINING	117
15	CHAPTER 15: A COUPLED ARTIFICIAL NEURAL NETWORK AND RSM MODEL FOR THE PREDICTION OF CHIP SERRATION FREQUENCY IN END MILLING OF INCONEL 718	117
16	CHAPTER 16: APPLICATION OF RESPONSE SURFACE METHODOLOGY COUPLED WITH GENETIC ALGORITHM FOR SURFACE ROUGHNESS OF INCONEL 718	123
17	CHAPTER 17: DEVELOPMENT OF A MATHEMATICAL MODEL FOR THE PREDICTION OF SURFACE ROUGHNESS IN END MILLING OF STAINLESS STEEL SS 304	133
18	CHAPTER 18: DEVELOPMENT OF AN ARTIFICIAL NEURAL NETWORK ALGORITHM FOR PREDICTING THE CUTTING FORCE IN END MILLING OF INCONEL 718 ALLOY	143
19	CHAPTER 19: DEVELOPMENT OF AN ARTIFICIAL NEURAL NETWORK ALGORITHM FOR PREDICTING THE SURFACE	149
20	CHAPTER 20: DEVELOPMENT OF TOOL LIFE PREDICTION MODEL OF TiAlN COATED TOOLS DURING PART C: HIGH SPEED HARD MILLING OF AISI H13 STEEL	155
21	CHAPTER 21: MODELING FOR SURFACE ROUGHNESS IN END-MILLING OF TITANIUM ALLOY Ti-6Al-4V USING UNCOATED WC INSERTS	161

22	CHAPTER 22: MODELING OF SURFACE ROUGHNESS DURING END MILLING OF AISI H13 HARDENED TOOL STEEL	167
23	CHAPTER 23: MODELING OF TOOL LIFE USING RESPONSE SURFACE METHODOLOGY IN HARD MILLING OF AISI D2 TOOL STEEL	175
24	CHAPTER 24: OPTIMIZATION OF SURFACE ROUGHNESS IN HIGH SPEED END MILLING OF TITANIUM ALLOY Ti-6Al-4V UNDER DRY CONDITION	181
25	CHAPTER 25: COMPARISON OF SURFACE ROUGHNESS IN END-MILLING OF TITANIUM ALLOY TI-6AL-4V USING UNCOATED WC-CO AND PCD INSERTS THROUGH GENERATION OF MODELS	189
26	CHAPTER 26: ASSESSMENT OF PERFORMANCE OF UNCOATED AND COATED CARBIDE INSERTS IN END MILLING OF TI-6AL-4V THROUGH MODELLING	195
	SECTION D: CRYOGENIC AND HIGH SPEED MACHINING OF METALS AND NON METALS	203
27	CHAPTER 27: THE EFFECT OF CRYOGENIC COOLING ON MACHINABILITY OF STAINLESS STEEL DURING TURNING	203
28	CHAPTER 28: COMPARISON OF MACHINABILITY OF CERAMIC INSERT IN ROOM TEMPERATURE AND CRYOGENIC COOLING CONDITIONS DURING END MILLING INCONEL 718	209
29	CHAPTER 29: HIGH SPEED END MILLING OF SINGLE CRYSTAL SILICON SING DIAMOND COATED TOOL	217
30	CHAPTER 30: IMPLEMENTATION OF HIGH SPEED OF SILICON USING DIAMOND COATED TOOLS WITH AIR BLOWING	225
31	CHAPTER 31: ELIMINATION OF BURR FORMATION DURING END MILLING OF POLYMETHYL METHACRYLATE (PMMA) THROUGH HIGH SPEED MACHINING	233
32	CHAPTER 32: WEAR MECHANISMS IN END MILLING OF INCONEL 718	239

33	CHAPTER 33: PERFORMANCE OF UNCOATED WC-CO INSERTS IN END MILLING OF ALUMINUM SILICON CARBIDE (ALSiC)	247
34	CHAPTER 34: APPLICATION OF PCD INSERTS IN END MILLING OF ALUMINUM SILICON CARBIDE (ALSIC)	253
35	CHAPTER 35: EFFECTS OF SCRIBING WHEEL DIMENSIONS ON LCD GLASS CUTTING	259

Development of a Mathematical Model for the Prediction of Surface Roughness in End Milling of Stainless Steel SS 304

A.K.M. Nurul Amin¹, Asif Mahmood¹

¹Faculty of Engineering – International Islamic University Malaysia

e-mail address of the corresponding author: akamin@iiu.edu.my

1.0 INTRODUCTION

The use of advanced computer-based systems for the selection of optimum conditions of mechanical components during process planning becomes essential for today's complex products. Computer aided manufacturing (CAM) has widely been implemented to obtain more accurate machining data and to ensure that optimum production is achieved. Machinability of a material provides an indication of its adaptability to be manufactured by a machining process. In general, machinability can be defined as an optimal combination of factors such as low cutting force, high material removal rate, good surface integrity, accurate and consistent workpiece geometrical characteristics, low tool wear rate and good curl or breakdown of chips.

In machinability studies investigations, statistical design of experiments is used quite extensively. Statistical design of experiments refers to the process of planning the experiment so that the appropriate data can be analyzed by statistical methods, resulting in valid and objective conclusions [1]. Design and methods such as factorial design, response surface methodology (RSM) and Taguchi methods are now widely use in place of one-factor-at-a-time experimental approach which is time consuming and exorbitant in cost. A machinability model may be defined as a functional relationship between the input of independent cutting variables (speed, feed, depth of cut) and the output known as responses (tool life, surface roughness, cutting force, etc) of a machining process [2]. Response surface methodology (RSM) is a combination of experimental and regression analysis and statistical inference. RSM is a dynamic and foremost important tool of design of experiment (DOE), wherein the relationship between response(s) of a process with its input decision variables is mapped to achieve the objective of maximization or minimization of the response properties [3]. Many machining researchers have used response surface methodology to design their experiments and assess results. Kaye et al [4] used response surface methodology in predicting tool flank wear using spindle speed change. A unique model has been developed which predicts tool flank wear, based on the spindle speed change, provided the initial flank wear at the beginning of the normal cutting stage is known. An empirical equation has also been derived for calculating the initial flank wear, given the speed, feed rate, depth of cut and workpiece hardness. Alauddin et al [5] applied response surface methodology to optimize the surface finish in end milling of Inconel 718 under dry condition