

Scopus

## Document details

[< Back to results](#) | 1 of 1[Export](#) [Download](#) [Print](#) [E-mail](#) [Save to PDF](#) [Add to List](#) [More... >](#)[Full Text](#) [View at Publisher](#)Industrial Crops and Products  
Volume 54, March 2014, Pages 291-295

## Optimizing the parameters in durian skin fiber reinforced polypropylene composites by response surface methodology (Article)

Aimi, N.N.<sup>a</sup>, Anuar, H.<sup>a</sup> , Manshor, M.R.<sup>ab</sup>, Nazri, W.B.W.<sup>b</sup>, Sapuan, S.M.<sup>c</sup> <sup>a</sup>Department of Manufacturing and Materials Engineering, Faculty of Engineering, International Islamic University Malaysia, Jalan Gombak, 53100 Kuala Lumpur, Malaysia<sup>b</sup>Food Technology Research Center, Malaysian Agriculture Research and Development Institute (MARDI), 43400 Serdang, Malaysia<sup>c</sup>Department of Mechanical and Manufacturing Engineering, Universiti Putra Malaysia (UPM), 43400 Serdang, Selangor, Malaysia

## Abstract

[View references \(20\)](#)

Awareness on the advantages of natural fibers stimulates the interest of researchers to use them as reinforcement in polymer composites for robust application. Therefore, investigation on optimizing the impact property of durian skin fiber (DSF) reinforced polypropylene (PP) composites was carried out to determine the effect of DSF content, fiber size and maleic anhydride polypropylene (MAPP) content. Response surface methodology (RSM) was used in the design of experiments and in the analysis of results. The optimized value for the maximum impact strength of PP-DSF composite was found at 50wt% DSF content and fiber size range of 250-500 $\mu$ m with 0wt% MAPP. The maximum impact property for PP-DSF composite was 10.66kJ/m<sup>2</sup>. From the analysis of variance (ANOVA), fiber content significantly affects the strength of PP-DSF composites, followed by the fiber size and MAPP content. The P-value of the model of experiment is less than 0.05 and the determination coefficient ( $R^2$ ) is nearly 1 which suggested that the model is significant and implies on the precision and processability in the production. © 2014 Elsevier B.V.

## Author keywords

Durian skin fiber Impact property Optimization Response surface methodology (RSM)

ISSN: 09266690

CODEN: ICRDE

Source Type: Journal

Original language: English

DOI: 10.1016/j.indcrop.2014.01.016

Document Type: Article

## References (20)

[View in search results format >](#) All [Export](#) [Print](#) [E-mail](#) [Save to PDF](#) [Create bibliography](#)Metrics  [View all metrics >](#)

9 Citations in Scopus

80th Percentile

1.97 Field-Weighted

Citation Impact

PlumX Metrics Usage, Captures, Mentions,  
Social Media and Citations  
beyond Scopus.

## Cited by 9 documents

Soda-Anthraquinone Durian (Durio Zibethinus Murr.) Rind Linerboard and Corrugated Medium Paper: A Preliminary Test

Masrol, S.R. , Ibrahim, M.H.I. , Adnan, S. (2017) *IOP Conference Series: Materials Science and Engineering*

Effects of total chlorine free (TCF) bleaching on the characteristics of Chemi-Mechanical (CMP) pulp and paper from Malaysian durian (Durio Zibethinus Murr.) rind

Masrol, S.R. , Ibrahim, M.H.I. , Adnan, S. (2017) *Jurnal Teknologi*

Melt volume flow rate and melt flow rate of kenaf fibre reinforced Floreon/magnesium hydroxide biocomposites

Lee, C.H. , Sapuan, S.M. , Lee, J.H. (2016) *SpringerPlus*[View all 9 citing documents](#)

Inform me when this document is cited in Scopus:

[Set citation alert >](#)[Set citation feed >](#)

- 1 Arbelaz, A., Fernández, B., Ramos, J.A., Retegi, A., Llano-Ponte, R., Mondragon, I.  
**Mechanical properties of short flax fibre bundle/polypropylene composites: Influence of matrix/fibre modification, fibre content, water uptake and recycling**  
 (2005) *Composites Science and Technology*, 65 (10), pp. 1582-1592. Cited 260 times.  
 doi: 10.1016/j.compscitech.2005.01.008  
[View at Publisher](#)
- 
- 2 Bangphan, S., Bangphan, P., Boonkang, T.  
 Implementation of response surface methodology using in small brown rice peeling machine: Part I  
 (2013) *World Acad. Sci. Eng. Technol.*, 74, pp. 611-615.
- 
- 3 Biagiotti, J., López-Manchado, M.A., Arroyo, M., Kenny, J.M.  
**Ternary Composites Based on PP-EPDM Blends Reinforced With Flax Fibers. Part II: Mechanical Properties/Morphology Relationship**  
 (2003) *Polymer Engineering and Science*, 43 (5), pp. 1031-1043. Cited 13 times.  
[View at Publisher](#)
- 
- 4 Canché-Escamilla, G., Rodriguez-Laviada, J., Cauich-Cupul, J.I., Mendizábal, E., Puig, J.E., Herrera-Franco, P.J.  
**Flexural, impact and compressive properties of a rigid-thermoplastic matrix/cellulose fiber reinforced composites**  
 (2002) *Composites - Part A: Applied Science and Manufacturing*, 33 (4), pp. 539-549. Cited 63 times.  
 doi: 10.1016/S1359-835X(01)00136-1  
[View at Publisher](#)
- 
- 5 Charoenvai, S., Khedari, J., Hirunlabh, J., Daguene, M., Quenard, M.  
 Impact of rice husk ash on the performance of durian fiberbased construction materials  
 (2005) *10th DBMC International Conference on Durability of Building Materials and Components*. Cited 3 times.  
 Retrieved from  
<http://www.cstb.fr/fileadmin/documents/publicationsScientifiques/DOC00003448.pdf>
- 
- 6 El-Sabbagh, A.  
**Effect of coupling agent on natural fibre in natural fibre/polypropylene composites on mechanical and thermal behaviour**  
 (2014) *Composites Part B: Engineering*, 57, pp. 126-135. Cited 49 times.  
 doi: 10.1016/j.compositesb.2013.09.047  
[View at Publisher](#)
- 
- 7 Amri, F., Husseinsyah, S., Hussin, K.  
**Mechanical, morphological and thermal properties of chitosan filled polypropylene composites: The effect of binary modifying agents**  
 (2013) *Composites Part A: Applied Science and Manufacturing*, 46 (1), pp. 89-95. Cited 16 times.  
 doi: 10.1016/j.compositesa.2012.10.014  
[View at Publisher](#)
- 
- 8 Folkes, M.J.  
 (1982) *Short Fiber Reinforced Thermoplastics*. Cited 270 times.  
 John Wiley & Sons, Britain

## Related documents

On the robust parameter design  
 Noorossanatp, R. , Ardakanitp, M.K.  
 (2007) *37th International Conference on Computers and Industrial Engineering 2007*

Durian husk as potential source for particleboard industry  
 Zddin, Z. , Risby, M.S.  
 (2010) *AIP Conference Proceedings*

Improvement in mechanical properties of reinforced thermoplastic elastomer composite with kenaf bast fibre

Anuar, H. , Zuraida, A.  
 (2011) *Composites Part B: Engineering*

[View all related documents based on references](#)

Find more related documents in Scopus based on:

Authors > Keywords >

- 
- 9 Foo, K.Y., Hameed, B.H.  
Transformation of durian biomass into a highly valuable end commodity: Trends and opportunities  
(2011) *Biomass and Bioenergy*, 35 (7), pp. 2470-2478. Cited 9 times.  
doi: 10.1016/j.biombioe.2011.04.004  
[View at Publisher](#)
- 
- 10 Khedari, J., Charoenvai, S., Hirunlabh, J.  
New insulating particleboards from durian peel and coconut coir  
(2003) *Building and Environment*, 38 (3), pp. 435-441. Cited 109 times.  
doi: 10.1016/S0360-1323(02)00030-6  
[View at Publisher](#)
- 
- 11 Manshor, R.M., Anuar, H., Wan Nazri, W.B., Ahmad Fitrie, M.I.  
Preparation and characterization of physical properties of durian skin fibers biocomposite  
(2012) *Advanced Materials Research*, 576, pp. 212-215. Cited 3 times.  
<http://www.scientific.net/AMR.576.212>  
ISBN: 978-303785498-3  
doi: 10.4028/www.scientific.net/AMR.576.212  
[View at Publisher](#)
- 
- 12 Zahedi, M., Pirayesh, H., Khanjanzadeh, H., Tabar, M.M.  
Organo-modified montmorillonite reinforced walnut shell/polypropylene composites  
(2013) *Materials and Design*, 51, pp. 803-809. Cited 14 times.  
doi: 10.1016/j.matdes.2013.05.007  
[View at Publisher](#)
- 
- 13 Myers, R.H., Montgomery, D.C.  
(2002) *Response Surface Methodology*. Cited 9105 times.  
Wiley, New York
- 
- 14 Myers, R.H., Montgomery, D.C., Geoffrey Vining, G., Borror, C.M., Kowalski, S.M.  
Response Surface Methodology: A Retrospective and Literature Survey  
(2004) *Journal of Quality Technology*, 36 (1), pp. 53-78. Cited 203 times.
- 
- 15 Ayrlimis, N., Kaymakci, A., Ozdemir, F.  
Physical, mechanical, and thermal properties of polypropylene composites filled with walnut shell flour  
(2013) *Journal of Industrial and Engineering Chemistry*, 19 (3), pp. 908-914. Cited 23 times.  
doi: 10.1016/j.jiec.2012.11.006  
[View at Publisher](#)
- 
- 16 Raissi, S.R., Farsani, E.  
Statistical process optimization through multi-response surface methodology  
(2009) *World Acad. Sci. Eng. Technol.*, 51, pp. 267-271. Cited 40 times.
-

- 17 Tanyildizi, M.S., Özer, D., Elibol, M.  
 Optimization of  $\alpha$ -amylase production by *Bacillus* sp. using response surface methodology  
 (2005) *Process Biochemistry*, 40 (7), pp. 2291-2296. Cited 220 times.  
 doi: 10.1016/j.procbio.2004.06.018  
[View at Publisher](#)
- 
- 18 Wang, Y.-H., Feng, J.-T., Zhang, Q., Zhang, X.  
 Optimization of fermentation condition for antibiotic production by *Xenorhabdus nematophila* with response surface methodology  
 (2008) *Journal of Applied Microbiology*, 104 (3), pp. 735-744. Cited 25 times.  
 doi: 10.1111/j.1365-2672.2007.03599.x  
[View at Publisher](#)
- 
- 19 Yang, H.-S., Kim, H.-J., Son, J., Park, H.-J., Lee, B.-J., Hwang, T.-S.  
 Rice-husk flour filled polypropylene composites; mechanical and morphological study  
 (2004) *Composite Structures*, 63 (3-4), pp. 305-312. Cited 250 times.  
 doi: 10.1016/S0263-8223(03)00179-X  
[View at Publisher](#)
- 
- 20 Zafari, A., Kianmehr, M.H., Abdolazadeh, R.  
 Modeling the effect of extrusion parameters on density of biomass pellet using artificial neural network  
 (2013) *International Journal of Recycling of Organic Waste in Agriculture*, 2 (1), art. no. 9, p. 11. Cited 5 times.  
[www.springer.com/environment/pollution+and+remediation/journal/40093](http://www.springer.com/environment/pollution+and+remediation/journal/40093)  
 doi: 10.1186/2251-7715-2-9  
[View at Publisher](#)

👤 Anuar, H.; Department of Manufacturing and Materials Engineering, Faculty of Engineering, International Islamic University Malaysia, Malaysia; email:hazleen@iiu.edu.my  
 © Copyright 2014 Elsevier B.V., All rights reserved.

< Back to results | 1 of 1

^ Top of page

## About Scopus

What is Scopus  
 Content coverage  
 Scopus blog  
 Scopus API  
 Privacy matters

## Language

日本語に切り替える  
 切换到简体中文  
 切换到繁體中文  
 Русский язык

## Customer Service

Help  
 Contact us

ELSEVIER

[Terms and conditions](#) [Privacy policy](#)

Copyright © 2017 Elsevier B.V. All rights reserved. Scopus® is a registered trademark of Elsevier B.V.

Cookies are set by this site. To decline them or learn more, visit our [Cookies page](#).

RELX Gr