

Document details

< Back to results | 1 of 1

Export Download Print E-mail Save to PDF Add to List More...

Full Text View at Publisher

Conference Record - IEEE Instrumentation and Measurement Technology Conference  
Volume 2016-July, 22 July 2016, Article number 7520343  
2016 IEEE International Instrumentation and Measurement Technology Conference, I2MTC 2016; Taipei International Convention CenterTaipei; Taiwan; 23 May 2016 through 26 May 2016; Category numberCFP16IMT-ART; Code 122785

Resonant coils analysis for inductively coupled wireless power transfer applications (Conference Paper)

Nataraj, C., Khan, S., Habaebi, M.H., Muthalif, A.G.A., Arshad, A.  
Department of Electrical and Computer Engineering, International Islamic University Malaysia, Malaysia

Abstract

View references (18)

This paper proposes Wireless Power Transfer (WPT) system, consisting of transmitter-receiver coils along with some conditioning and stabilizing circuits. The transmitter circuit is designed with a simple H bridge circuit to supply the pulses to source coil. The efficiency variation or performance with respect to the coil size has been demonstrated in this paper, which is not well demonstrated experimentally in the past. It is about an inductive link efficiency calculation as a function of the geometrical dimensions. The efficiency has been derived analytically, and analytical results are validated experimentally. From the results observed the effect of geometrical dimensions (area, distance, shape, and size) is explored. The performance analysis evaluated analytically against experimentally, infers that the inductive coupling with same sized coil has achieved maximum power transfer wirelessly, for a shorter distance with applied input voltage of 24 V at resonance frequency of 180 kHz. This proposed system is practically tested for applications such as charging of devices or providing wireless sensor networks with energy supplied. The results have got useful utility for Electric Vehicles automobile industry. © 2016 IEEE.

Author keywords

Inductive coupling power transfer efficiency resonant coils wireless power transfer

Indexed keywords

|                               |                               |                     |                            |                           |
|-------------------------------|-------------------------------|---------------------|----------------------------|---------------------------|
| Engineering controlled terms: | Automotive industry           | Bridge circuits     | Electromagnetic coupling   | Electromagnetic induction |
|                               | Reconfigurable hardware       | Transmitters        | Wireless sensor networks   |                           |
| Compendex keywords            | Geometrical dimensions        | Inductive couplings | Maximum power transfer     |                           |
|                               | Power transfer efficiency     | resonant coils      | Transmitter-receiver coils | Wireless power transfer   |
|                               | Wireless power transfer (WPT) |                     |                            |                           |
| Engineering main heading:     | Inductive power transmission  |                     |                            |                           |

ISSN: 10915281  
ISBN: 978-146739220-4  
CODEN: CRIIE  
Source Type: Conference Proceeding  
Original language: English

DOI: 10.1109/I2MTC.2016.7520343  
Document Type: Conference Paper  
Sponsors: IEEE,IEEE Instrumentation and Measurement Society  
Publisher: Institute of Electrical and Electronics Engineers Inc.

Metrics View all metrics

3 Citations in Scopus  
86th Percentile  
2.93 Field-Weighted Citation Impact

PlumX Metrics  
Usage, Captures, Mentions, Social Media and Citations beyond Scopus.

Cited by 3 documents

- Design of simple DC-to-DC Wireless Power Transfer via inductive coupling  
Nataraj, C. , Khan, S. , Eniola, F.F. (2017) *Proceedings of the 3rd IEEE International Conference on Advances in Electrical and Electronics, Information, Communication and Bio-Informatics, AEEICB 2017*
- Analysis of mutual inductance and coupling factor of inductively coupled coils for Wireless electricity  
Nataraj, C. , Khan, S. , Habaebi, M.H. (2017) *ARPN Journal of Engineering and Applied Sciences*
- Hybrid of conical and spiral approach for Wireless Power Transfer  
Nataraj, C. , Khan, S. , Habaebi, M.H. (2017) *Proceedings - 14th IEEE Student Conference on Research and Development: Advancing Technology for Humanity, SCOREd 2016*

View all 3 citing documents

Inform me when this document is cited in Scopus:  
Set citation alert > Set citation feed >

☐ All
 [Export](#)
[Print](#)
[E-mail](#)
[Save to PDF](#)
[Create bibliography](#)

- ☐ 1 Kiani, M., Ghovanloo, M.  
**The circuit theory behind coupled-mode magnetic resonance-based wireless power transmission**  
 (2012) *IEEE Transactions on Circuits and Systems I: Regular Papers*, 59 (9), art. no. 6138883, pp. 2065-2074. Cited 191 times.  
 doi: 10.1109/TCSI.2011.2180446  
[View at Publisher](#)

- ☐ 2 Goldstein, S.C., Stancil, D.D.  
**Magnetic Resonant Coupling As a Potential Means for Wireless Power Transfer to Multiple Small Receivers**  
 (2009) *IEEE Transactions on Power Electronics*, 24 (7), pp. 1819-1825. Cited 462 times.  
 doi: 10.1109/TPEL.2009.2017195  
[View at Publisher](#)

- ☐ 3 Jiang, B., Smith, J.R., Philipose, M., Roy, S., Sundara-Rajan, K., Mamishev, A.V.  
**Energy scavenging for inductively coupled passive RFID systems**  
 (2007) *IEEE Transactions on Instrumentation and Measurement*, 56 (1), pp. 118-125. Cited 73 times.  
 doi: 10.1109/TIM.2006.887407  
[View at Publisher](#)

- ☐ 4 Khan, S., Khan, I.M., Bahri, N.A.R.B., Saad, N.W.B.M.  
**Modeling of readout circuit for acquisition of sensory signal through non-contact means**  
 (2012) *2012 International Conference on Computer and Communication Engineering, ICCCE 2012*, art. no. 6271238, pp. 504-509.  
 ISBN: 978-146730478-8  
 doi: 10.1109/ICCCE.2012.6271238  
[View at Publisher](#)

- ☐ 5 Chang, W.-Y., See, K.-Y., Hu, B.  
**Characterization of component under DC biasing condition using an inductive coupling approach**  
 (2010) *IEEE Transactions on Instrumentation and Measurement*, 59 (8), art. no. 5286223, pp. 2109-2114. Cited 9 times.  
 doi: 10.1109/TIM.2009.2031850  
[View at Publisher](#)

- ☐ 6 Moez Khan, I.  
**(2013) Wireless Transfer of Low Power for Low Voltage Implanted Biomedical Devices-Coil Design Consideration**  
 M.Sc Thesis, IIUM, Selangor, Malaysia, 5 April

- ☐ 7 Khan, I.M., Khan, S., Khalifa, O.O.  
 Transfer of power to low power implanted biomedical devices: Coil design considerations  
 (2012) *Proceedings of I2MTC 2012*  
 May 13-16, Graz, Austria

## Related documents

Magnetic field design for optimal wireless power transfer to multiple receivers

Huang, X. , Gao, Y. , Zhou, J.  
*(2016) IET Power Electronics*

A novel design of magnetically coupled circuits for wireless power transfer with improved waveforms

Goyal, R.K. , Gautam, U. , Behera, R.K.  
*(2013) Proceedings of the IEEE International Conference on Industrial Technology*

On-axis field approximations for a (semi-) spheroid in a uniform field

Boggs, S.  
*(2003) IEEE Transactions on Dielectrics and Electrical Insulation*

[View all related documents based on references](#)

[Find more related documents in Scopus based on:](#)

[Authors >](#)
[Keywords >](#)