

# Web of Science

Search

Search Results

My Tools ▾

Search History

Marked List

 [Look Up Full Text](#)


Save to EndNote online ▾

[Add to Marked List](#)

1 of 1

## Preload-based Starling-like control of rotary blood pumps: An in-vitro evaluation

**By:** [Mansouri, M](#) (Mansouri, Mahdi)<sup>[1,2]</sup>; [Gregory, SD](#) (Gregory, Shaun D.)<sup>[2,3,4]</sup>; [Salamonsen, RF](#) (Salamonsen, Robert F.)<sup>[5,6]</sup>; [Lovell, NH](#) (Lovell, Nigel H.)<sup>[7]</sup>; [Stevens, MC](#) (Stevens, Michael C.)<sup>[2,7,8]</sup>; [Pauls, JP](#) (Pauls, Jo P.)<sup>[2,3,4]</sup>; [Akmeliawati, R](#) (Akmeliawati, Rini)<sup>[9]</sup>; [Lim, E](#) (Lim, Einly)<sup>[1]</sup>

[View ResearcherID and ORCID](#)

PLOS ONE

Volume: 12 Issue: 2

Article Number: e0172393

DOI: 10.1371/journal.pone.0172393

Published: FEB 17 2017

[View Journal Impact](#)

### Abstract

Due to a shortage of donor hearts, rotary left ventricular assist devices (LVADs) are used to provide mechanical circulatory support. To address the preload insensitivity of the constant speed controller (CSC) used in conventional LVADs, we developed a preload-based Starling-like controller (SLC). The SLC emulates the Starling law of the heart to maintain mean pump flow ((Q) over bar (P)) with respect to mean left ventricular end diastolic pressure (PLVEDm) as the feedback signal. The SLC and CSC were compared using a mock circulation loop to assess their capacity to increase cardiac output during mild exercise while avoiding ventricular suction (marked by a negative PLVEDm) and maintaining circulatory stability during blood loss and severe reductions in left ventricular contractility (LVC). The root mean squared hemodynamic deviation (RMSHD) metric was used to assess the clinical acceptability of each controller based on pre-defined hemodynamic limits. We also compared the in-silico results from our previously published paper with our in-vitro outcomes. In the exercise simulation, the SLC increased (Q) over bar (P) by 37%, compared to only 17% with the CSC. During blood loss, the SLC maintained a better safety margin against left ventricular suction with PLVEDm of 2.7 mmHg compared to -0.1 mmHg for CSC. A transition to reduced LVC resulted in decreased mean arterial pressure (MAP) and (Q) over bar (P) with CSC, whilst the SLC maintained MAP and (Q) over bar (P). The results were associated with a much lower RMSHD value with SLC (70.3%) compared to CSC (225.5%), demonstrating improved capacity of the SLC to compensate for the varying cardiac demand during profound circulatory changes. In-vitro and in-silico results demonstrated similar trends to the simulated changes in patient state however the magnitude of hemodynamic changes were different, thus justifying the progression to in-vitro evaluation.

### Keywords

**KeyWords Plus:** [VENTRICULAR ASSIST DEVICES](#); [HEART-FAILURE](#); [EXERCISE](#); [FLOW](#); [SPEED](#)

### Author Information

**Reprint Address:** Lim, E (reprint author)
 Univ Malaya, Dept Biomed Engr, Kuala Lumpur, Malaysia.

#### Addresses:

 [ 1 ] Univ Malaya, Dept Biomed Engr, Kuala Lumpur, Malaysia

[ 2 ] Prince Charles Hosp, Crit Care Res Grp, Innovat Cardiovasc Engr & Technol Lab,  
Brisbane, Qld, Australia

### Citation Network

0 Times Cited

[25 Cited References](#)[View Related Records](#)[Create Citation Alert](#)*(data from Web of Science Core Collection)*

### All Times Cited Counts

0 in All Databases

0 in Web of Science Core Collection

0 in BIOSIS Citation Index

0 in Chinese Science Citation Database

0 in Data Citation Index

0 in Russian Science Citation Index

0 in SciELO Citation Index

### Usage Count

Last 180 Days: 4

Since 2013: 4

[Learn more](#)

### This record is from:

**Web of Science Core Collection**  
- Science Citation Index Expanded

### Suggest a correction

If you would like to improve the quality of the data in this record, please [suggest a correction](#).