

## Document details


< Back to results | 1 of 3 Next >

Export Download Print E-mail Save to PDF Add to List More... >

[Full Text](#) View at Publisher

Journal of Alloys and Compounds  
Volume 722, 2017, Pages 458-466


## Microwave sintering of zirconia-toughened alumina (ZTA)-TiO<sub>2</sub>-Cr<sub>2</sub>O<sub>3</sub> ceramic composite: The effects on microstructure and properties (Article)

Manshor, H.<sup>ab</sup>, Abdullah, E.C.<sup>a</sup>, Azhar, A.Z.A.<sup>c</sup>, Sing, Y.W.<sup>d</sup>, Ahmad, Z.A.<sup>e</sup> 

<sup>a</sup>Malaysia – Japan International Institute of Technology (MJIT), Universiti Teknologi Malaysia Kuala Lumpur, Jalan Semarak, Kuala Lumpur, Malaysia

<sup>b</sup>Department of Science in Engineering, Faculty of Engineering, International Islamic University Malaysia, P.O. Box 10, Kuala Lumpur, Malaysia

<sup>c</sup>Department of Manufacturing and Materials Engineering, Faculty of Engineering, International Islamic University Malaysia, P.O. Box 10, Kuala Lumpur, Malaysia

View additional affiliations 

### Abstract

 View references (29)

This paper focuses on the development of a zirconia-toughened alumina ZTA-TiO<sub>2</sub>-Cr<sub>2</sub>O<sub>3</sub> ceramic composite by means of microwave sintering at 2.45 GHz within the range 1200 °C–1400 °C, with a dwell time of 5–20 min. It is aimed at attaining improved microstructure and properties at a lower sintering temperature and shorter soaking time, compared to using a conventional heating method. Consequently, the effects of sintering temperature and soaking time on densification, properties and microstructural behaviour of the composite, are investigated. XRD analysis reveals that the microwave-sintered samples possess a higher crystallinity at a higher sintering temperature. Microstructural analysis confirms the uniform distribution of particles and controlled grain growth; with the lowest AGI value being 1.28 grains/μm. The sample that is microwave-sintered at 1350 °C with 10 min of soaking time achieves a high density (95.74% of the theoretical density), elevated hardness (1803.4 HV), and excellent fracture toughness (9.61 MPa m<sup>1/2</sup>), and intergranular cracks. This proves that the microwave sintering technique enhances densification, microstructural evolution and the properties of the ceramic composite at a lower temperature and shorter soaking time, compared to conventional heating. Overall, the improved mechanical properties of the microwave-sintered ceramics, compared to conventionally-sintered ceramics, are attributed to the enhanced densification and finer and more homogeneous microstructure that is achieved through the use of a microwave sintering method. The results reveal that microwave sintering is effective in improving the microstructure and density of materials, and will be useful for enhancing the mechanical properties of ZTA-TiO<sub>2</sub>-Cr<sub>2</sub>O<sub>3</sub> ceramic composites. © 2017 Elsevier B.V.

### Author keywords

Fracture toughness Microwave sintering Vickers hardness ZTA

### Indexed keywords

Engineering controlled terms:

Alumina Ceramic materials Densification Density (specific gravity) Fracture  
Fracture toughness Grain growth Mechanical properties Microstructure  
Microwave heating Microwaves Sintered alumina Titanium dioxide Vickers hardness  
Zirconia

### Metrics

0 Citations in Scopus

0 Field-Weighted Citation Impact



PlumX Metrics 

Usage, Captures, Mentions, Social Media and Citations beyond Scopus.

### Cited by 0 documents

Inform me when this document is cited in Scopus:

[Set citation alert >](#)

[Set citation feed >](#)

### Related documents

In situ study on microwave sintering of ZTA ceramic: Effect of ZrO<sub>2</sub> content on densification, hardness, and toughness

Meunier, C. , Zuo, F. , Peillon, N. (2017) *Journal of the American Ceramic Society*

Effect of nanometer Al<sub>2</sub>O<sub>3</sub> powder on microstructure and properties of alumina ceramics by microwave sintering

Liu, Y. , Min, F.-F. , Zhu, J.-B. (2012) *Materials Science and Engineering A*

Preparation of large size ZTA ceramics with eccentric circle shape by microwave sintering

Chen, Y. , Fan, B. , Shao, G. (2016) *Journal of Advanced Ceramics*

View all related documents based on references

Find more related documents in Scopus based on:

Engineering main heading:    Sintering

## Funding details

Funding number	Funding sponsor	Acronym
FRGS/2/2013/TK05/UTM/01/5	Universiti Teknologi Malaysia	UTM
FRGS14-164-0405	International Islamic University Malaysia	IIUM
RAGS13-021-0084	International Islamic University Malaysia	IIUM

## Funding text

This work was funded by the International Islamic University Malaysia (IIUM) under Grant RAGS13-021-0084, Grant FRGS14-164-0405 and Universiti Teknologi Malaysia (UTM) under Grant FRGS/2/2013/TK05/UTM/01/5.

ISSN: 09258388

CODEN: JALCE

Source Type: Journal

Original language: English



DOI: 10.1016/j.jallcom.2017.06.115

Document Type: Article

Publisher: Elsevier Ltd

## References (29)

[View in search results format >](#)

All    [Export](#)     [Print](#)     [E-mail](#)    [Save to PDF](#)    [Create bibliography](#)

- 1    Singh, D.K.  
Manufacturing Technology: Theory and Problems (2008) . Cited 2 times.  
Pearson Education India

---

- 2    Stephenson, D.A., Agapiou, J.S.  
Metal Cutting Theory and Practice (2016) . Cited 421 times.  
third ed. CRC press

---

- 3    Maiti, K., Sil, A.  
Relationship between fracture toughness characteristics and morphology of sintered Al<sub>2</sub>O<sub>3</sub> ceramics  
(2010) *Ceramics International*, 36 (8), pp. 2337-2344. Cited 17 times.  
doi: 10.1016/j.ceramint.2010.07.031  
  
[View at Publisher](#)

---

- 4    Naglieri, V., Palmero, P., Montanaro, L., Chevalier, J.  
Elaboration of alumina-zirconia composites: Role of the zirconia content on the microstructure and mechanical properties  
(2013) *Materials*, 6 (5), pp. 2090-2102. Cited 24 times.  
<http://www.mdpi.com/1996-1944/6/5/2090/pdf>  
doi: 10.3390/ma6052090  
  
[View at Publisher](#)