

Document details

< Back to results | 1 of 1

Export Download Print E-mail Save to PDF Add to List More... >

Full Text View at Publisher

IOP Conference Series: Materials Science and Engineering
Volume 290, Issue 1, 30 January 2018, Article number 012039
International Conference on Advances in Manufacturing and Materials Engineering 2017, ICAMME 2017;
International Islamic University Malaysia (IIUM), Gombak CampusKuala Lumpur; Malaysia; 8 August 2017 through 9
August 2017; Code 134404

Tool Wear Mechanisms during Cutting of Soda Lime Glass (Conference Paper) (Open Access)

Konneh, M. ✉, Bagum, M.N., Ali, M.Y., Mohamed Arif, T.F.B.

Department of Manufacturing and Materials Engineering, Kulliyyah of Engineering, International Islamic University
Malaysia, Jalan Gombak, Kuala Lumpur, Malaysia

Abstract

View references (9)

Soda lime glass milling has high performance application. It is a challenging task to achieve fracture free surface on this material due to its brittle nature. High-speed end milling is capable to achieve ductile mode in an enhance flexibility. In this research, end milling of soda lime using uncoated carbide tool was performed where spindle speed varied from 20,000 to 40,000 rpm, cutting depth from 10 to 30 μm and feed rate from 5 to 20 mm/min in dry condition. The effects of cutting parameters (cutting speed, feed per tooth and depth of cut) on tool flank wear as well as wear mechanisms of tool flank investigated. Investigation showed that feed per edge has most influencing effect followed by cutting speed and depth of cut on flank wear and the main wear mechanism is abrasion wear. In some cases, oxidation, thermal diffusion and recast layer on tool flank also observed. © Published under licence by IOP Publishing Ltd.

Indexed keywords

Engineering controlled terms: Brittle fracture Carbide cutting tools Cutting Glass Lime Manufacture Milling (machining) Tribology Wear of materials

Compendex keywords: Cutting parameters High performance applications High speed end milling Influencing effects Soda Lime glass Tool flank wear Tool wear mechanism Wear mechanisms

Engineering main heading: Cutting tools

ISSN: 17578981
Source Type: Conference Proceeding
Original language: English

DOI: 10.1088/1757-899X/290/1/012039
Document Type: Conference Paper
Sponsors:
Publisher: Institute of Physics Publishing

References (9)

View in search results format >

All Export Print E-mail Save to PDF Create bibliography

Metrics ?

0 Citations in Scopus
0 Field-Weighted Citation Impact

PlumX Metrics Usage, Captures, Mentions, Social Media and Citations beyond Scopus.

Cited by 0 documents

Inform me when this document is cited in Scopus:
Set citation alert >
Set citation feed >

Related documents

An experimental investigation on the surface morphology in micro-end-milling of glass
Zhao, Y. , Zhang, Y. , Huo, D. (2014) ICAC 2014 - Proceedings of the 20th International Conference on Automation and Computing: Future Automation, Computing and Manufacturing
A new experimental approach to determination of critical depth in high speed machining of soda-lime glass
Mahmud, M.A. , Nurul Amin, A.K.M. , Arif, M.D. (2012) Advanced Materials Research

Surface morphology study in high speed milling of soda lime glass
Konneh, M. , Nasima Bagum, M. , Ali, M.Y. (2018) AIP Conference Proceedings

View all related documents based on references

- ☐ 1 Yan, J., Zhao, H., Kuriyagawa, T.
Effects of tool edge radius on ductile machining of silicon: An investigation by FEM

(2009) *Semiconductor Science and Technology*, 24 (7), art. no. 075018. Cited 30 times.
doi: 10.1088/0268-1242/24/7/075018

[View at Publisher](#)

- ☐ 2 Arif, M., Rahman, M., Yoke San, W.
Analytical model to determine the critical feed per edge for ductilebrittle transition in
milling process of brittle materials

(2011) *International Journal of Machine Tools and Manufacture*, 51 (3), pp. 170-181. Cited 45 times.
doi: 10.1016/j.ijmachtools.2010.12.003

[View at Publisher](#)

- ☐ 3 Nurul Amin, A.K.M., Bagum, M.N., Fathiah, N., Konneh, M., Ariff, T.F.B.M.
An Experimental Approach to Determine the Critical Depth of Cut in Brittle-to-Ductile
Phase Transition During End Milling of Soda-Lime Glass

(2016) *Arabian Journal for Science and Engineering*, 41 (11), pp. 4553-4562. Cited 7 times.
<http://www.springerlink.com/content/1319-8025>
doi: 10.1007/s13369-016-2174-7

[View at Publisher](#)

- ☐ 4 Cheng, K.
(2008) *Machining Dynamics: Fundamentals, Applications and Practices*. Cited 69 times.
(Springer Science amp; Business Media)

- ☐ 5 Wei, X., Qi, L., Zhou, J., Ju, L., Tian, W.
Tool wear morphologies and mechanisms for cutting C_f/Mg composites

(2016) *International Journal of Advanced Manufacturing Technology*, 86 (1-4), pp. 613-619.
<http://www.springerlink.com/content/0268-3768>
doi: 10.1007/s00170-015-8176-x

[View at Publisher](#)

- ☐ 6 Materiala, R.K.P.
(2016) *I Materiali in Tehnologije*, 50 (4), pp. 591-600.

- ☐ 7 Arif, M., Rahman, M., San, W.Y.
Ultraprecision ductile mode machining of glass by micromilling process

(2011) *Journal of Manufacturing Processes*, 13 (1), pp. 50-59. Cited 38 times.
doi: 10.1016/j.jmapro.2010.10.004

[View at Publisher](#)

- ☐ 8 Jia, P., Zhou, M.
(2012) *Tribology*, 1, p. 05.