

Full Text from Publisher



Save to EndNote online

Add to Marked List

◀ 1 of 1 ▶

Coil geometry models for power loss analysis and hybrid inductive link for wireless power transfer applications

By: Nataraj, C (Nataraj, Chandrasekharan)^[1]; Khan, S (Khan, Sheroz)^[2]; Habaebi, MH (Habaebi, Mohamed Hadi)^[2]

SADHANA-ACADEMY PROCEEDINGS IN ENGINEERING SCIENCES

Volume: 43 Issue: 5

Article Number: UNSP 67

DOI: 10.1007/s12046-018-0842-x

Published: MAY 2018

Document Type: Article

[View Journal Impact](#)

Abstract

This paper presents a hybrid inductive link for Wireless Power Transfer (WPT) applications. Achieving better power transfer efficiency over a relatively wider distance across coils is the prime objective in most of the WPT systems, but often suffers from power loss in the near field area of inductively coupled coils. One of the reasons for this power loss is the pattern of the magnetic field produced by the source coil used in the WPT system. Mostly the nature of magnetic field produced by the source coil is distributed radially over the coil, in which the produced magnetic field is not fully utilized. Achieving better efficiency and load current by reducing power loss is the main driving force of this work. One of the viable methods to reduce the power loss is by increasing the field intensity thereby redirecting the flux lines flow to be directional. With this aim, three coils such as solenoid, spiral and conical are designed and simulated to determine the magnetic field strength using Finite Element Method. The conical coil produces the highest self-inductance of 8.63 A mu H and a field strength of 1.542 Wb with the coil thickness of 3.20 mm. Then, WPT system is demonstrated with the inclusion of Maximum Power Point Tracking algorithm for improving efficiency. The schematic of flux generation of both in the transmitter and receiver sections are demonstrated and analyzed graphically. The efficiency of both simulation and experimental measurements are matched well with similar progression. The effect of parameters (angle, distance, and load resistance) on the efficiency is explored. The outcomes conclude that the inductive coupling has achieved 73% (average case) power transfer wirelessly over a distance of 5 cm with an input voltage of 5 V and 5 MHz frequency.

Keywords

Author Keywords: Coils geometry; inductive coupling; MPPT algorithm; power transfer efficiency; resonant coils; wireless power transfer

KeyWords Plus: TRANSFER SYSTEM; DESIGN; EFFICIENCY

Author Information

Reprint Address: Nataraj, C (reprint author)

Asia Pacific Univ Technol & Innovat, Fac Comp Engn & Technol, Kuala Lumpur, Malaysia.

Addresses:

[1] Asia Pacific Univ Technol & Innovat, Fac Comp Engn & Technol, Kuala Lumpur, Malaysia

+ [2] IIUM, Dept Elect & Comp Engn, Kuala Lumpur, Malaysia

E-mail Addresses: chander@apu.edu.my; sheroz@iium.edu.my; habaebi@iium.edu.my

Publisher

INDIAN ACAD SCIENCES, C V RAMAN AVENUE, SADASHIVANAGAR, P B #8005, BANGALORE 560 080, INDIA

Categories / Classification

Research Areas: Engineering

Web of Science Categories: Engineering, Multidisciplinary

[See more data fields](#)

◀ 1 of 1 ▶

Citation Network

In Web of Science Core Collection

0

Times Cited

 [Create Citation Alert](#)

24

Cited References

[View Related Records](#)

Use in Web of Science

Web of Science Usage Count

5

Last 180 Days

7

Since 2013

[Learn more](#)

This record is from:

Web of Science Core Collection
- Science Citation Index Expanded

Suggest a correction

If you would like to improve the quality of the data in this record, please suggest a correction.

Cited References: 24Showing 24 of 24 [View All in Cited References page](#)

(from Web of Science Core Collection)

1. **A Wireless-Implantable Microsystem for Continuous Blood Glucose Monitoring** Times Cited: 121
By: Ahmadi, Mohammad Mahdi; Jullien, Graham A.
IEEE TRANSACTIONS ON BIOMEDICAL CIRCUITS AND SYSTEMS Volume: 3 Issue: 3 Pages: 169-180 Published: JUN 2009
2. **Optimized magnetic design for inductive power transfer coils** Times Cited: 1
By: Bosshard, R; Muhlethaler, J; Kolar, JW; et al.
28 ANN IEEE POW EL C Published: 2013
[\[Show additional data\]](#)
3. **Comparative evaluation of control methods for inductive power transfer** Times Cited: 2
By: Bosshard, R; Badstubner, U; Kolar, J W; et al.
INT C REN EN RES APP Published: 2012
[\[Show additional data\]](#)
4. **Design and Optimization of Circular Magnetic Structures for Lumped Inductive Power Transfer Systems** Times Cited: 351
By: Budhia, Mickel; Covic, Grant A.; Boys, John T.
IEEE TRANSACTIONS ON POWER ELECTRONICS Volume: 26 Issue: 11 Pages: 3096-3108 Published: NOV 2011
5. **The New MPPT Algorithm Using ANN- Based PV** Times Cited: 1
By: Dzung, P Q; Le Dinh, K; Lee, H H; et al.
IEEE INT FORUM STRAT Published: 2010
[\[Show additional data\]](#)
6. **Wireless Power Transfer in Loosely Coupled Links: Coil Misalignment Model** Times Cited: 157
By: Fotopoulou, Kyriaki; Flynn, Brian W.
IEEE TRANSACTIONS ON MAGNETICS Volume: 47 Issue: 2 Pages: 416-430 Part: 2 Published: FEB 2011
7. **Narrow-Width Inductive Power Transfer System for Online Electrical Vehicles** Times Cited: 288
By: Huh, J.; Lee, S. W.; Lee, W. Y.; et al.
IEEE TRANSACTIONS ON POWER ELECTRONICS Volume: 26 Issue: 12 Pages: 3666-3679 Published: DEC 2011
8. **An Analysis of Magnetic Resonance Coupling Effects on Wireless Power Transfer by Coil Inductance and Placement** Times Cited: 19
By: Hwang, Hyeonseok; Moon, Junil; Lee, Bumsoo; et al.
IEEE TRANSACTIONS ON CONSUMER ELECTRONICS Volume: 60 Issue: 2 Pages: 203-209 Published: MAY 2014
9. **Analysis and Practical Considerations in Implementing Multiple Transmitters for Wireless Power Transfer via Coupled Magnetic Resonance** Times Cited: 57
By: Johari, Rizal; Krogmeier, James V.; Love, David J.
IEEE TRANSACTIONS ON INDUSTRIAL ELECTRONICS Volume: 61 Issue: 4 Pages: 1774-1783 Published: APR 2014
10. **Wireless Transfer of Power to Low Power Implanted Biomedical Devices: Coil Design Considerations** Times Cited: 2
By: Khan, Imran M.; Khan, Sheroz; Khalifa, Othman O.
2012 IEEE INTERNATIONAL INSTRUMENTATION AND MEASUREMENT TECHNOLOGY CONFERENCE (I2MTC) Book Series: IEEE Instrumentation and Measurement Technology Conference Pages: 2584-2588 Published: 2012
11. **Wireless power transfer via strongly coupled magnetic resonances** Times Cited: 1
By: Kurs, A; Karalis, A; Moffatt, R; et al.
Science Volume: 80 Pages: 37-46 Published: 2003
[\[Show additional data\]](#)
12. **A framework for evaluating multi-kilowatt highly-resonant wireless power transfer systems** Times Cited: 1
By: Kurs, A; Lestoquoy, G.
IEEE 82 VEH TECHN C Published: 2015

13. **Modeling of inductive coupling for wireless power transfer to integrated circuits** Times Cited: 1
By: Matias, R; Cunha, B; Martins, R.
IEEE Wireless Power Transfer Published: 2013
14. **Resonant coils analysis for inductively coupled wireless power transfer applications** Times Cited: 1
By: Nataraj, C; Khan, S; Habaebi, M H; et al.
IEEE INT INSTR MEAS Published: 2016
[\[Show additional data\]](#)
15. **Hybrid of Conical and Spiral Approach for Wireless Power Transfer** Times Cited: 2
By: Nataraj, C; Khan, S; Habaebi, M H; et al.
IEEE STUD C RES DEV Published: 2016
[\[Show additional data\]](#)
16. **DEVELOPMENT OF WIRELESS POWER TRANSFER SYSTEM USING RESONANCE PRINCIPLE WITH SECURITY FEATURES** Times Cited: 1
By: Nataraj, Chandrasekharan; Khan, Sheraz; Habaebi, Mohamed Hadi; et al.
IUM ENGINEERING JOURNAL Volume: 18 Issue: 2 Pages: 117-127 Published: 2017
17. **Two- and Three-Dimensional Omnidirectional Wireless Power Transfer** Times Cited: 60
By: Ng, Wai Man; Zhang, Cheng; Lin, Deyan; et al.
IEEE TRANSACTIONS ON POWER ELECTRONICS Volume: 29 Issue: 9 Pages: 4470-4474 Published: SEP 2014
18. **Field Distribution Models of Spiral Coil for Misalignment Analysis in Wireless Power Transfer Systems** Times Cited: 47
By: Nguyen, Minh Quoc; Hughes, Zachariah; Woods, Peter; et al.
IEEE TRANSACTIONS ON MICROWAVE THEORY AND TECHNIQUES Volume: 62 Issue: 4 Special Issue: SI Pages: 920-930 Part: 2 Published: APR 2014
19. **Receivers for Multifrequency Wireless Power Transfer: Design for Minimum Interference** Times Cited: 17
By: Pantic, Zeljko; Lee, Kibok; Lukic, Srdjan M.
IEEE JOURNAL OF EMERGING AND SELECTED TOPICS IN POWER ELECTRONICS Volume: 3 Issue: 1 Special Issue: SI Pages: 234-241 Published: MAR 2015
20. Title: [not available] Times Cited: 3
By: QIANG H
RES J APPL SCI ENG T Volume: 5 Pages: 5039 Published: 2013
21. **A fast telemetric pressure and temperature sensor system for medical applications** Times Cited: 23
By: Schlierf, R.; Horst, U.; Ruhl, M.; et al.
JOURNAL OF MICROMECHANICS AND MICROENGINEERING Volume: 17 Issue: 7 Pages: S98-S102 Published: JUL 2007
22. **A Two-Hop Wireless Power Transfer System With an Efficiency-Enhanced Power Receiver for Motion-Free Capsule Endoscopy Inspection** Times Cited: 54
By: Sun, Tianjia; Xie, Xiang; Li, Guolin; et al.
IEEE TRANSACTIONS ON BIOMEDICAL ENGINEERING Volume: 59 Issue: 11 Pages: 3247-3254 Published: NOV 2012
23. **Low voltage DC power supply with spike-blocking features** Times Cited: 1
By: Torla, A L; Khan, S; Muthalif, A G; et al.
IEEE INT INSTR MEAS Published: 2013
[\[Show additional data\]](#)
24. **Magnetic Resonance Wireless Power Transfer using Three-Coil System with Single Planar Receiver for Laptop Applications** Times Cited: 27
By: Van Thuan Nguyen; Kang, Seok Hyon; Choi, Jung Han; et al.
IEEE TRANSACTIONS ON CONSUMER ELECTRONICS Volume: 61 Issue: 2 Pages: 160-166 Published: MAY 2015

Showing 24 of 24 [View All in Cited References page](#)

Clarivate

Accelerating innovation

[© 2019 Clarivate](#) [Copyright notice](#) [Terms of use](#) [Privacy statement](#) [Cookie policy](#)

[Sign up for the Web of Science newsletter](#) [Follow us](#)

