

[< Back to results](#) | 1 of 1[↗ Export](#) [↓ Download](#) [🖨 Print](#) [✉ E-mail](#) [Save to PDF](#) [☆ Add to List](#) [More... >](#)[Full Text](#) [View at Publisher](#)Materialwissenschaft und Werkstofftechnik  
Volume 49, Issue 4, April 2018, Pages 460-466

## Preliminary development of porous aluminum via powder metallurgy technique: Vorentwicklung von porösem Aluminium durch Pulvermetallurgie (Article)

Jamal, N.A.<sup>a</sup> [✉](#), Maizatul, O.<sup>a</sup>, Anuar, H.<sup>a</sup>, Yusof, F.<sup>b</sup>, Nor, Y.A.<sup>c</sup>, Khalid, K.<sup>d</sup>, Zakaria, M.N.<sup>e</sup> [👤](#)<sup>a</sup>Manufacturing and Materials Engineering (MME) Department, Kulliyah of Engineering, International Islamic University Malaysia, P.O. Box 10, KUALA LUMPUR, Malaysia<sup>b</sup>Centre of Advanced Manufacturing and Materials Processing (AMMP), Faculty of Engineering, University Malaya, KUALA LUMPUR, Malaysia<sup>c</sup>Biotechnology Engineering Department, Kulliyah of Engineering, International Islamic University Malaysia, P.O. Box 10, KUALA LUMPUR, Malaysia[View additional affiliations](#) [v](#)

### Abstract

[v View references \(14\)](#)

Porous aluminum has been extensively studied, particularly in the field in which lightweight and high stiffness properties are essential. In this study, a preliminary investigation is performed to determine the optimum sintering temperature to develop porous aluminium by a powder metallurgy technique, using polymethylmethacrylate as a space holder. The effects of the sintering temperatures on the physical characteristics, oxidation level, microstructure and sintered density of the porous specimen are systematically evaluated. Based on the results, an increase in the sintering temperature from 580 °C to 600 °C changes the colour of the porous aluminum body from a silver-like colour to a gold-like colour, with some of the specimens encountering severe cracking, spalling and even collapsing. As such, the oxygen content is significantly increased from 0.45 wt.% to 2.14 wt. %, suggesting the oxidation phenomenon. In line with this, an obvious appearance of particle boundaries with less macro-pores formation is also observed. Additionally, the sintered density of the porous specimen is found to reduce from 1.305 g/cm<sup>3</sup> to 0.908 g/cm<sup>3</sup>. Therefore, fabrication of the resultant porous aluminium at 580 °C is an ideal condition in this study, owing to the ideal combination of physical characteristics, microstructure, oxidation level and sintered density. © 2018 Wiley-VCH Verlag GmbH & Co. KGaA, Weinheim

### Reaxys Database Information

[View Compounds](#)

### Author keywords

[microstructure](#) [oxidation level](#) [physical characteristics](#) [polymethylmethacrylate](#) [Porous aluminium](#)  
[powder metallurgy](#) [sintered density](#) [sintering temperature](#)

### Indexed keywords

Engineering controlled terms: [Aluminum](#) [Aluminum powder metallurgy](#) [Color](#) [Microstructure](#) [Oxidation](#)  
[Polyesters](#) [Polymethyl methacrylates](#) [Powder metallurgy](#)Engineering uncontrolled terms: [High stiffness](#) [Oxidation level](#) [Particle boundaries](#) [Physical characteristics](#)  
[Porous aluminium](#) [Powder metallurgy techniques](#) [Sintered density](#)  
[Sintering temperatures](#)

### Metrics [?](#)

0 Citations in Scopus

0 Field-Weighted  
Citation Impact

#### PlumX Metrics [v](#)

Usage, Captures, Mentions,  
Social Media and Citations  
beyond Scopus.

### Cited by 0 documents

Inform me when this document  
is cited in Scopus:[Set citation alert >](#)[Set citation feed >](#)

### Related documents

Fabrication and compressive  
properties of low to medium  
porosity closed-cell porous  
Aluminum using PMMA space  
holder techniqueJamal, N.A. , Tan, A.W. , Yusof, F.  
(2016) *Materials*The impact of composition and  
sintering temperature for  
stainless steel foams (SS316l)  
fabricated by space holder  
method with urea as space holderAbdullah, Z. , Ahmad, S. , Ramli,  
M.  
(2017) *Materials Science Forum*Solid mold investment casting -  
A replication process for open-  
cell foam metal productionGuler, K.A.  
(2015)  
*Materialpruefung/Materials  
Testing*[View all related documents based  
on references](#)[Find more related documents in  
Scopus based on:](#)[Authors >](#) [Keywords >](#)

## Funding details

Funding number	Funding sponsor	Acronym	Funding opportunities
	International Islamic University Malaysia	IIUM	
	International Islamic University Malaysia	IIUM	

## Funding text

We would like to express our gratitude to the International Islamic University Malaysia (IIUM) Research Initiatives Grant Scheme (RIGS) with project number of 16-091-0255 for funding the current project.

ISSN: 09335137

Source Type: Journal

Original language: English

DOI: 10.1002/mawe.201700269

Document Type: Article

Publisher: Wiley-VCH Verlag

## References (14)

[View in search results format >](#)

All  Export  Print  E-mail  Save to PDF  Create bibliography

- 1 Dewidar, M.  
Influence of processing parameters and sintering atmosphere on the mechanical properties and microstructure of porous 316L stainless steel for possible hard-tissue applications  
*(2012) International Journal of Mechanical and Mechanics Engineering*, 12 (1), pp. 10-24. Cited 10 times.  
[http://www.ijens.org/Vol\\_12\\_I\\_01/120301-8484-IJMME-IJENS.pdf](http://www.ijens.org/Vol_12_I_01/120301-8484-IJMME-IJENS.pdf)
- 2 Heydari Astaraie, A., Shahverdi, H.R., Elahi, S.H.  
Compressive behavior of Zn-22Al closed-cell foams under uniaxial quasi-static loading  
*(2015) Transactions of Nonferrous Metals Society of China (English Edition)*, 25 (1), pp. 162-169. Cited 11 times.  
doi: 10.1016/S1003-6326(15)63591-9  
[View at Publisher](#)
- 3 Ashby, M.F., Evans, A., Fleck, N., Wadley, H.N.G.  
*(2000) Metal Foams: A Design Guide*. Cited 2222 times.  
Butterworth-Heinemann, Oxford, United Kingdom
- 4 Jiang, B., Zhao, N.Q., Shi, C.S., Li, J.J.  
Processing of open cell aluminum foams with tailored porous morphology  
*(2005) Scripta Materialia*, 53 (6), pp. 781-783. Cited 68 times.  
doi: 10.1016/j.scriptamat.2005.04.055  
[View at Publisher](#)
- 5 Zhao, Y.  
*(2013) J. Powder Metall. Mining*, 2, p. 1000e.  
113

- 6 Morsi, K., Krommenhoek, M., Shamma, M.  
Novel Aluminum (Al)-Carbon Nanotube (CNT) Open-Cell Foams  
(2016) *Metallurgical and Materials Transactions A: Physical Metallurgy and Materials Science*, 47 (6), pp. 2574-2578. Cited 3 times.  
[http://www.springerlink.com/content/1073-5623?sortorder=asc&p\\_o=54](http://www.springerlink.com/content/1073-5623?sortorder=asc&p_o=54)  
doi: 10.1007/s11661-016-3423-9  
View at Publisher
- 
- 7 Mukherjee, M., García-Moreno, F., Jiménez, C., Rack, A., Banhart, J.  
Microporosity in aluminium foams  
(2017) *Acta Materialia*, 131, pp. 156-168. Cited 6 times.  
<http://www.journals.elsevier.com/acta-materialia/>  
doi: 10.1016/j.actamat.2017.03.039  
View at Publisher
- 
- 8 Arifvianto, B., Zhou, J.  
Fabrication of metallic biomedical scaffolds with the space holder method: A review  
(2014) *Materials*, 7 (5), pp. 3588-3622. Cited 37 times.  
<http://www.mdpi.com/1996-1944/7/5/3588/pdf>  
doi: 10.3390/ma7053588  
View at Publisher
- 
- 9 Huy, W.C.  
(2003) *Jpn. J. Appl. Phys.*, 42, p. L595.
- 
- 10 Ramezani, M., Neitzert, T.  
(2012) *J. Achiev. Mater. Manuf. Eng.*, 55, p. 790. Cited 22 times.
- 
- 11 Yang, D.H., Hur, B.Y., He, D.P., Yang, S.R.  
Effect of decomposition properties of titanium hydride on the foaming process and pore structures of Al alloy melt foam  
(2007) *Materials Science and Engineering A*, 445-446, pp. 415-426. Cited 52 times.  
doi: 10.1016/j.msea.2006.09.064  
View at Publisher
- 
- 12 Sercombe, T.B., Schaffer, G.B.  
The effect of trace elements on the sintering of Al - Cu alloys  
(1999) *Acta Materialia*, 47 (2), pp. 689-697. Cited 56 times.  
<http://www.journals.elsevier.com/acta-materialia/>  
doi: 10.1016/S1359-6454(98)00353-X  
View at Publisher
- 
- 13 Katsuyoshi, K., Tachai, L., Thotsaphon, T., Atsushi, K.  
(2007) *Trans. JWRI.*, 36, p. 29. Cited 3 times.
- 
- 14 Erasmus, E.P., Johnson, O.T., Sigalas, I., Massera, J.  
(2017) *Sci. Rep.*, 7, p. 1.

## About Scopus

[What is Scopus](#)  
[Content coverage](#)  
[Scopus blog](#)  
[Scopus API](#)  
[Privacy matters](#)

## Language

[日本語に切り替える](#)  
[切换到简体中文](#)  
[切换到繁體中文](#)  
[Русский язык](#)

## Customer Service

[Help](#)  
[Contact us](#)

**ELSEVIER**

[Terms and conditions](#) [Privacy policy](#)

Copyright © 2018 Elsevier B.V. All rights reserved. Scopus® is a registered trademark of Elsevier B.V.

Cookies are set by this site. To decline them or learn more, visit our [Cookies page](#).

 RELX Group