

## Abstract

In this work, a supercontinuum (SC) source is proposed and demonstrated using a highlydoped, 2 m long zirconia-erbium doped fiber (Zr-EDF) with a dopant concentration of 3800 ppm/wt and a narrow core 100 m long single-mode-fiber (SMF). A graphene based saturable absorber (SA) is used as a passive mode-locker, generating pulses with an average output power, pulse energy and peak power of ~0.9 mW, ~69.8 pJ and ~83 W respectively and a repetition rate of 12.9 MHz. This is then amplified using a 140 mW amplifier, giving an output power, pulse energy and peak power of ~75.0 mW, 5.8 nJ and ~6.76 kW respectively and injected into a 100 m long SMF, to generate an SC output which spans from 1450 to more than 1700 nm, with a pulse width at its full-width-at-half-maximum (FWHM) of 120 fs, 7 times lower than the 840 fs FWHM width of the pulses from the fiber laser. The narrow core SMF performs comparably to longer lengths of standard SMF-28 fibers.



Previous

Next

## Keywords

Supercontinuum; Narrow core single mode fiber; Graphene; Mode-locked fiber laser; Zirconiabased erbium-doped fiber

Recommended articles

Citing articles (0)

© 2018 Elsevier GmbH. All rights reserved.

## ELSEVIER

About ScienceDirect Remote access Shopping cart Contact and support Terms and conditions Privacy policy

We use cookies to help provide and enhance our service and tailor content and ads. By continuing you agree to the use of cookies.

Copyright © 2018 Elsevier B.V. or its licensors or contributors. ScienceDirect ® is a registered trademark of Elsevier B.V.

