

IEEE Access Open Access
Volume 7, 2019, Article number 8651565, Pages 27993-28000

Application of taguchi signal to noise ratio design method to ZnO thin film CMOS SAW resonators (Article)

Md Ralib, A.A., Nordin, A.N. ✉

Department of Electrical and Computer Engineering, Kulliyyah of Engineering, International Islamic University Malaysia, Kuala Lumpur, 53100, Malaysia

Abstract

View references (25)

A systematic approach using Taguchi method is proposed for optimization of complementary metal oxide semiconductor microelectromechanical system surface acoustic wave (SAW) resonators . The aim of the present method is to enhance the performance of SAW devices in terms of electromechanical coupling coefficient while reducing the design and development cost. Controllable factors such as a number of transducers, N_t , the distance between input and output transducers, L_c , and the thickness of the piezoelectric materials, T_c have been optimized. $L_{27}(3^{13})$ orthogonal array was chosen to conduct 27 simulations with three level parameters. Time and cost efficient 2D finite element simulations were done using COMSOL Multiphysics™ for two-step analysis Eigen frequency and frequency domain analysis. The orthogonal array, signal to noise ratio , and analysis of variance (ANOVA) were calculated to determine the best settings of the design parameters. The maximum electromechanical coupling coefficient is achieved at the optimal condition of $N_t = 6$; $L_c = 1.6 \mu\text{m}$; $T_c = 2.5 \mu\text{m}$ with increased performance by 4.68% for K^2 and 9.62% for $G_{12}(f)$ compared to the initial conditions. The interaction between pairs of factors has also been investigated. The Taguchi method reveals that both N_t and L_c , and the interaction of $N_t \times L_c$ plays crucial roles in optimizing the electroacoustic conversion of the SAW devices. Hence, the experiment shows that the performance of the SAW device has been successfully optimized. © 2019 IEEE.

Author keywords

- Electromechanical coupling coefficient
- piezoelectric thin film
- surface acoustic wave resonator
- Taguchi signal to noise ratio
- ZnO

Indexed keywords

Engineering controlled terms:

- Acoustic noise
- Acoustic resonators
- Acoustic surface wave devices
- Analysis of variance (ANOVA)
- CMOS integrated circuits
- Cost benefit analysis
- Electromechanical coupling
- Electromechanical devices
- Frequency domain analysis
- II-VI semiconductors
- Integrated circuit design
- MEMS
- Metals
- MOS devices
- Oxide semiconductors
- Piezoelectricity
- Taguchi methods
- Thin films
- Transducers
- Wide band gap semiconductors
- Zinc oxide

Engineering uncontrolled terms

- 2D finite element simulation
- Complementary metal oxide semiconductors
- Comsol multiphysics
- Design and Development
- Electromechanical coupling coefficients
- Optimal conditions
- Piezoelectric thin films
- Surface acoustic wave resonators

Engineering main heading:

- Signal to noise ratio

Metrics ⓘ

- 0 Citations in Scopus
- 0 Field-Weighted Citation Impact



PlumX Metrics Usage, Captures, Mentions, Social Media and Citations beyond Scopus.

Cited by 0 documents

Inform me when this document is cited in Scopus:

- Set citation alert >
- Set citation feed >

Related documents

- Design and analysis of a boosted pierce oscillator using MEMS SAW resonators
Hamzah, M.H. , Karim, J. , Ralib, A.A.M.
(2018) *Microsystem Technologies*
- A Low Jitter Monolithic MEMS Thin Film SAW Oscillator in 0.13 μm CMOS
El-Hemeily, A. , Ibrahim, S.A. , Atef, M.
(2018) *IFCS 2018 - IEEE International Frequency Control Symposium*
- Comparative analysis of the experience obtained from the use of SAW and BAW wireless resonator temperature sensors for surgery
Antcev, I. , Bogoslovsky, S. , Sapozhnikov, G.
(2015) *2015 IEEE International Ultrasonics Symposium, IUS 2015*
- View all related documents based on references

Funding details

Funding sponsor	Funding number	Acronym
International Islamic University Malaysia	RIGS 16-083-0247	
Ministry of Higher Education, Malaysia	FRGS17-032-0598	

Funding text

This work was supported in part by the Research Initiative Grant Scheme from the International Islamic University Malaysia under Grant RIGS 16-083-0247, and in part by the Ministry of Higher Education Malaysia under Grant FRGS17-032-0598.

ISSN: 21693536

Source Type: Journal

Original language: English

DOI: 10.1109/ACCESS.2019.2900590

Document Type: Article

Publisher: Institute of Electrical and Electronics Engineers Inc.

References (25)

View in search results format >

☐ All ☐ Export ☐ Print ☐ E-mail ☐ Save to PDF ☐ Create bibliography

- ☐ 1 Neculoiu, D., Bunea, A.-C., Dinescu, A.M., Farhat, L.A.
Band Pass Filters Based on GaN/Si Lumped-Element SAW Resonators Operating at Frequencies above 5 GHz ([Open Access](#))

(2018) *IEEE Access*, 6, art. no. 8449920, pp. 47587-47599.
<http://ieeexplore.ieee.org/xpl/RecentIssue.jsp?punumber=6287639>
doi: 10.1109/ACCESS.2018.2867456

[View at Publisher](#)
- ☐ 2 Lu, X., Mouthaan, K., Yeo, T.S.
A Wideband Bandpass Filter with Frequency Selectivity Controlled by SAW Resonators

(2016) *IEEE Transactions on Components, Packaging and Manufacturing Technology*, 6 (6), art. no. 7465832, pp. 897-905. Cited 2 times.
<http://cpmt.ieee.org/transactions-on-cpmt.html>
doi: 10.1109/TCPMT.2016.2553105

[View at Publisher](#)
- ☐ 3 Li, S., Sankaranarayanan, S.K.R.S., Fan, C., Su, Y., Bhethanabotla, V.R.
Achieving Lower Insertion Loss and Higher Sensitivity in a SAW Biosensor via Optimization of Waveguide and Microcavity Structures ([Open Access](#))

(2017) *IEEE Sensors Journal*, 17 (6), art. no. 7812628, pp. 1608-1616. Cited 8 times.
<http://ieeexplore.ieee.org/xpl/RecentIssue.jsp?punumber=7361>
doi: 10.1109/JSEN.2017.2651102

[View at Publisher](#)