



# Document details

1 of 1

Export Download More... >

Australian Journal of Electrical and Electronics Engineering  
Volume 16, Issue 3, 3 July 2019, Pages 117-126

## Single event transient effects on 3T and 4T CMOS active pixel sensors for different technologies (Article)

Sukor, M.A., Hedzir, A.S., Sabri, S.S., Hasbullah, N.F.

View additional authors v

Save all to author list

<sup>a</sup>Electrical and Computer Engineering, International Islamic University, Kuala Lumpur, Malaysia

<sup>b</sup>Malaysia National Space Agency, Selangor, Malaysia

View additional affiliations v

Cited by 0 documents

Inform me when this document is cited in Scopus:

Set citation alert >

Set citation feed >

Related documents

Find more related documents in Scopus based on:

Authors > Keywords >

### Abstract

The widely used CMOS Active Pixel Sensors (APS) in space imaging mission are vulnerable to radiations known as Single Event Transient (SET). This paper focus on 3T and 4T CMOS APS with technology from 130 nm scaling down to 32 nm, simulated using various Linear Energy Transfer (LET) magnitudes ranging from 3.3 to 67.7 MeV.cm<sup>2</sup>/mg. Larger transient currents were observed at higher LET for both APS architectures. The peak drain current of 3T increases with slightly steeper slope by roughly 8% than 4T due to the difficulty of electron transfer in 4T. In 3T, 130 nm, 90 nm, 65 nm and 45 nm override the 32 nm technology by 13.93%, 9.09%, 4.43% and 2.06%, respectively. The total charge collection of the 3T is constantly higher than the 4T APS by the ratio of at least 1.25 indicates 4T has a higher radiation hardness. A bright spot degradation is expected to occur in the image if the transient signal is more than 20% of the original signal which mainly attributed to the lower operating voltage and smaller nodal capacitance. From this study, 4T CMOS APS shown more radiation hardness than the 3T CMOS APS and 32 nm technology exhibits lowest radiation-tolerant. © 2019, © 2019 Engineers Australia.

### SciVal Topic Prominence

Topic: Radiation damage | Charge coupled devices | Dark signal

Prominence percentile: 75.893

### Author keywords

Active pixel sensor CMOS technologies linear energy transfer radiation single event transient

### Indexed keywords

Engineering controlled terms:

Capacitance CMOS integrated circuits Drain current Energy transfer Hardness Heat radiation Nanotechnology Pixels Radiation hardening

Engineering uncontrolled terms

Active Pixel Sensor CMOS active pixel sensors CMOS technology Linear energy transfer Radiation hardness Radiation tolerant Single event transients Transient current

Engineering main heading:

Transients

## Funding details

Funding sponsor	Funding number	Acronym
Ministry of Higher Education, Malaysia	RIGS16-338-0502	MOHE
	SP15-063-0185	
Ministry of Higher Education, Malaysia		MOHE

1  
This research is supported by a grant from Malaysia Ministry of Higher Education for RIGS grant scheme (RIGS16-338-0502).

2  
This work was supported by the Ministry of Higher Education, Malaysia [ANGKASA (SP15-063-0185)].

ISSN: 1448837X  
Source Type: Journal  
Original language: English

DOI: 10.1080/1448837X.2019.1624245  
Document Type: Article  
Publisher: Taylor and Francis Ltd.

👤 Hasbullah, N.F.; Electrical and Computer Engineering, International Islamic University, Kuala Lumpur, Malaysia;  
© Copyright 2019 Elsevier B.V., All rights reserved.

## About Scopus

What is Scopus  
Content coverage  
Scopus blog  
Scopus API  
Privacy matters

## Language

日本語に切り替える  
切换到简体中文  
切换到繁體中文  
Русский язык

## Customer Service

Help  
Contact us

**ELSEVIER**

[Terms and conditions](#) ↗ [Privacy policy](#) ↗

Copyright © Elsevier B.V. ↗. All rights reserved. Scopus® is a registered trademark of Elsevier B.V.

We use cookies to help provide and enhance our service and tailor content. By continuing, you agree to the use of cookies.

 RELX