

Document details

[< Back to results](#) | 1 of 1

[↗ Export](#) [↓ Download](#) [🖨 Print](#) [✉ E-mail](#) [📄 Save to PDF](#) [★ Add to List](#) [More... >](#)

[Full Text](#) [View at Publisher](#)

IIUM Engineering Journal [Open Access](#)
Volume 20, Issue 1, 2019, Pages 245-257

Magnetically plucked piezoelectric energy harvester via hybrid kinetic motion (Article) ([Open Access](#))

Azam, H.^a, Hanif, N.H.H.M.^a [✉](#), Ralib, A.A.M.^b [👤](#)

^aDepartment of Mechatronics Engineering, International Islamic University Malaysia, P.O. Box 10, Kuala Lumpur, 50728, Malaysia

^bDepartment of Electronic and Computer Engineering, International Islamic University Malaysia, P.O. Box 10, Kuala Lumpur, 50728, Malaysia

Abstract

[View references \(23\)](#)

Piezoelectric energy harvesting is a possible breakthrough to reduce the global issue of electronic waste as they can efficiently convert the ambient vibration to the electrical energy without any additional power. This work presents the design and development of a piezoelectric energy harvester that is capable of transforming vibration from ambient sources into electricity. It focuses on a magnetically plucked piezoelectric beam as an alternative to the mechanically induced harvesters, as the latter are subjected to wear and tear. A prototype comprising of a 40 mm PZT-5H piezoelectric beam with a permanent magnet mounted at one end of the beam, as well as a series of permanent magnets of same types attached on an eccentric rotor was developed along with a National Instruments® data acquisition device. Mean output voltages of 2.98 V, 1.76 V and 0.34 V were recorded when the eccentric rotors were slowly rotated at 8.4 rad/s with increasing distances of 5 mm, 7.5 mm and 10 mm respectively, between the magnets on the rotor and the beam. These results have proven that voltage could also be

ISSN: 1511788X

Source Type: Journal

Original language: English

DOI: 10.31436/iiumej.v20i1.981

Document Type: Article

Publisher: International Islamic University Malaysia-IIUM


References (23)


[View in search results format >](#)

All

[Export](#)

 [Print](#)

 [E-mail](#)

 [Save to PDF](#)

[Create bibliography](#)

1

Priya, S.

[Advances in energy harvesting using low profile piezoelectric transducers](#)

(2007) *Journal of Electroceramics*, 19 (1), pp. 165-182. Cited 620 times.

doi: 10.1007/s10832-007-9043-4

[View at Publisher](#)

2

Poulin, G., Sarraute, E., Costa, F.

[Generation of electrical energy for portable devices: Comparative study of an electromagnetic and a piezoelectric system](#)

(2004) *Sensors and Actuators, A: Physical*, 116 (3), pp. 461-471. Cited 209 times.

doi: 10.1016/j.sna.2004.05.013

[View at Publisher](#)

3

Pozzi, M., Zhu, M.

[Plucked piezoelectric bimorphs for knee-joint energy harvesting: Modelling and experimental validation](#)