

< Back to results | 1 of 1

Export Download Print E-mail Save to PDF Add to List More... >

View at Publisher

International Journal of Chemical Engineering [Open Access](#)
Volume 2019, 2019, Article number 5743590

Column Efficiency of Fluoride Removal Using Quaternized Palm Kernel Shell (QPKS) (Article) [\(Open Access\)](#)

Abu Bakar, A.H.^{a,b} , Abdullah, L.C.^{a,c} , Mohd Zahri, N.A.^d , Alkhatib, M.^e  

^aDepartment of Chemical and Environmental Engineering, Faculty of Engineering, Universiti Putra Malaysia, 43400 UPM Serdang, Selangor D.E., Malaysia

^bDepartment of Chemical and Petroleum Engineering, Faculty of Engineering, Technology and Built Environment, UCSI University, Cheras, Kuala Lumpur, 56000, Malaysia

^cInstitute of Tropical Forestry and Forest Products (INTROP), Universiti Putra Malaysia, UPM Serdang, Selangor D.E., 43400, Malaysia

View additional affiliations 

Abstract

 View references (42)

In this research, the adsorption potential of quaternized palm kernel shell (QPKS) to remove F⁻ from aqueous solution was investigated using fixed-bed adsorption column. Raw palm kernel shell waste was reacted with 3-chloro-2-hydroxypropyl trimethylammonium chloride (CHMAC) in order to modify the surface charge. The effects of inlet F⁻ concentrations (2-12 mg/l) and QPKS bed height (2-10 cm) with optimum pH (pH = 3) on the breakthrough characteristics of the adsorption system were determined. In the fixed-bed column, breakthrough time increases with increasing bed height due to increasing amount of active site on adsorbents to adsorb the fluoride ion. Decreasing trend of breakthrough values was obtained with increasing initial fluoride concentration due to greater driving force for the transfer process to overcome the mass transfer resistance in the column. The adsorptions were fitted to three well-established fixed-bed adsorption models, namely, Thomas, Yoon-Nelson, and Adams-Bohart models. The results fitted well to the Thomas and Yoon-Nelson models with correlation coefficient, $R^2 \geq 0.96$. © 2019 Ayu Haslija Abu Bakar et al.

Indexed keywords

Engineering controlled terms:

Chlorine compounds Fluorine compounds Mass transfer

Engineering uncontrolled terms

Adsorption potential Breakthrough time Correlation coefficient Fixed bed columns
Fixed-bed adsorption Fluoride concentrations Mass transfer resistances Palm kernel shells

Engineering main heading:

Adsorption

Funding details

Funding text

+e authors express their sincere gratitude to Chemical and Environmental Engineering Department of University Putra Malaysia and Faculty of Engineering, Technology and Built Environment, UCSI University, for the support given to this research project.

Metrics

0 Citations in Scopus

0 Field-Weighted Citation Impact



PlumX Metrics 

Usage, Captures, Mentions, Social Media and Citations beyond Scopus.

Cited by 0 documents

Inform me when this document is cited in Scopus:

[Set citation alert >](#)

[Set citation feed >](#)

Related documents

Defluoridation in fixed bed column filled with Zr(IV)-loaded garlic peel

Zhang, Y. , Xiong, L. , Xiu, Y. (2019) *Microchemical Journal*

Fluoride removal using simple protonated and xanthate modified protonated ficus religiosa branch powder in a fixed-bed column

Tariq, M. , Farooq, U. , Athar, M. (2019) *Desalination and Water Treatment*

Effective removal of Fluoride ions by rGO/ZrO₂ nanocomposite from aqueous solution: Fixed bed column adsorption modelling and its adsorption mechanism

Mohan, S. , Singh, D.K. , Kumar, V. (2017) *Journal of Fluorine Chemistry*

View all related documents based on references

Find more related documents in Scopus based on:

References (42)

[View in search results format >](#)

All Export Print E-mail Save to PDF Create bibliography

-
- 1 Shen, F., Chen, X., Gao, P., Chen, C.
Electrochemical removal of fluoride ions from industrial wastewater
(2003) *Chemical Engineering Science*, 58 (3-6), pp. 987-993. Cited 293 times.
<http://www.journals.elsevier.com/chemical-engineering-science/>
doi: 10.1016/S0009-2509(02)00639-5
[View at Publisher](#)
-
- 2 Lv, L., He, J., Wei, M., Evans, D.G., Zhou, Z.
Treatment of high fluoride concentration water by MgAl-CO₃ layered double hydroxides: Kinetic and equilibrium studies
(2007) *Water Research*, 41 (7), pp. 1534-1542. Cited 167 times.
doi: 10.1016/j.watres.2006.12.033
[View at Publisher](#)
-
- 3 Ruan, Z., Tian, Y., Ruan, J., Cui, G., Iqbal, K., Iqbal, A., Ye, H., (...), Yan, S.
Synthesis of hydroxyapatite/multi-walled carbon nanotubes for the removal of fluoride ions from solution
(2017) *Applied Surface Science*, 412, pp. 578-590. Cited 16 times.
<http://www.journals.elsevier.com/applied-surface-science/>
doi: 10.1016/j.apsusc.2017.03.215
[View at Publisher](#)
-
- 4 WHO, Guidelines for Drinking Water Quality, World Health Organization, Geneva, Switzerland, 4th edition, 2011
-
- 5 Roy, S., Dass, G.
Fluoride contamination in drinking water-A review
(2013) *Resources and Environment*, 3 (3), pp. 53-58. Cited 15 times.
-
- 6 Onyango, M.S., Matsuda, H.
Chapter 1 Fluoride Removal from Water Using Adsorption Technique
(2006) *Advances in Fluorine Science*, 2 (C), pp. 1-48. Cited 47 times.
doi: 10.1016/S1872-0358(06)02001-X
[View at Publisher](#)
-
- 7 Santhy, K., Selvapathy, P.
Removal of reactive dyes from wastewater by adsorption on coir pith activated carbon
(2006) *Bioresource Technology*, 97 (11), pp. 1329-1336. Cited 204 times.
doi: 10.1016/j.biortech.2005.05.016
[View at Publisher](#)
-