



# Document details

1 of 1

[Export](#) [Download](#) [More... >](#)

IOP Conference Series: Materials Science and Engineering  
 Volume 670, Issue 1, 2 December 2019, Article number 012013  
 6th International Conference on Applications and Design in Mechanical Engineering 2019, ICADME 2019; Penang Island; Malaysia; 26 August 2019 through 27 August 2019; Code 156586

## Evaporation lifetime and boiling curve on hemispherical stainless steel (304) surface (Conference Paper) [\(Open Access\)](#)

Illias, S., Hussain, S., Rosman, N.A., Abdullah, N.S., Shaiful, A.I.M., Omar, M.N.B., Ismail, K.A., Ani, H.

[View additional authors](#)

[Save all to author list](#)

<sup>a</sup>School of Manufacturing Engineering, Universiti Malaysia Perlis, Pauh Putra Campus, Perlis, Arau, 02600, Malaysia

<sup>b</sup>Department of Manufacturing and Materials, Kulliyah of Engineering, International Islamic University Malaysia, PO Box 10, Kuala Lumpur, 50728, Malaysia

[View additional affiliations](#)

### Abstract

The purpose of this research is to study and investigate the evaporation lifetime and boiling curve on hemispherical heated surface. The selected material was stainless steel (304). A nearly perfect and smooth hemispherical surface was developed by using EDM die sinker. For the test liquid, distilled water was used during the experimental work. The average droplet temperature was 31.36 °C corresponding to liquid subcooling  $\Delta T_{sub} = 68.64K$ . Based on the theoretical calculation, the diameter of the water droplet was approximately 5.00 mm. Meanwhile, the impact height was approximately 65.0 mm corresponding to the theoretical impact velocity of 1.129 m/s. The material was heated using a digital hot plate which was able to give an accurate reading and stable temperature fluctuation during the heating process. The temperature ranged from a low temperature of  $T_w = 100$  °C to a high temperature of  $T_w = 300$  °C. As a result, the boiling curve showed a similar pattern of other experimental work that consists of two (2) important points which are Critical Heat Flux(CHF) and Leidenfrost temperature. © Published under licence by IOP Publishing Ltd.

### SciVal Topic Prominence

Topic: [Spray steelmaking](#) | [Heat flux](#) | [Boiling regime](#)

Prominence percentile: 92.495

### Funding details

Funding sponsor	Funding number	Acronym
	FRGS/1/2018/TK03/UNIMAP/02/11	

1

The authors would like to thank the Ministry of Education Malaysia and the Research Management and Innovation Centre of Universiti Malaysia Perlis (project number: FRGS/1/2018/TK03/UNIMAP/02/11) for awarding a research grant to undertake this project.

Cited by 0 documents

Inform me when this document is cited in Scopus:

[Set citation alert >](#)

[Set citation feed >](#)

### Related documents

Find more related documents in Scopus based on:

[Authors >](#)

ISSN: 17578981

Source Type: Conference Proceeding

Original language: English

DOI: 10.1088/1757-899X/670/1/012013

Document Type: Conference Paper

Volume Editors: Majid M.S.A., Jamir M.R.M., Choon T.W., Rahman A.A.

Publisher: Institute of Physics Publishing

© Copyright 2020 Elsevier B.V., All rights reserved.

## About Scopus

[What is Scopus](#)

[Content coverage](#)

[Scopus blog](#)

[Scopus API](#)

[Privacy matters](#)

## Language

[日本語に切り替える](#)

[切换到简体中文](#)

[切换到繁體中文](#)

[Русский язык](#)

## Customer Service

[Help](#)

[Contact us](#)

**ELSEVIER**

[Terms and conditions ↗](#) [Privacy policy ↗](#)

Copyright © Elsevier B.V. ↗. All rights reserved. Scopus® is a registered trademark of Elsevier B.V.

We use cookies to help provide and enhance our service and tailor content. By continuing, you agree to the use of cookies.

 RELX