



Document details

< Back to results | 1 of 1

[↗ Export](#)
[⬇ Download](#)
[🖨 Print](#)
[✉ E-mail](#)
[📄 Save to PDF](#)
[★ Add to List](#)
[More... >](#)
[Full Text](#)[View at Publisher](#)

Journal of Mechanical Science and Technology
Volume 34, Issue 1, 1 January 2020, Pages 469-475

Optimum spacing between grooved tubes : An experimental study

(Article)

Afzal, A.^a , Mohammed Samee, A.D.^b, Abdul Razak, R.K.^a, Khan, S.A.^c, Khan, H.^d ^aDepartment of Mechanical Engineering, P. A. College of Engineering, Visvesvaraya Technological University, Mangaluru, India^bDepartment of Mechanical Engineering, N. K. Orchid College of Engineering, Solapur, India^cDepartment of Mechanical Engineering, International Islamic University Malaysia, Kuala Lumpur, Malaysia[View additional affiliations](#) ∨

Abstract

[∨ View references \(35\)](#)

An experimental study on optimum spacing between grooved tubes is reported in this paper. Two grooved tubes having pitch of 10 mm and 15 mm and a plain tube were considered for the heat transfer analysis. The spacing between two tubes with same pitch was varied from 10 mm to 35 mm with a step size of 5 mm. Velocity of air flowing over the tube surfaces was changed from 0.4 m/s to 1 m/s using a blower fan. Based on Nusselt number (Nu) the optimum spacing between the tubes was decided. The optimum spacing between grooved tubes of pitch 10 mm and 15 mm was compared with that of plain tubes. From the experimental analysis it was noticed that with increase in air velocity (increase in Reynolds number) the tube surface temperature reduced irrespective of any tube considered. Nu increased with increase in air velocity for all the tubes. The important conclusion drawn from the present study was that, there exists a limiting spacing (optimum) between the tubes above which no change in Nu was observed. Spacing of 30 mm was found to be the optimum spacing between the tubes irrespective of its surface geometry modifications. © 2020, The Korean Society of Mechanical Engineers and Springer-Verlag GmbH Germany, part of Springer Nature.

SciVal Topic Prominence ⓘ

Topic: Condensation | Heat transfer coefficients | Flow condensation

Prominence percentile: 95.947



Author keywords

[Grooved tubes](#)
[Grooves](#)
[Heat transfer](#)
[Nusselt number](#)
[Optimum spacing](#)

Indexed keywords

Engineering controlled terms:

[Air](#)
[Heat transfer](#)
[Nusselt number](#)
[Reynolds equation](#)
[Reynolds number](#)

Engineering uncontrolled terms

[Air velocities](#)
[Experimental analysis](#)
[Grooved tubes](#)
[Grooves](#)
[Heat transfer analysis](#)
[Optimum spacing](#)
[Surface geometries](#)
[Surface temperatures](#)
[Metrics ⓘ](#) [View all metrics >](#)

PlumX Metrics



Usage, Captures, Mentions,
Social Media and Citations
beyond Scopus.

Cited by 0 documents

Inform me when this document
is cited in Scopus:

[Set citation alert >](#)[Set citation feed >](#)

Related documents

Investigation of heat transfer and fluid flow over pocket cavity in the rear part of gas turbine

Liu, J. , Wang, C. , Wang, L.
(2016) *ASME International Mechanical Engineering Congress and Exposition, Proceedings (IMECE)*

Turbulent flow and heat transfer enhancement in rectangular channels with novel cylindrical grooves

Liu, J. , Xie, G. , Simon, T.W.
(2015) *International Journal of Heat and Mass Transfer*

Heat transfer and turbulent flow characteristics over pocket cavity in the junction part of an outlet guide vane in a gas turbine

Liu, J. , Hussain, S. , Wang, L.
(2017) *Applied Thermal Engineering*

[View all related documents based on references](#)

[Find more related documents in Scopus based on:](#)

ISSN: 1738494X

Source Type: Journal

Original language: English




DOI: 10.1007/s12206-019-1244-7

Document Type: Article

Publisher: Korean Society of Mechanical Engineers

References (35)

[View in search results format >](#)

☐ All [Export](#)  Print  E-mail  Save to PDF [Create bibliography](#)

- ☐ 1 Chang, T.-H., Lee, K.-S., Chang, K.-W., Kim, S.M., Lee, C.-H.
Heat transfer characteristics of a short helical plate in a horizontal circular tube

(2019) *Journal of Mechanical Science and Technology*, 33 (8), pp. 3613-3620.
<http://www.springerlink.com/content/1738-494X>
doi: 10.1007/s12206-019-0701-7

[View at Publisher](#)

- ☐ 2 Arani, A.A.A., Kazemi, M.
Analysis of fluid flow and heat transfer of nanofluid inside triangular enclosure equipped with rotational obstacle
(2019) *Journal of Mechanical Science and Technology*, pp. 1-13.

- ☐ 3 Ali, M.S., Sharma, N., Tariq, A.
Heat transfer and flow field features between surface mounted trapezoidal-ribs

(2019) *Journal of Mechanical Science and Technology*, 33 (10), pp. 5017-5023.
<http://www.springerlink.com/content/1738-494X>
doi: 10.1007/s12206-019-0940-7

[View at Publisher](#)

- ☐ 4 Afzal, A., Samee, A.D.M., Razak, R.K.A.
Experimental thermal investigation of CuO-W nanofluid in circular minichannel
(2017) *Modelling Measurement and Control B*, 86 (2), pp. 335-344. Cited 12 times.

- ☐ 5 Darzi, A.A.R., Farhadi, M., Sedighi, K., Shafaghat, R., Zabihi, K.
Experimental investigation of turbulent heat transfer and flow characteristics of SiO₂/water nanofluid within helically corrugated tubes

(2012) *International Communications in Heat and Mass Transfer*, 39 (9), pp. 1425-1434. Cited 54 times.
doi: 10.1016/j.icheatmasstransfer.2012.07.027

[View at Publisher](#)