To our beloved Sensei Prof. Susumu Horiguchi

Acknowledgments

All praises goes to Almighty Allah (swt), the most merciful and sustainer, who has been showering his endless blessings on the author throughout of his life.

The authors are very much pleased to express my sincere and profound gratitude and profuse heartfelt thanks to late Prof. Susumu Horiguchi of GSIS at Tohoku university for his constant encouragement and kind guidance during this research work. We are deeply grateful to him for his enthusiasm and insight, which have made research a most enjoyable and fulfilling experience. His phenomenal depth of knowledge and ability to discern the key points of the research problem inspire us a lot. We are both incredibly proud and immensely lucky to become his students.

We have learned much from discussion with colleagues over the years including Prof. Y. Hibino (JAIST), Prof. M. Kaneko (JAIST), Dr. Y. Miura (Shonan IT), Dr. M. Fukushi (GSIS, Tohoku Univ), Dr. Y. Fukushima(Sophia Univ., Tokyo), Dr. R. Hayashi (Kanazawa IT), E. Horiguchi (JAIST) for their helpful discussion, comments, and suggestions during this research work. The authors are indebted to the to the Ministry of Education, Science, Sports, and Culture, Japan for the financial support of this research work.

Last but not least, the authors are heartfelt thankful to their family members for their bountiful forbearance and significant sacrifice and encouragement. They were putting up with many dreary evenings and weekends when we were doing this research work. Their tolerance an understanding made it possible for us to complete this endeavor.

Contents

A	Acknowledgments ii			
1	Intr 1.1 1.2 1.3 1.4	oducti Introd Interco Motiva Contri	on uction	1 1 2 6 8
	1.5	Synop	sis of this Book	9
2	Inte	rconne	ection Networks for Massively Parallel Computers	11
	2.1	Introd	uction	11
	2.2	Definit	tions \ldots	13
		2.2.1	Fundamental Definitions	13
		2.2.2	Topological Characteristics of Interconnection Networks	13
		2.2.3	Layout Characteristics of Interconnection Networks	14
		2.2.4	Dynamic Communication Performance Metrics	14
	2.3	Interco	onnection Network Topologies	14
		2.3.1	Completely-Connected Networks	15
		2.3.2	Star Networks	15
		2.3.3	Tree Networks	16
		2.3.4	Hypercubic Networks	19
		2.3.5	Array Networks	21
	2.4	Hierar	chical Interconnection Network (HIN)	24
		2.4.1	Completely-Connected Network based HIN	25
		2.4.2	Tree Network based HIN	27
		2.4.3	Hypercube Network based HIN	28
		2.4.4	Array Network based HIN	30
	2.5	Conclu	sions	35
3	Hier	rarchic	cal Torus Network (HTN)	36
	3.1	Introd	uction	36
	3.2	Archit	ecture of the HTN	37
		3.2.1	Basic Module	37
		3.2.2	Higher Level Interconnection	38
		3.2.3	Addressing and Routing	40
	3.3	Static	Network Performance	43

		3.3.1	Node Degree	. 43
		3.3.2	Diameter	. 44
		3.3.3	Average Distance	. 46
		3.3.4	Cost	. 48
		3.3.5	Connectivity	. 48
		3.3.6	Bisection Width	. 49
	3.4	Wafer	Stacked Implementation	. 51
		3.4.1	3D Stacked Implementation	. 51
		3.4.2	Peak Number of Vertical Links	. 51
		3.4.3	Layout Area	. 56
		3.4.4	Maximum Wire Length	. 60
	3.5	Conclu	usions	. 62
1	Dvr	omic	Communication Performance of the HTN	63
4	1 1	Introd	uction	63
	4.1 4.2	Routi	ng Algorithm	. 00 64
	4.2	<i>1</i> 2 1	Resources and Allocation Units	. 05
		4.2.1	Taxonomy of Bouting Algorithm	. 00
		4.2.2	Primitive Considerations	. 00
		4.2.5	Channel Dependency Graph	. 01
	13	4.2.4 Dimor	Sion-Order Bouting (DOB) for HTN	. 10
	4.0	131	Bouting Algorithm for HTN	. 10
		4.3.1	Deadlock-free Bouting	. 11
		4.3.2	Minimum Number of Virtual Channels	· 13
	1.1	4.0.0 Dynar	nic Communication Performance using DOR	. 02
	4.4	1 1 1	Porformance of Interconnection Networks	. 00
		4.4.1	Simulation Environment	. 00
		4.4.2	Traffic Pattorns	. 04
		4.4.5	Dynamic Communication Performance Evaluation	. 00
		4.4.5	Effect of Message Longth	102
		4.4.5	Effect of the Number of Virtual Channels	. 102
	15	4.4.0 Adopt	ive Routing	. 105
	4.0	151	Link Selection (LS) Algorithm	106
		4.5.1	Channel-Selection (CS) Algorithm	100
		4.5.2	Combination of LS and CS (LS \pm CS) Algorithm	. 100
		4.5.4	Deadlock-Free Bouting	. 110
	4.6	Route	r Cost and Speed	113
	1.0	461	Router Gate Counts	113
		462	Router Speed	114
	47	T.U.2 Dynar	nic Communication Performance using Adaptive Routing	. 117
	4.8	Conclu		. 122
_	D	C		10-
5	Kec	onfigu	ration Architecture and Application Mappings	125
	5.1	Introd		. 125
	5.2	Kecon	nguration Architecture of the HTN	. 126
		5.2.1	Reconfiguration Scheme	. 126

6	5.3 5.4 Pru	5.2.2System Yield of the HTN127Application Mappings on HTN1315.3.1Converge and Diverge1325.3.2Bitonic Merge1325.3.3Fast Fourier Transform (FFT)1345.3.4Finding the Maximum1355.3.5Processing Time135Conclusions141 142
	6.1 6.2	Introduction 142 Pruned Network 143 5.2.1 Pruned Torus Network 143 5.2.2 Pruned HTN 145
	6.3	BD-WSI Implementation of the Pruned HTN 147 5.3.1 Peak Number of Vertical Links 147 5.3.2 Layout Area 147 Conclusion 147
	0.4	\mathcal{L} onclusion
7	Mo	fication of other Hierarchical Networks based on Torus-Torus In-
	terc	nnection 150
	7.1	ntroduction
	7.2	Modified Hierarchical 3D-Torus Network
		(.2.1 Interconnection of the MH3D1 Network
		(.2.2 Routing Algorithm
		$(2.3 \text{Deadlock-Free Routing} \dots \dots$
		7.2.4 Static Network Performance
		(2.5 Dynamic Communication Performance
	7.9	$(2.0 \text{Summary} \dots \dots \dots \dots \dots \dots \dots \dots \dots $
	1.3	$\begin{array}{llllllllllllllllllllllllllllllllllll$
		(.5.1 Interconnection of the 11N
		7.3.2 Routing Algorithm
		7.3.4 Static Notwork Performance 168
		7.3.5 Dynamic Communication Performance 160
		7.3.6 Summary 179
	7.4	$Conclusion \dots \dots$
8	Cor	lusions
0	81	introduction 173
	8.2	Conclusions $\dots \dots \dots$
	8.3	Future Directions
	Ref	rences 178
	Ind	x 191

List of Figures

2.1	Completely-connected networks for $N = 4$, $N = 8$, and $N = 12$	15
2.2	(a) A star-connected network of nine nodes (b) Star graph network	16
2.3	A 15 node binary tree network	17
2.4	A 15 node X-tree network	17
2.5	The 2D mesh-of-trees. Leaf nodes from the original grid are denoted with	
	black circles. Nodes added to form row trees are denoted with red squares,	
	and nodes added to form column trees are denoted with blue squares	18
2.6	A fat-tree network	18
2.7	The Binary cube networks of zero, one, two, three, and four dimensions,	
	the nodes are labeled using n -bit binary numbers. \ldots \ldots \ldots	20
2.8	(a) The 3-dimensional binary cube network (b) The 3-dimensional CCC.	
	Labels for individual nodes in the CCC are binary cube node label and the	
	adjacent link label.	21
2.9	A four-node linear array and ring network	22
2.10	A layout for a ring network which minimizes link lengths $(N = 8)$	22
2.11	2D mesh and torus networks with 4 nodes in each dimension	23
2.12	3D mesh and torus networks with 4 nodes in each dimension	24
2.13	A level-2 MFC network with 8 clusters and the cluster size is 8	26
2.14	An example of 16-node swapped network with the 4-node complete graph	
	as its basis.	26
2.15	A pyramid network of 16 node	27
2.16	A hierarchical clique network	28
2.17	Fibonacci cubes	29
2.18	A HCN $(2,2)$ network	30
2.19	Recursive diagonal torus network	31
2.20	Standard 1D-SRT consisting of 32 nodes	32
2.21	Level-2 interconnection of TESH network	33
2.22	Interconnection of a Level-2 H3D-torus network	34
2.23	Interconnection of a Level-2 H3D-mesh network	35
3.1	Interconnection of HTN	37
3.2	Basic module of the HTN	38
3.3	Interconnection of a Level-2 HTN	39
3.4	Interconnection of a Level-3 HTN	39
3.5	Routing algorithm of the HTN	42
3.6	Illustration of degree of HTN	43
3.7	Diameter of networks as a function of number of nodes (N)	45
3.8	Average distance of networks as a function of number of nodes (N)	47

3.9	Average distance of various networks with 4096 nodes.	47
3.10	Cost of different networks as a function of number of nodes (N)	48
3.11	Illustration of connectivity for 2D-mesh network.	49
3.12	Bisection width of networks as a function of number of nodes (N)	50
3.13	Structure of 3D stacked implementation	52
3.14	Structure of microbridge and feedthrough	52
3.15	PE array in a silicon plane for wafer stacked-implementation	53
3.16	Vertical links of 2D-mesh network in 3D wafer stacked-implementation	53
3.17	Vertical links of 2D-torus network in 3D wafer stacked-implementation	53
3.18	Interconnection scheme of 2D-torus in 3D stacked implementation	54
3.19	A comparison of peak number of vertical links of HTN with other networks	56
3.20	Layout area of 2D-torus for $N = 16$, $L = 4$ and $p = 1 $	58
3.21	Normalized layout area	60
3.22	2D-planner realization of 3D-torus network.	61
4.1	Units of resource allocation.	66
4.2	Wormhole routing	68
4.3	An example of the blocked wormhole-routed message	68
4.4	Time-space diagram of a wormhole-routed message	69
4.5	An example of deadlock involving four packets	70
4.6	Virtual channel	71
4.7	Message blocking while physical channels remain idle	72
4.8	Virtual channel allows to pass blocked message	72
4.9	(a) A ring network with unidirectional channels. (b) The associated channel	
	dependency graph contains a cycle. (c) Each physical channel is logically	
	split into two virtual channels. (d) A modified channel dependency graph	
	without cycles.	74
4.10	Deadlock configuration in (a) mesh network (b) torus network	76
4.11	A set of routing paths created by the dimension order routing in a 2D-mesh	
	network	77
4.12	Dimension-order routing algorithm for HTN	80
4.13	An example of message routing in HTN	81
4.14	Nonuniform traffic patterns on a 8×8 mesh networks: (a) dimension-	
	reversal traffic and (b) bit-reversal traffic	87
4.15	Dynamic communication performance of dimension-order routing with uni-	
	form traffic pattern on various networks: (a) 1024 nodes, different virtual	
	channels, short message, and $q = 0$ (b) 1024 nodes, 3 virtual channels,	
	short message, and $q = 0$	90
4.16	Dynamic communication performance of dimension-order routing with uni-	
	form traffic pattern on various networks: (a) 256 nodes, 3 virtual channels,	
	short message, and $q = 1$ (b) 512 nodes, 3 virtual channels, short message,	
	and $q = 1$, (c) 1024 nodes, 3 virtual channels, short message, and $q = 1$,	
	(d) 1024 nodes, 3 virtual channels, medium-length message, and $q = 1$, (e)	
	1024 nodes, 3 virtual channels, long message, and $q = 1, \ldots \ldots$	91

4.17 Dynamic communication performance of dimension-order routing with uniform traffic pattern on various networks: (a) 256 nodes, 2 virtual channels, short message, and q = 1 (b) 256 nodes, 2 virtual channels, medium-length message, and q = 1, (c) 256 nodes, 2 virtual channels, long message, and q = 1, (d) 1024 nodes, 2 virtual channels, short message, and q = 1, (e) 1024 nodes, 2 virtual channels, medium-length message, and q = 1, and (f) 924.18 Dynamic communication performance of dimension-order routing with hotspot traffic pattern on various networks: (a) 256 nodes, 3 virtual channels, 5% hot-spot traffic, short message, and q = 1 (b) 512 nodes, 3 virtual channels, 5% hot-spot traffic, short message, and q = 1, and (c) 1024 nodes, 3 virtual channels, 5% hot-spot traffic, short message, and q = 1 . . 944.19 Dynamic communication performance of dimension-order routing with hotspot traffic pattern on various networks: (a) 256 nodes, 3 virtual channels, 2% hot-spot traffic, short message, and q = 1 (b) 256 nodes, 3 virtual channels, 10% hot-spot traffic, short message, and q = 1, (c) 1024 nodes, 3 virtual channels, 2% hot-spot traffic, short message, and q = 1, and (d) 1024 nodes, 3 virtual channels, 10% hot-spot traffic, short message, and 95 4.20 Dynamic communication performance of dimension-order routing with dimension reversal traffic pattern on various networks: (a) 256 nodes, 3 virtual channels, 2-dimensional reversal traffic, short message, and q = 1 (b) 1024 node, 3 virtual channels, 2-dimensional reversal traffic, short message, and q = 1, (c) 256 nodes, 3 virtual channels, 3-dimensional reversal traffic, short message, and q = 1, (d) 1024 nodes, 3 virtual channels, 3-dimensional reversal traffic, short message, and $q = 1, \ldots, \ldots, \ldots, \ldots, \ldots$ 97 4.21 Dynamic communication performance of dimension-order routing with bitreversal traffic pattern on various networks: (a) 256 nodes, 3 virtual channels, short message, and q = 1 (b) 512 nodes, 3 virtual channels, short message, and q = 1, (c) 1024 nodes, 3 virtual channels, short message, and q = 1, (d) 1024 nodes, 3 virtual channels, medium-length message, and q = 1, and (e) 1024 nodes, 3 virtual channels, long message, and q = 1. 98 4.22 Dynamic communication performance of dimension-order routing with complement traffic pattern on various networks: (a) 256 nodes, 3 virtual channels, short message, and q = 1, (b) 512 nodes, 3 virtual channels, short message, and q = 1, (c) 1024 nodes, 3 virtual channels, short message, and q = 1 (d) 1024 nodes, 3 virtual channels, medium-length message, and q = 1, and (e) 1024 nodes, 3 virtual channels, long message, and q = 1. . . 100 4.23 Dynamic communication performance of dimension-order routing with bitflip traffic pattern on various networks: (a) 256 nodes, 2 virtual channels, short message, and q = 1 and (b) 1024 nodes, 2 virtual channels, short message, and $q = 1. \ldots 101$ 4.24 Dynamic communication performance of large-size HTN by dimensionorder routing under various traffic patterns: 3 virtual channels, short message.102 4.25 Average message latency divided by message length vs. network throughput of HTN: 1024 nodes, 2 VCs, and q = 1....103

ferent virtual channels and short message on the large-size HTN: (a) hot spot traffic, (b) bit reversal traffic, (c) 2-dimension reversal, (d) 3-dimension reversal, and (c) complement traffic patterns	4.26	Dynamic communication performance of dimension-order routing with dif-	
spot traffic, (b) bit reversal traffic, (c) 2-dimension reversal, (d) 3-dimension reversal, and (e) complement traffic patterns		ferent virtual channels and short message on the large-size HTN: (a) hot	
reversal, and (e) complement traffic patterns		spot traffic, (b) bit reversal traffic, (c) 2-dimension reversal, (d) 3-dimension	
 4.27 Routing messages in a 6 × 6 mesh from node (0, i) to node (i, 5) (for 0 ≤ i ≤ 5); (a) Using dimension order routing, five messages must traverse the channel from (0, 4) to (0, 5), (b) Using adaptive routing, all messages proceed simultaneously		reversal, and (e) complement traffic patterns	. 104
$\begin{split} i \leq 5; (a) Using dimension order routing, five messages must traverse the channel from (0, 4) to (0, 5), (b) Using adaptive routing, all messages proceed simultaneously $	4.27	Routing messages in a 6×6 mesh from node $(0, i)$ to node $(i, 5)$ (for $0 \leq$	
the channel from $(0, 4)$ to $(0, 5)$, (b) Using adaptive routing, all messages proceed simultaneously		$i \leq 5$; (a) Using dimension order routing, five messages must traverse	
 proceed simultaneously		the channel from $(0,4)$ to $(0,5)$, (b) Using adaptive routing, all messages	
 4.28 Å 6 × 6 mesh with a faulty link from node (3, 2) to node (3, 3). (a) With dimension order routing messages from dark nodes to the shaded area cannot be delivered. (b) With adaptive routing, messages can be delivered between all pairs of nodes		proceed simultaneously.	. 106
 dimension order routing messages from dark nodes to the shaded area cannot be delivered. (b) With adaptive routing, messages can be delivered between all pairs of nodes. 107 4.29 Selection of physical link by link-selection algorithm . 108 4.30 Link-selection algorithm for HTN . 109 4.31 Selection of virtual channels by channel-selection algorithm . 110 4.32 A block diagram of router architecture . 114 4.33 Comparison of dynamic communication performance of the HTN between DOR, LS, CS, and LS+CS algorithms with uniform traffic pattern: 1024 nodes, 3 virtual channels, and q = 1. 1204 nodes, 3 virtual channels, short message, and q = 1. 1204 nodes, 3 virtual channels, 16 flits, and q = 1. 120 4.36 Comparison of dynamic communication performance of the HTN between DOR, LS, CS, and LS+CS algorithms with bit-reversal traffic pattern: 1024 nodes, 3 virtual channels, 16 flits, and q = 1. 120 4.36 Comparison of dynamic communication performance of the HTN between DOR, LS, CS, and LS+CS algorithms with bit-flip traffic pattern: 1024 nodes, 3 virtual channels, 16 flits, and q = 1. 121 4.37 Comparison of dynamic communication performance of the HTN between DOR, LS, CS, and LS+CS algorithms with perfect shuffle traffic pattern: 1024 nodes, 3 virtual channels, short message, and q = 1. 121 4.37 Comparison of dynamic communication performance of the HTN between DOR, LS, CS, and LS+CS algorithms with perfect shuffle traffic pattern: 1024 nodes, 3 virtual channels, short message, and q = 1. 121 4.38 Dynamic communication performance of the HTN between DOR, LS, CS, and LS+CS algorithms with perfect shuffle traffic pattern: 1024 nodes, 3 virtual channels, short message, and q = 1. 124 nodes, 3 virtual channels, short message, and q = 1. 125. 125. 126 traffic pattern: 1024 nodes, 127 <l< td=""><td>4.28</td><td>A 6×6 mesh with a faulty link from node (3, 2) to node (3, 3). (a) With</td><td></td></l<>	4.28	A 6×6 mesh with a faulty link from node (3, 2) to node (3, 3). (a) With	
 not be delivered. (b) With adaptive routing, messages can be delivered between all pairs of nodes		dimension order routing messages from dark nodes to the shaded area can-	
between all pairs of nodes		not be delivered. (b) With adaptive routing, messages can be delivered	
 4.29 Selection of physical link by link-selection algorithm		between all pairs of nodes.	. 107
 4.30 Link-selection algorithm for HTN	4.29	Selection of physical link by link-selection algorithm	. 108
 4.31 Selection of virtual channels by channel-selection algorithm	4.30	Link-selection algorithm for HTN	. 109
 4.32 A block diagram of router architecture	4.31	Selection of virtual channels by channel-selection algorithm	. 110
 4.33 Comparison of dynamic communication performance of the HTN between DOR, LS, CS, and LS+CS algorithms with uniform traffic pattern: 1024 nodes, 3 virtual channels, and q = 1	4.32	A block diagram of router architecture	. 114
 DOR, LS, CS, and LS+CS algorithms with uniform traffic pattern: 1024 nodes, 3 virtual channels, and q = 1	4.33	Comparison of dynamic communication performance of the HTN between	
 nodes, 3 virtual channels, and q = 1		DOR. LS. CS. and LS+CS algorithms with uniform traffic pattern: 1024	
 4.34 Comparison of dynamic communication performance of the HTN between DOR, LS, CS, and LS+CS algorithms with 5% hot-spot traffic pattern: 1024 nodes, 3 virtual channels, short message, and q = 1		nodes, 3 virtual channels, and $q = 1$.	. 119
 DOR, LS, CS, and LS+CS algorithms with 5% hot-spot traffic pattern: 1024 nodes, 3 virtual channels, short message, and q = 1	4.34	Comparison of dynamic communication performance of the HTN between	
 1024 nodes, 3 virtual channels, short message, and q = 1		DOR. LS. CS. and LS+CS algorithms with 5% hot-spot traffic pattern:	
 4.35 Comparison of dynamic communication performance of the HTN between DOR, LS, CS, and LS+CS algorithms with bit-reversal traffic pattern: 1024 nodes, 3 virtual channels, 16 flits, and q = 1		1024 nodes, 3 virtual channels, short message, and $q = 1, \ldots, \ldots$. 120
 DOR, LS, CS, and LS+CS algorithms with bit-reversal traffic pattern: 1024 nodes, 3 virtual channels, 16 flits, and q = 1	4.35	Comparison of dynamic communication performance of the HTN between	
 nodes, 3 virtual channels, 16 flits, and q = 1		DOR, LS, CS, and LS+CS algorithms with bit-reversal traffic pattern: 1024	
 4.36 Comparison of dynamic communication performance of the HTN between DOR, LS, CS, and LS+CS algorithms with bit-flip traffic pattern: 1024 nodes, 3 virtual channels, short message, and q = 1		nodes. 3 virtual channels. 16 flits, and $q = 1, \dots, n$. 120
 DOR, LS, CS, and LS+CS algorithms with bit-flip traffic pattern: 1024 nodes, 3 virtual channels, short message, and q = 1	4.36	Comparison of dynamic communication performance of the HTN between	_
 nodes, 3 virtual channels, short message, and q = 1		DOR, LS, CS, and LS+CS algorithms with bit-flip traffic pattern: 1024	
 4.37 Comparison of dynamic communication performance of the HTN between DOR, LS, CS, and LS+CS algorithms with perfect shuffle traffic pattern: 1024 nodes, 3 virtual channels, short message, and q = 1		nodes, 3 virtual channels, short message, and $q = 1, \ldots, \ldots, \ldots$. 121
 DOR, LS, CS, and LS+CS algorithms with perfect shuffle traffic pattern: 1024 nodes, 3 virtual channels, short message, and q = 1	4.37	Comparison of dynamic communication performance of the HTN between	
 1024 nodes, 3 virtual channels, short message, and q = 1		DOR. LS. CS. and LS+CS algorithms with perfect shuffle traffic pattern:	
 4.38 Dynamic communication performance improvement by LS+CS algorithm over DOR algorithm (a) Maximum throughput enhancement and (b) Message latency reduction		1024 nodes, 3 virtual channels, short message, and $q = 1, \ldots, \ldots$. 121
 over DOR algorithm (a) Maximum throughput enhancement and (b) Message latency reduction. 123 5.1 Hierarchical redundancy of the HTN 5.2 Different switch states for reconfiguration: (a) no connect, (b) north-tosouth and east-to-west, (c) north-to-west and south-to-east, and (d) north-to-east and south-to-west connects. 5.3 Reconfiguration of a plane for the BM in the presence of 4 faulty PEs: Diagonal 5.4 Reconfiguration of a plane for the BM in the presence of 4 faulty PEs: Square 128 5.5 Reconfiguration of a plane for the BM in the presence of 4 faulty PEs: Concatenated L-shape and inverse L-shape 5.6 Yield for BM and Level-2 network vs. fault density without spare node 133 5.8 CONVERGE on a 4 × 4 2D-mesh 	4.38	Dynamic communication performance improvement by LS+CS algorithm	
 sage latency reduction		over DOR algorithm (a) Maximum throughput enhancement and (b) Mes-	
 5.1 Hierarchical redundancy of the HTN		sage latency reduction.	. 123
 5.2 Different switch states for reconfiguration: (a) no connect, (b) north-to-south and east-to-west, (c) north-to-west and south-to-east, and (d) north-to-east and south-to-west connects. 5.3 Reconfiguration of a plane for the BM in the presence of 4 faulty PEs: Diagonal	5.1	Hierarchical redundancy of the HTN	. 127
 south and east-to-west, (c) north-to-west and south-to-east, and (d) north-to-east and south-to-west connects. 5.3 Reconfiguration of a plane for the BM in the presence of 4 faulty PEs: Diagonal . 5.4 Reconfiguration of a plane for the BM in the presence of 4 faulty PEs: Square128 5.5 Reconfiguration of a plane for the BM in the presence of 4 faulty PEs: Concatenated L-shape and inverse L-shape . 5.6 Yield for BM and Level-2 network vs. fault density without spare node . 130 5.7 Yield for BM and Level-2 network vs. fault density with spare node . 131 5.8 CONVERGE on a 4 × 4 2D-mesh . 	5.2	Different switch states for reconfiguration: (a) no connect, (b) north-to-	
 to-east and south-to-west connects		south and east-to-west, (c) north-to-west and south-to-east, and (d) north-	
 5.3 Reconfiguration of a plane for the BM in the presence of 4 faulty PEs: Diagonal		to-east and south-to-west connects.	. 127
 Diagonal	5.3	Reconfiguration of a plane for the BM in the presence of 4 faulty PEs:	
 5.4 Reconfiguration of a plane for the BM in the presence of 4 faulty PEs: Square128 5.5 Reconfiguration of a plane for the BM in the presence of 4 faulty PEs: Concatenated L-shape and inverse L-shape		Diagonal	. 128
 5.5 Reconfiguration of a plane for the BM in the presence of 4 faulty PEs: Concatenated L-shape and inverse L-shape	5.4	Reconfiguration of a plane for the BM in the presence of 4 faulty PEs: Squar	e128
Concatenated L-shape and inverse L-shape	5.5	Reconfiguration of a plane for the BM in the presence of 4 faulty PEs:	
 5.6 Yield for BM and Level-2 network vs. fault density without spare node 130 5.7 Yield for BM and Level-2 network vs. fault density with spare node 131 5.8 CONVERGE on a 4 × 4 2D-mesh		Concatenated L-shape and inverse L-shape	. 129
5.7 Yield for BM and Level-2 network vs. fault density with spare node \ldots 131 5.8 CONVERGE on a 4 × 4 2D-mesh \ldots 133	5.6	Yield for BM and Level-2 network vs. fault density without spare node	. 130
5.8 CONVERGE on a 4×4 2D-mesh	5.7	Yield for BM and Level-2 network vs. fault density with spare node	. 131
	5.8	CONVERGE on a 4×4 2D-mesh $\ldots \ldots \ldots$. 133

5.9	The total number of communication steps of the bitonic merge in different	
	networks	139
5.10	The total number of communication steps of the bitonic merge in different	
	networks	139
5.11	The total number of communication steps of the FFT in different networks	140
5.12	The total number of communication steps for finding the maximum in	
	different networks	140
6.1	A $(4 \times 4 \times 4)$ 3D-torus network (a) unpruned, (b) pruning along the z	
	direction, T_1 , (c) pruning along the $x + y + z$ direction, T_2 , and (d) pruning	
	along the $x + y$ direction, disjoint network	144
6.2	A (4×4) pruned torus obtained by pruning along the $x + y$ direction	145
6.3	Pruned Hierarchical Torus Network $(m = 4, n = 4)$	146
6.4	An illustration of Level-2 HTN_3	146
6.5	A comparison of peak number of vertical links of various HTN	148
6.6	Normalized layout area (1024 PEs, 16 Wafers, and 64 PEs/Wafer)	148
7.1	Basic module of the MH3DT network	151
7.2	Interconnection of a Level-2 MH3DT network	152
7.3	Routing algorithm of the MH3DT network	154
7.4	Dynamic communication performance of dimension-order routing with uni-	
	form traffic pattern on various networks: 4096 nodes, 2 VCs, 16 flits	160
7.5	Average transfer time divided by message length versus network through-	
	put of MH3DT network: 4096 nodes, 2 VCs, 16 flits, Buffer Size 2 flits	161
7.6	Dynamic communication performance of dimension order routing with uni-	
	form traffic pattern on the MH3DT network: 4096 nodes, various virtual	
	channels,, 16 flits, Buffer Size 2 flits.	162
7.7	Basic module of the TTN	164
7.8	Interconnection of a Level-2 TTN	165
7.9	Routing algorithm of the TTN	166
7.10	Dynamic communication performance of dimension-order routing with uni-	
	form traffic pattern on various networks: 4096 nodes, 4 VCs, 16 flits, and	
	$q = 0. \dots \dots \dots \dots \dots \dots \dots \dots \dots $	171
7.11	Dynamic communication performance of dimension-order routing with uni-	
	form traffic pattern on various networks: 4096 nodes, 4 VCs, 16 flits, and	
	$q=1. \ldots \ldots \ldots \ldots \ldots \ldots \ldots \ldots \ldots $	171

List of Tables

2.1	A collection of types of interconnection networks used in commercial and
	experimental parallel computers
3.1	Diameter of HTN with Level- L
3.2	Comparison of degree and connectivity for various networks
3.3	Parameters for layout area in 3D stacked implementation
3.4	Comparison of maximum wire length of different networks
4.1	The total number of links of various networks with 1024 node
4.2	Maximum throughput of the HTN (<i>Flits/Cycle/Node</i>)
4.3	Gate counts for router modules
4.4	Gate counts for HTN routers
4.5	Delays for the router module
4.6	Module delay constants for a 0.8 micron CMOS process
4.7	Module delay for a 0.8 micron CMOS process
4.8	Performance Improvement using selection algorithm over dimension-order
	routing \ldots
5.1	The total number of communication steps on a network for bitonic merge,
	FFT, and finding the maximum
6.1	Comparison of wiring complexity of various Level-2 HTN
7.1	Comparison of static network performance of various network with 4096
	node
7.2	Comparison of static network performance of various network with 4096
	node