

Free Accepted Article From Repository

Look Up Full Text

Full Text from Publisher

Find PDF

A Export...

Add to Marked List

1 of 1

## Optical fiber coated Zinc Oxide (ZnO) nanorods decorated with Palladium (Pd) for hydrogen sensing

By: Idris, NF (Idris, Nur Farahi)<sup>[1]</sup>; Yahya, NAM (Yahya, Nor Akmar Mohd)<sup>[2]</sup>; Yaacob, MH (Yaacob, Mohd Hanif)<sup>[2]</sup>; Idris, AH (Idris, Auni Hamimi)<sup>[3]</sup>; Harun, SW (Harun, Sulaiman Wadi)<sup>[4]</sup>; Saidin, N (Saidin, Norazlina)<sup>[1]</sup>

[View Web of Science ResearcherID and ORCID](#)

### OPTICAL MATERIALS

Volume: 96

Article Number: UNSP 109291

DOI: 10.1016/j.optmat.2019.109291

Published: OCT 2019

Document Type: Article

[View Journal Impact](#)

### Abstract

A novel hydrogen (H-2) sensor was developed using acid-etched optical fiber coated with zinc oxide (ZnO) nanorods. The sensing performance was done by comparing the acid-etched fiber coated with ZnO nanorods with and without decorated Palladium (Pd). The conventional optical single-mode fiber (SMF) with a diameter of 125  $\mu\text{m}$  has been modified as a transducing platform by etching it to 11  $\mu\text{m}$  diameter using hydrofluoric acid (HF) to enhance the evanescent field of the light propagates in the fiber core. The etched fiber was coated with ZnO nanorods via hydrothermal process by using seeding and growth solution method. The sensing layer was characterized through Scanning Electron Microscopy (SEM), Energy Dispersive X-Ray (EDX) and X-Ray Diffraction (XRD) to verify the properties of ZnO. Catalyst Palladium (Pd) was sputtered onto the ZnO nanorods to improve H-2 detection. The developed sensor operating temperature was found to be 150 degrees C that produces 6.36 dBm increase in response towards the 1% concentration of H-2 in synthetic air. It was then tested with different concentration of H-2. The sensor decorated with Pd has better performance in sensing compared to non-decorated Pd based on the output power versus time. The sensor best response and recovery times is 6 and 5 min respectively, for acid-etched optical fiber coated with ZnO nanorods decorated with Pd for 0.75% of H-2 concentrations at 150 degrees C. The results indicate the optical fiber sensor might improve the performance towards H-2 as oppose to the conventional electrical sensor.

### Keywords

**Author Keywords:** Hydrogen sensor; Etching optical fiber; Fiber optic sensor; Light-intensity response; Zinc oxide nanorods; Hydrothermal method

**KeyWords Plus:** GAS SENSORS; NANOSTRUCTURES; FABRICATION; GROWTH

### Author Information

**Reprint Address:** Saidin, N (reprint author)

+ Int Islamic Univ Malaysia, Dept Elect & Comp Engn, Kuala Lumpur 53100, Malaysia.

#### Addresses:

+ [ 1 ] Int Islamic Univ Malaysia, Dept Elect & Comp Engn, Kuala Lumpur 53100, Malaysia

+ [ 2 ] Univ Putra Malaysia, Photon Syst Engn Lab, Seri Kembangan 43300, Selangor, Malaysia

+ [ 3 ] Univ Malaysia Pahan, Fac Chem Engn & Nat Resources, Kuantan 26300, Pahang, Malaysia

+ [ 4 ] Univ Malaya, Dept Elect Engn, Kuala Lumpur 50603, Malaysia

**E-mail Addresses:** [norazlina@iium.edu.my](mailto:norazlina@iium.edu.my)

### Funding

Funding Agency	Grant Number
Ministry of Higher Education (MOHE), Malaysia, Fundamental Research Grant Scheme (FRGS)	FRGS19-052-0660

[View funding text](#)

### Publisher

### Citation Network

In Web of Science Core Collection

0

Times Cited

[Create Citation Alert](#)

32

Cited References

[View Related Records](#)

### Use in Web of Science

Web of Science Usage Count

3

Last 180 Days

3

Since 2013

[Learn more](#)

This record is from:

Web of Science Core Collection

- Science Citation Index Expanded

[Suggest a correction](#)

If you would like to improve the quality of the data in this record, please [suggest a correction](#).

ELSEVIER, RADARWEG 29, 1043 NX AMSTERDAM, NETHERLANDS

**Journal Information**

Impact Factor: Journal Citation Reports

**Categories / Classification**

Research Areas: Materials Science; Optics

Web of Science Categories: Materials Science, Multidisciplinary; Optics

**Document Information**

Language: English

Accession Number: WOS:000496866100043

ISSN: 0925-3467

eISSN: 1873-1252

**Other Information**

IDS Number: JN4JS

Cited References in Web of Science Core Collection: 32

Times Cited in Web of Science Core Collection: 0

[See fewer data fields](#)

◀ 1 of 1 ▶

**Cited References: 32**Showing 30 of 32 [View All in Cited References page](#)*(from Web of Science Core Collection)*

- |    |  |                         |
|----|--|-------------------------|
| 1. | Title: [not available]<br>By: Arasu, P.T.; Khalaf, A.L.; Aziz, S.H.A.; et al.<br>Optical Fiber Based Ammonia Gas Sensor with Carbon Nanotubes Sensing Enhancement Pages: 5-8 Published: 2017<br><a href="#">[Show additional data]</a>   | <b>Times Cited: 1</b>   |
| 2. | <a href="#">Tapered plastic optical fiber coated with ZnO nanostructures for the measurement of uric acid concentrations and changes in relative humidity</a><br>By: Batumalay, M.; Harith, Z.; Rifaie, H. A.; et al.<br>SENSORS AND ACTUATORS A-PHYSICAL Volume: 210 Pages: 190-196 Published: APR 1 2014                                       | <b>Times Cited: 38</b>  |
| 3. | <a href="#">Sensitivity, selectivity, and stability of gas-sensitive metal-oxide nanostructures</a><br>By: Bochenkov, V. E.; Surgeev, G. B.<br>Metal Oxide Nanostructures and Their Applications Volume: 3 Pages: 31-52  | <b>Times Cited: 1</b>   |
| 4. | <a href="#">Optical fiber-based evanescent ammonia sensor</a><br>By: Cao, WQ; Duan, YX<br>SENSORS AND ACTUATORS B-CHEMICAL Volume: 110 Issue: 2 Pages: 252-259 Published: OCT 14 2005  | <b>Times Cited: 122</b> |
| 5. | <a href="#">Optical hydrogen sensor based on etched fiber Bragg grating sputtered with Pd/Ag composite film</a><br>By: Dai, Jixiang; Yang, Minghong; Yu, Xun; et al.<br>OPTICAL FIBER TECHNOLOGY Volume: 19 Issue: 1 Pages: 26-30 Published: JAN 2013  | <b>Times Cited: 65</b>  |
| 6. | <a href="#">Optical and structural properties of well-aligned ZnO nanoneedle arrays grown on porous silicon substrates by electric field-assisted aqueous solution method</a><br>By: Dalvand, Ramazanali; Mahmud, Shahrom; Alimanesh, Mahmoud; et al.<br>CERAMICS INTERNATIONAL Volume: 43 Issue: 1 Pages: 1488-1494 Part: B Published: JAN 2017 | <b>Times Cited: 5</b>   |
| 7. | <a href="#">Semiconductor metal oxide gas sensors: A review</a><br>By: Dey, Ananya<br>MATERIALS SCIENCE AND ENGINEERING B-ADVANCED FUNCTIONAL SOLID-STATE MATERIALS Volume: 229 Pages: 206-217 Published: MAR 2018   | <b>Times Cited: 208</b> |
| 8. | <a href="#">Deletion of TXNIP Mitigates High-Fat Diet-Impaired Angiogenesis and Prevents Inflammation in a Mouse Model of Critical Limb</a>  | <b>Times Cited: 7</b>   |