

# Document details

#### 1 of 1

到 Export ▲ Download More... >

International Journal of Energy Research Volume 44, Issue 2, 1 February 2020, Pages 1000-1011

## Experimental study on performance of square tube absorber with phase change material (Article)

Sharol, A.F., Abdul Razak, A., Abdul Majid, Z.A., Fudholi, A.

View additional authors >

国 Save all to author list

<sup>a</sup>College of Engineering Technology, Faculty of Mechanical Engineering Technology, Universiti Malaysia Pahang, Pekan, Pahang, Malaysia

<sup>b</sup>Kuliyyah of Allied Health Sciences, International Islamic University of Malaysia, Kuantan, Pahang, Malaysia <sup>c</sup>Solar Research Energy Institute, Universiti Kebangsaan Malaysia, Bangi, Selangor, Malaysia

View additional affiliations  $\checkmark$ 

#### Abstract

The intermittent nature of solar radiation has decreased the performance efficiency of solar heaters. Integrating the solar heater with thermal energy storage component could increase its performance effectively. In this article, an investigation on the effect of phase change material (PCM) as the thermal energy storage component on the performance of square aluminum tube was carried out experimentally. In the first phase, the temperature behavior of square aluminum tube with two types of PCM, namely, generic plant-based PCM (A2) and paraffin wax (A3), was compared with square aluminum tube without PCM (A1). In the second phase, the performance of square aluminum tube was investigated with different paraffin wax masses of 38 g (B1), 48 g (B2), and 58 g (B3). Based on the result, the A3 tube configuration performed better than A1 and A2 tube configurations with higher heat gain rate (0.08°C/s) and lower heat discharge rate (-0.04°C/s). The B2 tube configuration was found to have maximum heat gain of 3.73 kJ with higher heat discharge rate as compared with other square tube configurations. The average temperature difference between internal and external surface tube of B2 was lower (4.3°C) leading to higher average temperature difference at ambient temperature of 25.3°C. Instantaneous efficiency of the tube B2 is higher than the B1 and B3 tube configurations by 16% and 26%, respectively. The result suggests that the insertion of paraffin wax inside the square absorber tube improves the temperature response of the absorber in the situation of intermittent solar radiation. © 2019 John Wiley & Sons, Ltd.

#### SciVal Topic Prominence (i)

Topic: Solar dryers | Drying | Air collector

Prominence percentile: 97.794 **①** 

#### Author keywords

(phase change material (PCM)) cross-matrix absorber (CMA) (solar energy) thermal energy storage

#### Indexed keywords

Engineering controlled terms:

Aluminum (Heat storage) (Paraffins) (Phase change materials) (Solar energy Solar heating (Storage (materials)) (Thermal energy Solar radiation )

#### Cited by 0 documents

Inform me when this document is cited in Scopus:

Set citation alert >

Set citation feed >

#### Related documents

Find more related documents in Scopus based on:

Authors > Keywords >

Engineering (cross-matrix absorber (CMA)) (External surfaces) (Heat discharge rates) uncontrolled terms Instantaneous efficiencies Performance efficiency Temperature behavior Temperature differences Temperature response Engineering main Tubes (components)

heading:

### Funding details

Funding sponsor	Funding number	Acronym
Universiti Kebangsaan Malaysia	MRUN-RAKAN RU-2019-001/3	
Universiti Malaysia Pahang	RDU1703137	

1

The authors wish to express their grateful acknowledgement to Universiti Malaysia Pahang for the financial support under project grant RDU1703137 and Universiti Kebangsaan Malaysia under project grant MRUN-RAKAN RU-2019-001/3.

ISSN: 0363907X **CODEN: IJERD** Source Type: Journal Original language: English DOI: 10.1002/er.4971 Document Type: Article

Publisher: John Wiley and Sons Ltd

- 🙎 Abdul Razak, A.; College of Engineering Technology, Faculty of Mechanical Engineering Technology, Universiti Malaysia Pahang, Pekan, Pahang, Malaysia;
- © Copyright 2020 Elsevier B.V., All rights reserved.

**Customer Service About Scopus** Language

日本語に切り替える What is Scopus Help 切换到简体中文 Content coverage Contact us

切換到繁體中文 Scopus blog Русский язык Scopus API

Privacy matters

**ELSEVIER** Terms and conditions *¬* Privacy policy >

Copyright © Elsevier B.V 7. All rights reserved. Scopus® is a registered trademark of Elsevier B.V.

We use cookies to help provide and enhance our service and tailor content. By continuing, you agree to the use of cookies.

