



Document details

[Back to results](#) | 1 of 1

[Export](#) [Download](#) [Print](#) [E-mail](#) [Save to PDF](#) [Add to List](#) [More... >](#)

[Full Text](#) [View at Publisher](#)

Biomedizinische Technik

Volume 65, Issue 4, 1 August 2020, Pages 461-468

Electrical stimulator with mechanomyography-based real-time monitoring, muscle fatigue detection, and safety shut-off: A pilot study (Article)

Naeem, J.^a, Hamzaid, N.A.^a , Azman, A.W.^b, Bijak, M.^{a,c}

^aDepartment of Biomedical Engineering, Faculty of Engineering, University of Malaya, Kuala Lumpur, 50603, Malaysia

^bDepartment of Electrical and Computer Engineering, Faculty of Engineering, International Islamic University Malaysia, Kuala Lumpur, 53100, Malaysia

^cMedical University Vienna, Center for Medical Physics and Biomedical Engineering, Vienna, Austria

Abstract

[View references \(44\)](#)

Functional electrical stimulation (FES) has been used to produce force-related activities on the paralyzed muscle among spinal cord injury (SCI) individuals. Early muscle fatigue is an issue in all FES applications. If not properly monitored, overstimulation can occur, which can lead to muscle damage. A real-time mechanomyography (MMG)-based FES system was implemented on the quadriceps muscles of three individuals with SCI to generate an isometric force on both legs. Three threshold drop levels of MMG-root mean square (MMG-RMS) feature (thr50, thr60, and thr70; representing 50%, 60%, and 70% drop from initial MMG-RMS values, respectively) were used to terminate the stimulation session. The mean stimulation time increased when the MMG-RMS drop threshold increased (thr50: 22.7 s, thr60: 25.7 s, and thr70: 27.3 s), indicating longer sessions when lower performance drop was allowed. Moreover, at thr70, the torque dropped below 50% from the initial value in 14 trials, more than at thr50 and thr60. This is a clear indication of muscle fatigue detection using the MMG-RMS value. The stimulation time at thr70 was significantly longer ($p = 0.013$) than that at thr50. The results demonstrated that a real-time MMG-based FES monitoring system has the potential to prevent the onset of critical muscle fatigue in individuals with SCI in prolonged FES sessions. © 2020 Walter de Gruyter GmbH, Berlin/Boston 2020.

SciVal Topic Prominence

Topic: Muscle Fatigue | Electromyography | Muscle Isometric Contraction

Prominence percentile: 83.203

Author keywords

[FES](#) [KE](#) [MMG](#) [RMS](#) [SCI](#)

Indexed keywords

Engineering controlled terms:

[Drops](#) [Functional electric stimulation](#)

[Metrics](#) [View all metrics >](#)

Cited by 0 documents

Inform me when this document is cited in Scopus:

[Set citation alert >](#)

Related documents

Electrically evoked wrist extensor muscle fatigue throughout repetitive motion as measured by mechanomyography and near-infrared spectroscopy

Mohamad Saadon, N.S. , Hamzaid, N.A. , Hasnan, N. (2019) *Biomedizinische Technik*

Mechanomyography and torque during FES-evoked muscle contractions to fatigue in individuals with spinal cord injury

Mohamad, N.Z. , Hamzaid, N.A. , Davis, G.M. (2017) *Sensors (Switzerland)*

Development and evaluation of a two-dimensional electrocutaneous cognitive feedback system for use in paraplegic standing

Matjačić, Z. , Jensen, P.L. , Riso, R.R. (2000) *Journal of Medical Engineering and Technology*

[View all related documents based on references](#)

Find more related documents in Scopus based on:

[Authors >](#) [Keywords >](#)

Engineering
uncontrolled terms

Electrical stimulators | Functional electrical stimulation | Mechanomyography
Monitoring system | Paralyzed muscles | Real time monitoring | Root Mean Square
Spinal cord injuries (SCI)

Engineering main
heading:

Muscle

EMTREE medical
terms:

adult | Article | clinical article | diagnostic value | functional electrical stimulation | human
leg | mechanomyography | middle aged | muscle fatigue | muscle isometric contraction
muscle strength | myography | pilot study | priority journal | quadriceps femoris muscle
reaction time | spinal cord injury | torque | validation study

Device tradename:

ADXL335, Biodex dynamometer System 4, Biodex, United States, RehaTrode

Manufacturers:

Device manufacturer:

Biodex, United States;

National Instruments, United States

Funding details

Funding sponsor	Funding number	Acronym
Universiti Malaya	GPF0688A-2018	

Funding text

Research funding : The research was funded by the University of Malaya faculty Research Grant (GPF0688A-2018).

ISSN: 00135585
CODEN: BMZTA
Source Type: Journal
Original language: English

DOI: 10.1515/bmt-2019-0191
PubMed ID: 32304295
Document Type: Article
Publisher: De Gruyter

References (44)

[View in search results format >](#)

All Export Print E-mail Save to PDF [Create bibliography](#)

1 Krajl, A., Bajd, T., Turk, R., Benko, H.

Posture switching for prolonging functional electrical stimulation standing in paraplegic patients ([Open Access](#))

(1986) *Paraplegia*, 24 (4), pp. 221-230. Cited 51 times.
doi: 10.1038/sc.1986.31

[View at Publisher](#)
