

PREPARATION AND CHARACTERIZATION OF LATEX FILLER NANOCOMPOSITES

By: Omar, MF (Omar, Mohamad Firdaus)^[1,2]; Mohamad, N (Mohamad, Nuriah)^[2]; Ali, FB (Ali, Fathilah Binti)^[1]

IUM ENGINEERING JOURNAL

Volume: 21 Issue: 2 Pages: 230-238

Published: JUL 2020

Document Type: Article

Abstract

Latex compounding which incorporates various types of >clays as filler the rubber can significantly give reinforcement in the rubber matrix when rubber/clay nanocomposites are formed, but the filler agglomerates. Thus, study was conducted by using Kaolin clay as the filler in the rubber nanocomposites with silane coupling agent to functionalize the surface of the filler. This study was done in order to investigate the mechanical properties of various functionalized Kaolin in latex nanocomposites, to prepare various ratios of Kaolin to rubber, and to characterize mechanical, thermal and morphological properties of the Kaolin in latex nanocomposites. To achieve these, six types of silane coupling agents was used for Kaolin filler surface functionalization purpose during the filler's incorporation in latex compounding. The optimized coupling agent, USi 7301 (7-chloropropyltrimetoxysilane) - with tensile strength value of 32.77 MPa, elongation at break value of 632.589 % and force at break value of 6.737 N was used to further functionalize Kaolin filler in different ratios so as to achieve the optimum mechanical, thermal and morphological properties of the filler in the polymer matrix. Universal tensile machine was used to analyze the mechanical properties of the nanocomposites, while the Scanning Electron Microscopy (SEM) and Differential Scanning Calorimetry (DSC) were used to observe the morphological and thermal properties of the nanocomposites, respectively. The results showed that reducing the Total Solids Content (TSC) of Kaolin filler to 26 % somehow showed the optimized properties of the nanocomposites, giving 34.00 MPa tensile strength, 576.494 % elongation at break and 6.564 N force at break. Rough surface morphology was observed under SEM suggesting the occurrence of phase separation between the hydrophilic filler and the hydrophobic rubber matrix. In the DSC plot, sample with USi-7301 and with functionalized Kaolin filler 26 % TSC showed glass transition temperature shifted to lower region compared to normal nitrile rubber. The reinforcement of nanocomposites formed will not only enhance the properties of the nanocomposites, but is also economically feasible thus brings advantages to the industry.

Keywords

Author Keywords: [rubber](#); [latex](#); [filler](#); [nanocomposites](#); [silane coupling agent](#)

Author Information

Reprint Address:

International Islamic University Malaysia Int Islamic Univ Malaysia, Fac Engn, Dept Biotechnol Engn, Jalan Gombak, Kuala Lumpur 53100, Malaysia.

Corresponding Address: Ali, FB (corresponding author)

+ Int Islamic Univ Malaysia, Fac Engn, Dept Biotechnol Engn, Jalan Gombak, Kuala Lumpur 53100, Malaysia.

Addresses:

+ [1] Int Islamic Univ Malaysia, Fac Engn, Dept Biotechnol Engn, Jalan Gombak, Kuala Lumpur 53100, Malaysia

[2] Top Glove Sdn Bhd, R&D Ctr, Lot 64593, Jalan Dahlia KU-8, Klang 41050, Selangor, Malaysia

E-mail Addresses: fathilah@ium.edu.my

Funding

Funding Agency	Grant Number
HUM Faculty of Engineering	
Top Glove Sdn. Bhd. and its RD department	

[View funding text](#)

Publisher

KULLIYAH ENGINEERING, INT ISLAMIC UNIV MALAYSIA, JALAN GOMBAK, 53100, MALAYSIA

Citation Network

In Web of Science Core Collection

0

Times Cited

[Create Citation Alert](#)

13

Cited References

[View Related Records](#)

Use in Web of Science

Web of Science Usage Count

0

Last 180 Days

0

Since 2013

[Learn more](#)

This record is from:

Web of Science Core Collection

- Emerging Sources Citation Index

[Suggest a correction](#)

If you would like to improve the quality of the data in this record, please suggest a correction.

Categories / Classification

Research Areas: Engineering

Web of Science Categories: Engineering, Multidisciplinary

[See more data fields](#)

◀ 19 of 196 ▶

Cited References: 13

Showing 13 of 13 [View All in Cited References page](#)

(from Web of Science Core Collection)

1. [Studies on the effect of titanate coupling agent \(2.0%\) on the mechanical properties of flyash-filled polybutadiene rubber](#) Times Cited: 18
By: Alkadasi, NAN; Sarwade, BD; Hundiwale, DG; et al.
JOURNAL OF APPLIED POLYMER SCIENCE Volume: 93 Issue: 3 Pages: 1293-1298 Published: AUG 5 2004
2. [Design and Preparation of Cross-Linked Polystyrene Nanoparticles for Elastomer Reinforcement](#) Times Cited: 17
By: Lu, Ming; Zhou, Jianjun; Wang, Liansheng; et al.
JOURNAL OF NANOMATERIALS Volume: 2010 Article Number: 352914 Published: 2010
3. [Carboxylated acrylo nitrile butadiene rubber latex/kaolin nanocomposites: preparation and properties](#) Times Cited: 5
By: Nair, K. Preetha; Nair, Ajalesh B.; Joseph, Rani
COMPOSITE INTERFACES Volume: 21 Issue: 6 Pages: 571-583 Published: 2014
4. Title: [not available] Times Cited: 10
By: NASSAR A
NANOSCIENCE NANOENGI Volume: 1 Pages: 89 Published: 2013
5. [Quality of water treated by coagulation using Moringa oleifera seeds](#) Times Cited: 281
By: Ndabigengesere, A; Narasiah, KS
WATER RESEARCH Volume: 32 Issue: 3 Pages: 781-791 Published: MAR 1998
6. [Synthesis of Natural Rubber/Palygorskite Nanocomposites via Silylation and Cation Exchange](#) Times Cited: 1
By: Nor, N. A. Mohd; Muttalib, S. N. A.; Othman, N.
NANOCLAY REINFORCED POLYMER COMPOSITES: NANOCOMPOSITES AND BIONANOCOMPOSITES Book Series: Engineering Materials Pages: 261-289 Published: 2016
7. [Synthesis and structure of smectic clay/poly\(methyl methacrylate\) and clay/polystyrene nanocomposites via in situ intercalative polymerization](#) Times Cited: 310
By: Okamoto, M; Morita, S; Taguchi, H; et al.
POLYMER Volume: 41 Issue: 10 Pages: 3887-3890 Published: MAY 2000
8. [Preparation of polystyrene-clay nanocomposite by solution intercalation technique](#) Times Cited: 27
By: Paul, P. K.; Hussain, S. A.; Bhattacharjee, D.; et al.
BULLETIN OF MATERIALS SCIENCE Volume: 36 Issue: 3 Pages: 361-366 Published: JUN 2013
9. [General Purpose Elastomers: Structure, Chemistry, Physics and Performance](#) Times Cited: 25
By: Robert, A. S.; Ing, K.
Advances in Elastomers I Pages: 11-45 Published: 2013
Publisher: Springer, Berlin Heidelberg
[\[Show additional data\]](#)
10. [Do the rubber plantations in tropical China act as large carbon sinks?](#) Times Cited: 21
By: Song, Qing-Hai; Tan, Zheng-Hong; Zhang, Yi-Ping; et al.
IFOREST-BIOGEOSCIENCES AND FORESTRY Volume: 7 Pages: 42-47 Published: OCT 21 2013
11. Title: [not available] Times Cited: 1
By: Takatoh, K.; Sakamoto, M.; Hasegawa, R.; et al.
Alignment Technology and Applications of Liquid Crystal Devices Pages: 90-95 Published: 2005
Publisher: CRC Press, Boca Raton
[\[Show additional data\]](#)
12. [Rubber/clay nanocomposites by combined latex compounding and melt mixing: A masterbatch process](#) Times Cited: 36
By: Tan, Jinghua; Wang, Xiaoping; Luo, Yuanfang; et al.