



# Document details

< Back to results | 1 of 1

📄 Export 📄 Download 🖨️ Print ✉️ E-mail 📄 Save to PDF ☆ Add to List More... >

Test Engineering and Management  
Volume 81, 27 December 2019, Pages 5702-5708

## The load reliant power transfer of the series-to-series inductive resonant wireless power transfer (Article)

Adam, I.<sup>a,b</sup> ✉️, Khan, S.<sup>a</sup> ✉️, Zaharudin, Z.<sup>a,b</sup> ✉️, Abdul Kadir, K.<sup>b</sup> ✉️, Nurdin, A.N.<sup>a</sup> ✉️, Yaacob, M.<sup>a</sup> ✉️, Khalil, A.<sup>c</sup> ✉️

<sup>a</sup>Kulliyah of Engineering, International Islamic University, P.O. Box 10, Kuala Lumpur, 50728, Malaysia  
<sup>b</sup>University of Kuala Lumpur, Batu 8, Jalan Sungai Pusu, Gombak, Selangor, 531000, Malaysia  
<sup>c</sup>Electrical and Electronic Engineering, Universiti Teknologi Brunei, Jalan Tungku Link Gadong, BE1410, Brunei Darussalam

### Abstract

✓ View references (16)

In this paper, the effect of the output impedance to the power transfer efficiency of the series-to-series inductive resonant wireless power transfer at the resonance frequency is reviewed in details. The analysis is carried out by utilizing the theoretical inductive resonance wireless power transfer model using the MATLAB® package. In this paper, the experiment is designed to confirm the highest power transfer efficiency is obtained at the resonance frequency for the given value of the coupling coefficient. Besides that, the experiment is also conducted to find the optimum load impedance for all given value of coupling coefficient. The analysis shows that the maximum wireless power transfer efficiency for series-to-series inductive resonant wireless power transfer is at the maximum peak when operational at the resonance frequency. In addition, the power transfer efficiency is improved by working at the optimum load impedance. The experimental set up is presented and the analytical results are reported. © 2019 Mattingley Publishing. All rights reserved.

### SciVal Topic Prominence ⓘ

Topic: Inductive Power Transmission | Charging (Batteries) | Electric Vehicles

Prominence percentile: 99.701 ⓘ

### Author keywords

Efficiency Power Transfer Wireless Power Transfer

### Indexed keywords

Engineering controlled terms: Efficiency Energy transfer Natural frequencies

Engineering uncontrolled terms: Analytical results Coupling coefficient Experimental set up Output impedance Power transfer efficiency Power transfers Resonance frequencies Wireless power

Engineering main heading: Inductive power transmission

### Funding details

Metrics ⓘ View all metrics >



PlumX Metrics  
Usage, Captures, Mentions, Social Media and Citations beyond Scopus.

Cited by 0 documents

Inform me when this document is cited in Scopus:

Set citation alert >

Set citation feed >

### Related documents

Design of efficient optimized wireless power transfer system

Wu, Q. , Wang, L. , Ju, D. (2020) *Journal of Power Electronics*

Maximum Efficiency Tracking for Wireless Power Transfer Systems with Dynamic Coupling Coefficient Estimation

Dai, X. , Li, X. , Li, Y. (2018) *IEEE Transactions on Power Electronics*

Maximum-Efficiency Operation of a 3.7 kW Inductive Wireless Charging System by Using On-Off Keying Modulation

Zhong, W. , Li, H. , Cui, H. (2018) *2018 IEEE Energy Conversion Congress and Exposition, ECCE 2018*

View all related documents based on references

Find more related documents in Scopus based on:

Authors > Keywords >

RIGS 15-147-0147,RMC RIGS 16-067-0231

## Funding text

The technical support by colleagues and staff of the UniKL and IIUM are gratefully acknowledged. We also would like to thank the anonymous referees for valuable comments and suggestions. Financial assistance for this research by the IIUM Research Management Center (RMC) via RIGS Grant No RIGS 15-147-0147 and RMC RIGS 16-067-0231 are highly acknowledged.

ISSN: 01934120

CODEN: TENMA

Source Type: Trade Journal

Original language: English

Document Type: Article

Publisher: Mattingley Publishing

## References (16)

[View in search results format >](#) All  Export  Print  E-mail  Save to PDF  Create bibliography

- 1 Li, P., Bashirullah, R.  
A Wireless Power Interface for Rechargeable Battery Operated Medical Implants  
(2007) *IEEE Transactions on Circuits and Systems II: Express Briefs*, 54 (10), pp. 912-916. Cited 158 times.  
doi: 10.1109/TCSII.2007.901613  
[View at Publisher](#)

- 2 Kim, C.-G., Seo, D.-H., You, J.-S., Park, J.-H., Cho, B.H.  
Design of a contactless battery charger for cellular phone  
(2001) *IEEE Transactions on Industrial Electronics*, 48 (6), pp. 1238-1247. Cited 254 times.  
<http://ieeexplore.ieee.org.ezproxy.um.edu.my/xpl/tocresult.jsp?isnumber=5410131>  
doi: 10.1109/41.969404  
[View at Publisher](#)

- 3 Wang, C.-S., Stielau, O.H., Covic, G.A.  
Design considerations for a contactless electric vehicle battery charger  
(2005) *IEEE Transactions on Industrial Electronics*, 52 (5), pp. 1308-1314. Cited 1055 times.  
doi: 10.1109/TIE.2005.855672  
[View at Publisher](#)

- 4 Porto, R.W., Brusamarello, V.J., Müller, I., Cabrera Riaño, F.L., De Sousa, F.R.  
Wireless power transfer for contactless instrumentation and measurement  
(2017) *IEEE Instrumentation and Measurement Magazine*, 20 (4), art. no. 8006394, pp. 49-54. Cited 10 times.  
<https://ieeexplore-ieee-org.ezproxy.um.edu.my/xpl/mostRecentIssue.jsp?punumber=5289>  
doi: 10.1109/MIM.2017.8006394  
[View at Publisher](#)