

CFD analysis of compressible flows in a convergent-divergent nozzle

By: [Khan, SA](#) (Khan, Sher Afghan) ¹;
[Ibrahim, OM](#) (Ibrahim, Omar Mohamed) ¹;
[Aabid, A](#) (Aabid, Abdul) ^{1, 2}

[View Web of Science ResearcherID and ORCID](#)
 (provided by Clarivate)

MATERIALS TODAY-PROCEEDINGS

Volume: 46 **Page:** 2835-2842 **Special Issue:** SI **Part:** 7

[Full text at publisher](#)

[Export](#) ▾

[Add To Marked List](#)

< 1 of 12 >

Meeting: [2nd International Conference on Smart and Sustainable Developments in Materials, Manufacturing and Energy Engineering \(SME\)](#)

Location: Nitte, INDIA

Date: DEC 22-23, 2020

Sponsor: NMAM Inst Technol

Abstract

A Nozzle is a mechanical device that uses pressure energy and fluid enthalpy to increase the outflow velocity and control fluid flow direction. To obtain the nozzle duct's shock pattern, the flow inside the nozzle must be supersonic with a Mach number greater than one. Experimentally, the shock pattern is obtained for a nozzle with a Mach number 2 and nozzle pressure ratio (NPR) equivalent to 7 and below. For Mach $M = 2$, the needed NPR is equal to 7.82 for correct expansion.. When the NPR is greater than 7.82, flow from the nozzles is under-expanded. For NPR less than 7.72 the flow from the nozzle is over-expanded. In this paper, the computational fluid mechanics (CFD) technique was used to simulate the nozzle flow based on the experimental investigation. A two-dimensional transient compressible flow of air through a supersonic nozzle was simulated using ANSYS fluent software. A

Citation Network

In Web of Science Core Collection

1

Citation

[🔔 Create citation alert](#)

All Citations

1 In All Databases
 + [See more citations](#)

View Related Records

You may also like...

[Abbasalizadeh, M; Jafarmadar, S; Shirvani, H; The Effects of Pressure Difference in Nozzle's two Phase Flow on the Quality of Exhaust Mixture](#)

INTERNATIONAL JOURNAL OF ENGINEERING


[OHTA, J; FUJII, T; TAKENAKA, N; et al. PERFORMANCE AND FLOW CHARACTERISTICS OF NOZZLES FOR INITIALLY SUBCOOLED HOT WATER \(INFLUENCE OF TURBULENCE AND DECOMPRESSION RATE\)](#)

INTERNATIONAL JOURNAL OF MULTIPHASE FLOW

[Hasan, ABMT; Characteristics of overexpanded nozzle flows in imposed oscillating condition](#)

INTERNATIONAL JOURNAL OF HEAT AND FLU. ²⁷

FLOW



time-dependent flow using the density-based implicit solver was used to analyze the simulation results. The results illustrate that the CFD technique simulates the fluid flows and the formation of shock in a duct and gives useful information about fluid dynamics analysis. (C) 2021 Elsevier Ltd. All rights reserved. Selection and peer-review under responsibility of the scientific committee of the International Conference on Smart and Sustainable Developments in Materials, Manufacturing and Energy Engineering.

Keywords

Author Keywords: [CFD](#); [Compressible flow](#); [C-D nozzle](#); [ANSYS simulation](#); [Mach number](#)

Author Information

Corresponding Address : Aabid, Abdul (corresponding author)

▼ Prince Sultan Univ, Coll Engr, Dept Engr Management, POB 66833, Riyadh 11586, Saudi Arabia

Addresses:

▼ ¹ Int Islamic Univ Malaysia, Fac Engr, Dept Mech Engr, POB 10, Kuala Lumpur 50728, Malaysia

▼ ² Prince Sultan Univ, Coll Engr, Dept Engr Management, POB 66833, Riyadh 11586, Saudi Arabia

E-mail Addresses: abdul.aabid@live.iium.edu.my

Categories/Classification

Research Areas: Materials Science

Document Information

Language: English

Accession Number: WOS:000668903600020

ISSN: 2214-7853

Other Information

IDS Number: TC8QP

— [See fewer data fields](#)

Journal information

MATERIALS TODAY-PROCEEDINGS

ISSN: 2214-7853

Current Publisher: ELSEVIER, RADARWEG 29, 1043 NX AMSTERDAM, NETHERLANDS

Research Areas: Materials Science

Web of Science Categories: Materials Science, Multidisciplinary

Yamaguchi, T; Hizawa, T; Kobayashi, H; et al. [Development and verification of a supersonic nozzle with a rectangular cross section at a Mach number of 2.8 for a scramjet model combustor](#)

JOURNAL OF THERMAL SCIENCE AND TECHNOLOGY

Oskouie, AK; Wang, HC; Noll, KE; et al. [Calculated calibration curves for particle size determination based on time-of-flight \(TOF\)](#)

AEROSOL SCIENCE AND TECHNOLOGY

[See all](#)

Most Recently Cited by

Aabid, A; Khan, SA; Baig, M; [A Critical Review of Supersonic Flow Control for High-Speed Applications](#)

APPLIED SCIENCES-BASEL

Use in Web of Science

Web of Science Usage Count

0

Last 180 Days

0

Since 2013

[Learn more](#)

This record is from:

Web of Science Core Collection

Conference Proceedings Citation Index – Science (CPCI-S)

Suggest a correction








If you would like to improve the quality of the data in this record, please [Suggest a correction](#)








35 Cited References







Showing 30 of 35



[View as set of results](#)

(from Web of Science Core Collection)









© 2021 Clarivate
Training Portal
Product Support

Data Correction
Privacy Statement
Newsletter

Copyright Notice
Cookie Policy
Terms of Use

Follow Us
 