English

Products

Web of Science™

Search

Marked List

History

Alerts

Sign In ~

Register

Search > Results for Optimization of ... > Optimization of dry sliding wear behavior of aluminium-based hybrid MMC'...

Free Full Text from Publisher



Export ~

Add To Marked List

< 1 of 1 >

By: Aabid, A (Aabid, Abdul) $^{[1]}$; Murtuza, MA (Murtuza, Mohammed Ali) $^{[2]}$; Khan, SA (Khan, Sher Afghan) $^{[3]}$; Baig, M (Baig, Muneer) $^{[1]}$

View Web of Science ResearcherID and ORCID (provided by Clarivate)

JOURNAL OF MATERIALS RESEARCH AND TECHNOLOGY-JMR&T

Volume: 16 Page: 743-763

DOI: 10.1016/j.jmrt.2021.12.005

Published: JAN-FEB 2022
Indexed: 2022-01-05

Document Type: Article

Abstract

Due to its exceptional mechanical characteristics combined with lightweight and fuel-efficient materials, metal matrix composites (MMCs) have largely been developed for the automotive and aerospace industries. In this paper, an attempt was made to investigate the dry sliding wear behavior of aluminium-based hybrid MMC's through the experimental approach. The experiments were performed for three types of filler materials: Boron carbide (B4C), Molybdenum Di-sulphide (MoS2), and graphite (Gr) particulates of 50 mm were reinforced into aluminium-2219 matrix using stir casting technique. On the other hand, data computing is a trend in mechanical engineering and is increasing drastically in recent years. It has proved one of the most costefficient methods to identify the optimum results with a limited number of experiments. Hence, this research was carried, with an emphasis on optimization, utilizing the design of experiments (DOE) technique with specified parameters. For DOE, additional experiments were conducted based on full factorial design and then different analyses were performed such as ANOVA, regressions equation, and confirmation tests to examine the effect of parameters on the wear behavior of composites. Besides, the influence of wear parameters such as applied load (L), sliding speed (S), and sliding distance (S-D) on the wear loss were investigated. The current investigation realized that B4C particles in the matrix increases the wear resistance of MMC when compared to other selected materials of this study. (C) 2021 The Author(s). Published by Elsevier B.V.

Keywords

Author Keywords: Hybrid MMC 'S; Aluminum alloys; Dry sliding; Wear

Keywords Plus: MATRIX COMPOSITES; TRIBOLOGICAL BEHAVIOR; ABRASIVE

MEAD. MICDOCTDUCTUDE. CADDIDE. DECICAL CDEED. DAC

0

Citations

Create citation alert

54

Cited References View Related Records

You may also like...

Kumar, GRBS; Prakash, SG;

EFFECT OF REINFORCEMENT AND CHILLS ON THE TRIBOLOGICAL BEHAVIOUR OF AL-12% SI/B4C COMPOSITE

IMECE 2008: PROCEEDINGS OF THE ASME INTERNATIONAL MECHANICAL ENGINEERING CONGRESS AND EXPOSITION, VOL 7

Patel, GCM; Pradeep, NB; Shettigar, AK; et al. Experimental analysis and optimization of plasma spray parameters on microhardness and wear loss of Mo-Ni-Cr coated super duplex stainless steel

AUSTRALIAN JOURNAL OF MECHANICAL ENGINEERING

Yang, H; Topping, TD; Schoenung, JM; et al. Tensile behavior and strengthening mechanisms in a submicron B4C-reinforced Al trimodal composite

MATERIALS SCIENCE AND ENGINEERING A-STRUCTURAL MATERIALS PROPERTIES MICROSTRUCTURE AND PROCESSING

Mungara, SR; Manohar, HS; Trishul, MA;

Study of mechanical characteristics of stir ca

AA7050 RAC motal matrix coramic compositos

WEAK, MICKUSTRUCTURE, CARDIDE, DESIGN, SPEED, D4C

Author Information

Corresponding Address: Aabid, Abdul (corresponding author)

Prince Sultan Univ, Coll Engn, Engn Management Dept, POB 66833,

Riyadh 11586, Saudi Arabia

Corresponding Address: Murtuza, Mohammed Ali (corresponding author)

▼ Univ BDT Coll Engn, Dept Mech Engn, Davanagere 577004, Karnataka, India

Addresses:

- ▼ 1 Prince Sultan Univ, Coll Engn, Engn Management Dept, POB 66833, Riyadh 11586, Saudi Arabia
- Univ BDT Coll Engn, Dept Mech Engn, Davanagere 577004, Karnataka, India
- ▼ 3 Int Islamic Univ Malaysia, Fac Engn, Dept Mech Engn, Kuala Lumpur 53100, Malaysia

E-mail Addresses: aaabid@psu.edu.sa; alinvicta83@gmail.com

Categories/Classification

Research Areas: Materials Science; Metallurgy & Metallurgical Engineering

Funding

Funding agency

Structures and Materials (S&M) Research Lab of Prince Sultan

University

Prince Sultan University

Funding Table

View funding text

Document Information

Language: English

Accession Number: WOS:000735333600004

ISSN: 2238-7854 eISSN: 2214-0697

Other Information

IDS Number: XW0QA

See fewer data fields

MATERIALS TODAY-PROCEEDINGS

AATOOO-D4C Metat matrix ceramic composites

Singh, SCE; Selvakumar, N;

Effect of milled B4C nanoparticles on tribological analysis, microstructure and mechanical properties of Cu-4Cr matrix produced by hot extrusion

ARCHIVES OF CIVIL AND MECHANICAL ENGINEERING

See all

Use in Web of Science

Web of Science Usage Count

0

0

Last 180 Days

Since 2013

Learn more

This record is from: Web of Science Core Collection

 Science Citation Index Expanded (SCI-EXPANDED)

Suggest a correction

If you would like to improve the quality of the data in this record, please Suggest a

correction

5.039

Journal

Impact Factor ™

(2020)

Journal information

JOURNAL OF MATERIALS RESEARCH AND TECHNOLOGY-JMR&T

ISSN: 2238-7854 eISSN: 2214-0697

Current Publisher: ELSEVIER, RADARWEG 29, 1043 NX

AMSTERDAM, NETHERLANDS

Journal Impact Factor: Journal Citation Report TM

Research Areas: Materials Science; Metallurgy & Metallurgical

Enginooring



2/24/22, 11:30 AM

Optimization of dry sliding wear behavior of aluminium-based hybrid MMC's using experimental and DOE methods-Web of Scien...

принеения

Web of Science Categories: Materials Science, Multidisciplinary;

Metallurgy & Metallurgical Engineering

| Showing 30 of 54 | View as set of results | | | |
|------------------|------------------------|----|---------------------------------|-------|
| | | (f | rom Web of Science Core Collect | tion) |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |

| | 31 |
|--|----|

Optimization of dry sliding wear behavior of aluminium-based hybrid MMC's using experimental and DOE methods-Web of Scien...

2/24/22, 11:30 AM

| 2/2 | 4/22, 11: | 30 AM | Optimization of dry sliding wear be | ehavior of aluminiu | m-based hybrid MM0 | C's using experiment | al and DOE methods-W | eb of Scien |
|-----|-----------|-------|-------------------------------------|---------------------|--------------------|----------------------|----------------------|-------------|
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | © 2022 | Data | Copyright | Manage | Follow |
| | | | | Clarivate | Correction | Notice | cookie | Us |
| | | | | Training | Privacy | Cookie | preferences | y f |
| | | | | Portal | Statement | Policy | | - 1 |
| | | | | Product | Newsletter | Terms of | | |

Use

Support