

Results for INNOVATIVE US... >

Innovative Use of Crumb Rubber and Silica Fume in Hot Mix Asphalt: A Mate...



MENU



Free Full Text from Publisher

Export ▾

Add To Marked List

< 1 of 1 >

Innovative Use of Crumb Rubber and Silica Fume in Hot Mix Asphalt: A Material Properties Study

By [Bujang, M](#) (Bujang, Mastura) ^{[1], [2]}; [Hui, MTS](#) (Hui, Michelle Ting Sze) ^[2]; [Kam, LW](#) (Kam, Leong Wen) ^{[1], [2]}; [Tat, LY](#) (Tat, Lim Yong) ^{[1], [2]}; [Azahar, WNAW](#) (Azahar, Wan Nur Aifa Wan) ^[3]

[View Web of Science ResearcherID and ORCID](#) (provided by Clarivate)

Source [JURNAL KEJURUTERAAN](#)

← [View Journal Impact](#)

Volume: 38 Issue: 2 Page: 797-808

DOI: 10.17576/jkukm-2026-38(2)-26

Published MAR 2026

Indexed 2026-04-28

Document Type Article

Abstract

A significant percentage of road pavements suffer from cracking and rutting, primarily owing to poor asphalt mixture characteristics and heightened traffic loads. Subsequently, they acquire defects such as creep, fatigue, and rutting. To address these issues, this study explores the use of crumb rubber (recycled tyres) and silica fume (by-product of silicon alloy production) as modifiers for enhancing asphalt performance. Asphalt mixes were prepared with varying amounts of crumb rubber (5-10% by weight of bitumen) and silica fume (5-10% by weight of fine aggregate). Aggregate tests (Aggregate Impact Value Test, Aggregate Crushing Value Test, Los Angeles Abrasion Value Test, and water absorption), bitumen tests (penetration, softening point, and ductility), and mechanical performance tests (resilient modulus, dynamic creep, and Scanning Electron Microscopy analysis) were performed. Results revealed that the mixture containing 10% crumb rubber and 5% silica fume exhibited a 25% increase in resilient modulus and a 30% reduction in permanent strain compared to the conventional mixture. This combination modification method is unique in integrating both crumb rubber and silica fume at optimized levels to enhance the performance for both mechanical and morphological properties simultaneously. It can be concluded that the utilizing of these materials significantly improves pavement lifespan and reduces environmental impact while also improving sustainability and durability.

Keywords

Author Keywords: [Crumb rubber](#); [silica fume](#); [hot mix asphalt](#); [modified asphalt](#); [green pavement](#)

Author Information

Corresponding Address: Bujang, Mastura (corresponding author)
Univ Technol Sarawak, Ctr Res Innovat & Sustainable Dev, Sibul
96000, Sarawak, Malaysia

Corresponding Address: Bujang, Mastura (corresponding author)
Univ Technol Sarawak, Sch Engn & Technol, Sibul
96000, Sarawak, Malaysia

E-mail Addresses :

mastura.bujang@uts.edu.my

Addresses :

¹ Univ Technol Sarawak, Ctr Res Innovat & Sustainable Dev,
Sibul
96000, Sarawak, Malaysia

² Univ Technol Sarawak, Sch Engn & Technol, Sibul
96000,
Sarawak, Malaysia

▼ ³ Int Islamic Univ Malaysia, Dept Civil Engn, Gombak,
Malaysia
E-mail Addresses :
mastura.bujang@uts.edu.my

**Categories/
Classification** Research Areas: Engineering

**Web of Science
Categories** [Engineering, Multidisciplinary](#)

Funding

▼ [View funding text](#)

Funding agency	Grant number	Hide All Details
UTS research grant	4/2023/19 (01)	
Ministry of Higher Education & Scientific Research (MHESR)		Hide details
Appeared in source as: Ministry of Higher Education (MOHE)		
University of Technology Sarawak		

+ [See more data fields](#)

Journal information

[JURNAL KEJURUTERAAN](#)

← [View Journal Impact](#)

ISSN 0128-0198

eISSN 2289-7526

0.6

Journal
Impact
Factor™
(2024)

0.16