

Brought to you by [INTERNATIONAL ISLAMIC UNIVERSITY MALAYSIA](#)



Scopus



[Back](#)

Flowsheet Design and Modelling for High Purity Praseodymium and Neodymium by Solvent Extraction

[Еріткішпен экстракциялау арқылы жоғары тазалықтағы празеодим мен неодимді алудың технологиялық схемасын әзірлеу және модельдеу]

[Разработка и моделирование технологической схемы получения высокочистого празеодима и неодима методом экстракции растворителем]

[Kompleksnoe Ispolzovanie Mineralnogo Syra](#) • Article • [Open Access](#) • 2027 •

DOI: 10.31643/2027/6445.35

[Zulkifli, Norazihan](#)^a ; [Shoparwe, Noor Fazliani](#)^a ; [Yusoff, Abdul Hafidz](#)^a ; [Abdullah A.Z.](#)^b ; [Ahmad, Mohammad Norazmi](#)^c

^a Gold, Rare Earth and Material Technopreneurship Centre (GREAT), Faculty of Bioengineering and Technology, Universiti Malaysia Kelantan, Kelantan, Jeli, 17600, Malaysia

[Show all information](#)

0

Citations

[Full text](#) [Export](#) [Save to list](#)

[Document](#)

[Impact](#)

[Cited by \(0\)](#)

[References \(37\)](#)

[Similar documents](#)

Abstract

Purifying rare earth elements (REEs) from ion-adsorbed clay (IAC) deposits demands complex solvent extraction (SX) setups to achieve commercial-grade purity. This study presents the design and validation of a four-train counter-current SX flowsheet for processing a pre-treated REE chloride liquor sourced from Malaysia's Jeli deposit. Using an iterative steady-state mass-balance simulation in Microsoft Excel, the research determines the operational parameters needed to achieve a 4N

(99.99%) terminal purity target for each REE stream. The methodology involved pinpointing critical A/B separation cuts and optimising the organic-to-aqueous (O/A) ratios across the cascade. The results show that the flowsheet effectively fractionates the feedstock, starting with a bulk LREE/HREE separation (Train 1) and culminating in the challenging separation of praseodymium (Pr) and neodymium (Nd) (Train 4). The simulation identified Pr/Nd separation as the primary technical bottleneck, requiring 62 equilibrium stages (NE) due to a low separation factor (β) of 1.70. In contrast, simpler bulk splits needed as few as 16 stages. These findings confirm the theoretical minimum stage requirements (N_{min}) and provide a detailed stage-wise concentration profile for each train. The study concludes that the Pr/Nd circuit dictates the overall plant footprint and capital intensity. The developed flowsheet offers a solid technical blueprint for commercialising Malaysian IAC resources, ensuring high-purity REE recovery through optimised metallurgical design. © 2027, Institute of Metallurgy and Ore Beneficiation JSC. All rights reserved.

Author keywords

equilibrium curve; extraction stages; P507; REE separation; solvent extraction

Corresponding authors

Corresponding
author

N.F. Shoparwe

Affiliation

Gold, Rare Earth and Material Technopreneurship Centre (GREAT), Faculty of
Bioengineering and Technology, Universiti Malaysia Kelantan, Kelantan, Jeli,
17600, Malaysia

Email address

fazliana.s@umk.edu.my

© Copyright 2026 Elsevier B.V., All rights reserved.

Abstract

Author keywords

Corresponding authors

About Scopus