



Results for FLEXIBLE PET-B... >

Flexible PET-based resistive tactile sensors via a hybrid fabrication approac...



MENU



Free Full Text From Publisher

Export ▾

Add To Marked List ▾

< 1 of 1 >

Flexible PET-based resistive tactile sensors via a hybrid fabrication approach using reduced graphene oxide/silver nanoparticle nanocomposite electrodes and graphene piezoresistive layer

By [Azhar, MIM](#) (Azhar, Muhammad Izzuddin Mohamad) ^[1]; [Ralib, AAM](#) (Ralib, Aliza Aini Md) ^[1]; [Nordin, NHD](#) (Nordin, Nor Hidayati Diyana) ^[2]; [Jaafar, SMHSM](#) (Jaafar, Syed Muhammad Hafiz Syed Mohd) ^[3]; [Kamal, SAA](#) (Kamal, Shafarina Azlinda Ahmad) ^[4]; [Kamaruddin, NH](#) (Kamaruddin, Nurul Hazierah) ^[5]; [Abd Aziz, AS](#) (Abd Aziz, Aiman Sajidah) ^[5]

[View Web of Science ResearcherID and ORCID](#) (provided by Clarivate)

Source [JOURNAL OF MATERIALS SCIENCE-MATERIALS IN ELECTRONICS](#)

[← View Journal Impact](#)

Volume: 37 Issue: 15
DOI: 10.1007/s10854-026-17553-w

Article Number 1212

Published MAY 2026

Early Access MAY 2026

Indexed 2026-06-06

Document Type Article

Jump to [↓ Enriched Cited References](#)

Abstract Precise measurement of force and pressure plays a vital role in human motion monitoring where it widely used in rehabilitation to track grip strength by measuring force distribution generated during movement. Flexible commercial resistive force sensor or so called force sensitive resistors (FSRs) are widely used in wearable electronics for detecting force changes associated with human motion. While commercial FSRs are commonly employed, it lacks adaptability, flexibility and ergonomic fit required in rehabilitation settings. Personalized and custom-made resistive sensors provide tailored sensing range, sensitivity and flexibility to facilitate personalized therapy. Hence, this work explores the new technique for developing a flexible PET-based resistive tactile sensor using a hybrid fabrication approach. The developed sensor consists of the interdigitated electrode, piezoresistive layer, and the gap spacer. The reduced graphene oxide/silver nanoparticle nanocomposite electrodes layer was fabricated using inkjet printing, while the graphene piezoresistive layer was fabricated using stencil printing. The measurement setup consists of dynamic mechanical analysis (DMA) system to analyze the sensing range, sensitivity, response and recovery time, and stability. Measurement result shows a nonlinear response similar to the commercial FSR. The fabricated PET-based resistive tactile sensor achieved fractional change of resistance of 0.35 and reaching saturated resistance at 35 kPa. Low response time and recovery time was also recorded at 164.04 ms and 161.54 ms, respectively. The custom PET-based resistive tactile sensor demonstrated stable performance with minimal variation of output signal when subjected to a constant displacement and load over 400 load cycles at a frequency of 1

Hz. The sensor was tested in a system to detect gripping action by sensing muscle contraction forces from 3 upper forearm muscle groups. Hence, the proposed flexible PET-based resistive tactile sensor using inkjet printable rGO/AgNP nanocomposites conductive ink and graphene ink has high potential to be used for wearable pressure sensing applications.

Keywords

Keywords Plus: FORCE SENSING RESISTORS; OXIDE

Author Information

Corresponding Address Ralib, Aliza Aini (corresponding author)
: Md

▼ Int Islamic Univ Malaysia, Dept Elect & Comp Engr, VLSI MEMS Res Unit, Kulliyyah Engr, Kuala Lumpur 53100, Malaysia
E-mail Addresses :

alizaaini@iium.edu.my

Addresses :

▼ ¹ Int Islamic Univ Malaysia, Dept Elect & Comp Engr, VLSI MEMS Res Unit, Kulliyyah Engr, Kuala Lumpur 53100, Malaysia

▼ ² Int Islamic Univ Malaysia, Dept Mechatron Engr, Kulliyyah Engr, Jalan Gombak, Kuala Lumpur 53100, Malaysia

▼ ³ Univ Teknol PETRONAS, Ctr Innovat Nanostruct & Nanodevices COINN, Seri Iskandar 32610, Perak, Malaysia

▼ ⁴ Univ Malaya, Fac Sci, Low Dimens Mat Res Ctr, Dept Phys, Kuala Lumpur 50603, Malaysia

▼ ⁵ MIMOS Berhad, Semicond R&D, Jalan Inovasi 3, Taman Teknol Malaysia, Kuala Lumpur 57000, Malaysia

E-mail Addresses :

alizaaini@iium.edu.my

Data availability statement

The data that support the findings of this study are available from the corresponding author upon reasonable request.

Conflict of interest statement

The authors declare that they have no known competing financial interests or personal relationships that could have appeared to influence the work reported in this paper.

Categories/ Classification

Research Areas: Engineering; Materials Science; Physics