

[Results for SURFACE ROUG...](#) >

Surface roughness analysis in turning titanium alloy under MQL and cryoge...



MENU



Export ▾

Add To Marked List ▾

< 1 of 1 >

Surface roughness analysis in turning titanium alloy under MQL and cryogenic coolants

By [Sulaiman, MA](#) (Sulaiman, Mohd Amri) ^[1] ; [Salleh, MS](#) (Salleh, Mohd Shukor) ^[1] ; [Khairussaleh, NKM](#) (Khairussaleh, Nor Khairusshima Muhammad) ^[2] ; [Ibrahim, IN](#) (Ibrahim, Ikhwan Nasir) ^[1] ; [Tomadi, SH](#) (Tomadi, Siti Haryani) ^[2] ; [Rizal, M](#) (Rizal, Muhammad) ^[3]

[Are you this author?](#)

[View Web of Science ResearcherID and ORCID](#) (provided by Clarivate)

Source [JURNAL TRIBOLOGI](#)

← [View Journal Impact](#)

Volume: 49 Page: 83-94

Published JUN 2026

Indexed 2026-07-04

Document Type Article

Abstract

Titanium alloys are valued for their high strength-to-weight ratio and thermal stability, making them essential in aerospace and medical applications. However, their poor thermal conductivity and rapid tool wear pose significant challenges to machinability. This study investigates the effects of minimum quantity lubrication (MQL) and cryogenic CO₂ cooling on surface roughness during the turning of titanium alloy (Ti-6Al-4V ELI). Turning operational were conducted on a CNC lathe using uncoated carbide inserts. The cutting parameters were set as follows: cutting speeds of 120, 170, and 220 m/min; feed rates of 0.10, 0.15, and 0.20 mm/rev; and depths of cut of 0.4, 0.5, and 0.6 mm. Surface roughness was measured with a portable Mitutoyo SJ-301 tester over a 20 mm cutting length at three different locations along the machined surface. Response surface methodology (RSM) was applied to analyze the data, assess model accuracy, and identify significant factors. Results showed that MQL consistently produced better surface quality, with feed rate identified as the most influential factor; lower feed rates yielded smoother finishes. These findings emphasize the role of advanced cooling techniques in enhancing machining performance, particularly for aerospace and biomedical applications where high precision is critical.

Keywords

Author Keywords: [Ti-6Al-4V ELI](#); [Turning process](#); [MQL](#); [Cryogenic](#); [Surface roughness](#)

Keywords Plus: [PARAMETERS](#)

Author Information

Corresponding Address: Sulaiman, Mohd (corresponding author) Amri

▼ Univ Teknikal Malaysia Melaka, Fac Ind & Mfg Technol & Engn, Hang Tuah Jaya 76100, Melaka, Malaysia

E-mail Addresses : mohdamri@utem.edu.my

Addresses :

▼ ¹ Univ Teknikal Malaysia Melaka, Fac Ind & Mfg Technol & Engn, Hang Tuah Jaya 76100, Melaka, Malaysia

▼ ² Int Islamic Univ Malaysia, Dept Mfg & Mat Engn, Kulliyah Engn, Gombak 53100, Selangor, Malaysia

▼ ³ Univ Syiah Kuala Darussalam, Fac Engn, Dept Mech Engn, Banda Aceh 23111, Indonesia

E-mail Addresses :