

Full Text from Publisher



Save to EndNote online

Add to Marked List

◀ 1 of 1 ▶

Performance of combined PTFE hydrophilic and hydrophobic membrane during laundry/detergent wastewater treatment by air gap membrane distillation (AGMD): an experimental study

By: Siddique, IJ (Siddique, Istiaq Jamil)^[1]; Bahar, R (Bahar, Rubina)^[2]; Ibrahim, S (Ibrahim, Shaliza)^[3]; Al Hazza, MHF (Al Hazza, Muataz Hazza Faizi)^[1]

DESALINATION AND WATER TREATMENT

Volume: 127 Pages: 255-261

DOI: 10.5004/dwt.2018.22757

Published: SEP 2018

Document Type: Article

[View Journal Impact](#)

Abstract

Membrane distillation (MD) is making a rapid progress in desalination and wastewater treatment research. Though MD produces lower distillate yield compared with other membrane processes, its ability to be used with varieties of renewable and waste energy source coupled to produce ultrapure water makes it a competitive choice. One of the major drawbacks of MD is the fouling and pore wetting of the membrane surface, and therefore modifications to membrane surface characteristics and combining MD with other techniques are necessary for successful rejection of all sorts of organic, inorganic and biological contaminants, except few. One of them is household wastewater containing common laundry detergent sodium dodecylbenzenesulfonate. Although it has been reported that alkaline surfactant causes pore wetting in hydrophobic membranes, but the extent of damage and the severe drop in permeate quality has not been reported. In this work, the preliminary experiments have been carried out with standard laundry wastewater and it has been observed that commercially available hydrophobic polytetrafluoroethylene membrane permits all the constituents of the feed water in presence of small amount of laundry detergent. Complete pore wetting of the membrane makes it reach very high permeate flux (40 L/m² h) and the distillate quality is near to the feed water (>2,400 mu S/cm). A simple technique was developed to prevent pore wetting, by combining hydrophilic and hydrophobic membrane without using any interfacial-bonding agent or crosslinking agent. This simple technique successfully produced pure distillate from feed water containing detergent with a conductivity of 12-20 mu S/cm.

Keywords

Author Keywords: Membrane distillation (MD); Air gap membrane distillation (AGMD); Hydrophilic-hydrophobic membrane; Membrane pore wetting; Laundry/detergent wastewater treatment

KeyWords Plus: BEHAVIOR

Author Information

Reprint Address: Bahar, R (reprint author)

Univ Tunku Abdul Rahman, Dept Mech & Mat Engr, Lee Kong Chian Fac Engr & Sci, Sungai Long 43000, Kajang, Malaysia.

Addresses:

+ [1] Int Islamic Univ Malaysia, Dept Mfg & Mat Engr, Jalan Gombak, Kuala Lumpur 50728, Malaysia

[2] Univ Tunku Abdul Rahman, Dept Mech & Mat Engr, Lee Kong Chian Fac Engr & Sci, Sungai Long 43000, Kajang, Malaysia

+ [3] Univ Malaya, Dept Civil Engr, Kuala Lumpur 50603, Malaysia

E-mail Addresses: jamil@allieditbd.com; rubina@utar.edu.my; shaliza@um.edu.my; muataz@iiium.edu.my

Funding

Funding Agency	Grant Number
Ministry of Higher Education Malaysia through Fundamental Research Grant Scheme	FRGS-14-118-0359
University of Malaya through IIUM-UM Joint Grant	CG015-2014

Citation Network

In Web of Science Core Collection

0

Times Cited

 Create Citation Alert

11

Cited References

[View Related Records](#)

Use in Web of Science

Web of Science Usage Count

2

Last 180 Days

2

Since 2013

[Learn more](#)

This record is from:

Web of Science Core Collection
- Science Citation Index Expanded

Suggest a correction

If you would like to improve the quality of the data in this record, please suggest a correction.

[View funding text](#)**Publisher**

DESALINATION PUBL, 36 WALCOTT VALLEY DRIVE,, HOPKINTON, MA 01748 USA

Categories / Classification

Research Areas: Engineering; Water Resources

Web of Science Categories: Engineering, Chemical; Water Resources

[See more data fields](#)

◀ 1 of 1 ▶

Cited References: 11Showing 11 of 11 [View All in Cited References page](#)

(from Web of Science Core Collection)

- | | | |
|-----|--|------------------|
| 1. | Air gap membrane distillation: A detailed study of high saline solution
By: Alkudhiri, Abdullah; Hilal, Nidal
DESALINATION Volume: 403 Special Issue: SI Pages: 179-186 Published: FEB 1 2017 | Times Cited: 14 |
| 2. | Economic feasibility of on-site greywater reuse in multi-storey buildings
By: Friedler, E; Hadari, M
DESALINATION Volume: 190 Issue: 1-3 Pages: 221-234 Published: APR 15 2006 | Times Cited: 114 |
| 3. | Operational experience of a solar membrane distillation demonstration plant in Pozo Izquierdo-Gran Canaria Island (Spain)
By: Gemma Raluy, R.; Schwantes, Rebecca; Subiela, Vicente J.; et al.
DESALINATION Volume: 290 Pages: 1-13 Published: MAR 30 2012 | Times Cited: 44 |
| 4. | Laundry water recycling in ship by direct nanofiltration with tubular membranes
By: Guilbaud, Julie; Masse, Anthony; Andres, Yves; et al.
RESOURCES CONSERVATION AND RECYCLING Volume: 55 Issue: 2 Pages: 148-154 Published: DEC 2010 | Times Cited: 6 |
| 5. | Title: [not available]
By: Johnson, R. A.; Nguyen, M. H.
Understanding Membrane Distillation and Osmotic Distillation Published: 2017
Publisher: John Wiley and Sons, Hoboken, NJ | Times Cited: 1 |
| 6. | Fouling and crystallisation behaviour of superhydrophobic nano-composite PVDF membranes in direct contact membrane distillation
By: Meng, Suwan; Ye, Yun; Mansouri, Jaleh; et al.
JOURNAL OF MEMBRANE SCIENCE Volume: 463 Pages: 102-112 Published: AUG 1 2014 | Times Cited: 59 |
| 7. | Title: [not available]
By: Millipore, Merck.
FALP14250 & VERBAR; Fluoropore Membrane Filter: Overview
URL: http://www.merckmillipore.com/MY/en/product/Fluoropore-Membrane-Filter,MM_NF-FALP14250# | Times Cited: 1 |
| 8. | Title: [not available]
By: Millipore, Merck.
JHWP14225 & VERBAR; Ominopore Membrane Filter: Overview
URL: https://www.merckmillipore.com/MY/en/product/Ominopore-Membrane-Filter-PTFE-Hydrophilic,MM_NF-JHWP04700# | Times Cited: 1 |
| 9. | Organic fouling behavior in direct contact membrane distillation
By: Naidu, Gayathri; Jeong, Sanghyun; Kim, Sung-Jo; et al.
DESALINATION Volume: 347 Pages: 230-239 Published: AUG 15 2014 | Times Cited: 43 |
| 10. | Application of sodium alginate-carrageenan coatings to PTFE membranes for protection against wet-out by surface-active agents | Times Cited: 5 |

By: Xu, JB; Bartley, JP; Johnson, RA

SEPARATION SCIENCE AND TECHNOLOGY Volume: 40 Issue: 5 Pages: 1067-1081 Published: 2005

11. **Concentration of radioactive components in liquid low-level radioactive waste by membrane distillation**

Times Cited: 55

By: Zakrzewska-Trznadel, G; Harasimowicz, M; Chmielewski, AG

JOURNAL OF MEMBRANE SCIENCE Volume: 163 Issue: 2 Pages: 257-264 Published: NOV 1 1999

Showing 11 of 11 [View All in Cited References page](#)

Clarivate

Accelerating innovation

© 2019 Clarivate [Copyright notice](#) [Terms of use](#) [Privacy statement](#) [Cookie policy](#)

[Sign up for the Web of Science newsletter](#) [Follow us](#)

